

EMG 45-DIO 8E-1N5408 - Diode block



2949389

<https://www.phoenixcontact.com/us/products/2949389>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Diode module, with eight diodes, can be individually wired, diode type 1N 5408

Your advantages

- Electrical decoupling of messages in fault reporting systems
- Spark-suppression diodes for limiting surge voltages of inductive loads

Commercial data

Item number	2949389
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	C440
Product key	CK4M11
Catalog page	Page 266 (C-5-2019)
GTIN	4017918083779
Weight per piece (including packing)	91.84 g
Weight per piece (excluding packing)	91.84 g
Customs tariff number	85411000
Country of origin	DE

EMG 45-DIO 8E-1N5408 - Diode block



2949389

<https://www.phoenixcontact.com/us/products/2949389>

Technical data

Product properties

Product type	Diode module
Insulation characteristics	
Pollution degree	2

Input data

Diode

Description of the input	8 diodes, individually wired
Diode type	1 N 5408
Max. operating voltage U_{\max}	250 V AC
Peak reverse voltage per diode	1000 V
Reverse current per diode	10 μ A
Conducting state voltage per diode	approx. 0.8 V
Conducting state current per diode	1.5 A (with single load)
	0.3 A (with simultaneous loads)

Connection data

Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3
Conductor cross section rigid	0.2 mm ² ... 4 mm ²
Conductor cross section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross section AWG	24 ... 12

Dimensions

Width	45 mm
Height	75 mm
Depth	55 mm

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C

Approvals

CE

Certificate	CE-compliant
Note	and EN 61326

Standards and regulations

EMG 45-DIO 8E-1N5408 - Diode block



2949389

<https://www.phoenixcontact.com/us/products/2949389>

Standards/regulations	DIN EN 50178
-----------------------	--------------

Mounting

Mounting type	DIN rail mounting
Assembly instructions	in rows with zero spacing
Mounting position	any

EMG 45-DIO 8E-1N5408 - Diode block


2949389

<https://www.phoenixcontact.com/us/products/2949389>



Drawings

Circuit diagram



EMG 45-DIO 8E-1N5408 - Diode block



2949389

<https://www.phoenixcontact.com/us/products/2949389>

Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2949389>



EAC

Approval ID: RU*DE*08.B.01841/19

EMG 45-DIO 8E-1N5408 - Diode block



2949389

<https://www.phoenixcontact.com/us/products/2949389>

Classifications

ECLASS

ECLASS-11.0	27371010
ECLASS-12.0	27371010
ECLASS-13.0	27371010

ETIM

ETIM 9.0	EC002278
----------	----------

UNSPSC

UNSPSC 21.0	32151500
-------------	----------

EMG 45-DIO 8E-1N5408 - Diode block



2949389

<https://www.phoenixcontact.com/us/products/2949389>

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

EMG 45-DIO 8E-1N5408 - Diode block



2949389

<https://www.phoenixcontact.com/us/products/2949389>

Accessories

EMG-GKS 12 - Marking material

2947035

<https://www.phoenixcontact.com/us/products/2947035>



Device marking label, width: 12 mm, area: 12 x 8 mm, e.g. for EML(10x7) R adhesive marking material

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com