

EMG 90-DIO 17E - Diode block

2954895

<https://www.phoenixcontact.com/pc/products/2954895>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Diode module, with 17 diodes, individually wired, diode type 1N 4007

Your advantages

- Electrical decoupling of messages in fault reporting systems
- Spark-suppression diodes for limiting surge voltages of inductive loads

Commercial data

Item number	2954895
Packing unit	5 pc
Minimum order quantity	1 pc
Product key	CK4M11
Catalog page	Page 266 (C-5-2019)
GTIN	4017918085179
Weight per piece (including packing)	166.34 g
Weight per piece (excluding packing)	166.34 g
Customs tariff number	85411000
Country of origin	DE

EMG 90-DIO 17E - Diode block

2954895

<https://www.phoenixcontact.com/pc/products/2954895>



Technical data

Product properties

Product type	Diode module
Insulation characteristics	
Pollution degree	2

Input data

Diode	
Description of the input	17 diodes, individually connected
Diode type	1 N 4007
Max. operating voltage $U_{\max}$	250 V AC
Peak reverse voltage per diode	1300 V
Reverse current per diode	5 μ A
Conducting state voltage per diode	approx. 0.8 V
Conducting state current per diode	0.7 A (with single load)
	0.5 A (with simultaneous loads)

Connection data

Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3
Conductor cross section rigid	0.2 mm ² ... 4 mm ²
Conductor cross section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross section AWG	24 ... 12

Dimensions

Width	90 mm
Height	75 mm
Depth	55 mm

Material specifications

Color	green (RAL 6021)
-------	------------------

Environmental and real-life conditions

Ambient conditions	
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C

Approvals

CE	
Certificate	CE-compliant

EMG 90-DIO 17E - Diode block



2954895

<https://www.phoenixcontact.com/pc/products/2954895>

Note	and EN 61326
------	--------------

Standards and regulations

Standards/regulations	DIN EN 50178
-----------------------	--------------

Mounting

Mounting type	DIN rail mounting
Assembly instructions	in rows with zero spacing
Mounting position	any

EMG 90-DIO 17E - Diode block


2954895

<https://www.phoenixcontact.com/pc/products/2954895>



Drawings

Circuit diagram



EMG 90-DIO 17E - Diode block

2954895

<https://www.phoenixcontact.com/pc/products/2954895>



Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/2954895>



EAC

Approval ID: RU*DE*08.B.01841/19

EMG 90-DIO 17E - Diode block



2954895

<https://www.phoenixcontact.com/pc/products/2954895>

Classifications

ECLASS

ECLASS-11.0	27371010
ECLASS-12.0	27371010
ECLASS-13.0	27371010

ETIM

ETIM 9.0	EC002278
----------	----------

UNSPSC

UNSPSC 21.0	32151500
-------------	----------

EMG 90-DIO 17E - Diode block



2954895

<https://www.phoenixcontact.com/pc/products/2954895>

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com