## SD-BR/SC/LA/GY - Socket

2963886

https://www.phoenixcontact.com/us/products/2963886



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Rail-mountable socket, with light indicator, housing color: gray, with screw connection, national version: Pin pattern USA, without UL rating, housing width 45 mm

## Commercial data

Item number	2963886
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	BE76
Product key	BE7614
GTIN	4017918831974
Weight per piece (including packing)	76.01 g
Weight per piece (excluding packing)	75.49 g
Customs tariff number	85366990
Country of origin	GR

# SD-BR/SC/LA/GY - Socket

2963886

https://www.phoenixcontact.com/us/products/2963886



## Technical data

#### **Product properties**

	Product type	Socket
	For country-specific use in	BR
Ele	ectrical properties	
	Nominal voltage U <sub>N</sub>	250 V AC
	Nominal current I <sub>N</sub>	16 A
Co	nnection data	
	Connection method	Screw connection
	Stripping length	8 mm
	Conductor cross section flexible	0.2 mm <sup>2</sup> 2.5 mm <sup>2</sup>
	Conductor cross section rigid	0.2 mm <sup>2</sup> 4 mm <sup>2</sup>
	Cross section AWG	30 12
	Screw thread	M3

#### Signaling

Status display Glow lamp or LED with preresistor	
--	--

#### Dimensions

Width	45 mm
Height	75 mm
Depth	70.5 mm

#### Material specifications

Color	gray
Insulating material	PA
Contact material	CuZn37

#### Environmental and real-life conditions

Ambient conditions	
Degree of protection	IP20
Ambient temperature (operation)	-20 °C 60 °C
Ambient temperature (storage/transport)	-20 °C 60 °C

#### Mounting

Connection method	Screw connection




2963886 https://www.phoenixcontact.com/us/products/2963886



Drawings

Circuit diagram





2963886

https://www.phoenixcontact.com/us/products/2963886



## Environmental product compliance

REACh SVHC	Lead 7439-92-1 Hexahydromethylphthalic anhydride
China RoHS	
China RoHS	Environmentally Friendly Use Period = 50 years

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com