#### 2966812

https://www.phoenixcontact.com/us/products/2966812

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Commercial data

Item number	2966812
Packing unit	50 pc
Minimum order quantity	50 pc
Sales key	C461
Product key	CK62Z1
Catalog page	Page 426 (C-5-2019)
GTIN	4017918130633
Weight per piece (including packing)	0.45 g
Weight per piece (excluding packing)	0.403 g
Customs tariff number	85366990
Country of origin	DE



Single plug-in bridge, number of positions: 2, length: 6 mm, color: blue

2966812

https://www.phoenixcontact.com/us/products/2966812



## Technical data

Product type     Bridge       Number of positions     2       Electrical properties     6 A       Maximum load current     6 A       Vertical according to UL 94     6 mm	Product properties				
Electrical properties   Maximum load current   6 A   Connection data   Maximum load current   6 A   Dimensions   Length   6 mm	Product type	Bridge			
Maximum load current       6 A         Connection data       6 A         Maximum load current       6 A         Dimensions       6 mm         Length       6 mm         Material specifications       5 mm         Color       blue	Number of positions	2			
Connection data   Maximum load current   6 A   Dimensions   Length   6 mm     Naterial specifications   Color   blue	Electrical properties				
Maximum load current       6 A         Dimensions       Implementation         Length       6 mm         Material specifications       6 mm         Color       blue	Maximum load current	6 A			
Dimensions       Length       6 mm       Material specifications       Color     blue	Connection data				
Length     6 mm       Material specifications     6 mm       Color     blue	Maximum load current	6 A			
Material specifications Color blue	Dimensions				
Color blue	Length	6 mm			
	Material specifications				
Flammability rating according to UL 94 V0	Color	blue			
	Flammability rating according to UL 94	VO			



2966812

https://www.phoenixcontact.com/us/products/2966812

### Approvals

🌣 To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/2966812



CULus Listed
 Approval ID: E199827

2966812

https://www.phoenixcontact.com/us/products/2966812



### Classifications

#### ECLASS

ECLASS-11.0	27141140
ECLASS-12.0	27141140
ECLASS-13.0	27371692

#### ETIM

	ETIM 9.0	EC002586		
UN	UNSPSC			
	UNSPSC 21.0	39121400		

2966812

https://www.phoenixcontact.com/us/products/2966812

## Environmental product compliance

#### EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com