

PLC-BSP- 12DC/21 - Relay base

2967426

<https://www.phoenixcontact.com/pc/products/2967426>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



6.2 mm PLC basic terminal block with spring-cage connection, without relay or solid-state relay, for mounting on DIN rail NS 35/7,5, 1 changeover contact, input voltage 12 V DC

Commercial data

Item number	2967426
Packing unit	10 pc
Minimum order quantity	1 pc
Sales key	08
Product key	CK6221
GTIN	4017918165291
Weight per piece (including packing)	26.06 g
Weight per piece (excluding packing)	25.69 g
Customs tariff number	85366990
Country of origin	DE

PLC-BSP- 12DC/21 - Relay base

2967426

<https://www.phoenixcontact.com/pc/products/2967426>



Technical data

Notes

Utilization restriction

EMC note	EMC: class A product, see manufacturer's declaration in the download area
----------	---

Product properties

Product family	PLC-INTERFACE
Application	Universal
Set comprises	2967439 PLC-RSP- 12DC/21 2967442 PLC-RSP- 12DC/21AU
Operating mode	100% operating factor
Compatible components	Miniature relay, REL-MR-12DC/21AU, REL-MR-12DC/21

Electrical properties

Protective circuit	Damping diode, polarity protection diode
--------------------	--

Input data

Nominal input voltage U_N	12 V DC
Protective circuit	Freewheeling diode

Output data

Compatible components	Miniature relay, REL-MR-12DC/21AU, REL-MR-12DC/21
-----------------------	---

Connection data

Input side

Connection method	Spring-cage connection
Stripping length	8 mm
Conductor cross section rigid	0.14 mm ² ... 2.5 mm ²
Conductor cross section flexible	0.14 mm ² ... 2.5 mm ²
Conductor cross section AWG	26 ... 14

Output side

Connection method	Spring-cage connection
Stripping length	8 mm
Conductor cross section rigid	0.14 mm ² ... 2.5 mm ²
Conductor cross section flexible	0.14 mm ² ... 2.5 mm ²
Conductor cross section AWG	26 ... 14

Signaling

Status display	LED
----------------	-----

Dimensions

PLC-BSP- 12DC/21 - Relay base



2967426

<https://www.phoenixcontact.com/pc/products/2967426>

Width	6.2 mm
Height	80 mm
Depth	94 mm

Material specifications

Color	green (RAL 6021)
Flammability rating according to UL 94	V0 (Housing)

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-40 °C ... 60 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C

Mounting

Mounting type	DIN rail mounting
Assembly note	in rows with zero spacing
Mounting position	any

PLC-BSP- 12DC/21 - Relay base

2967426

<https://www.phoenixcontact.com/pc/products/2967426>



Classifications

ECLASS

ECLASS-11.0	27371603
-------------	----------

PLC-BSP- 12DC/21 - Relay base



2967426

<https://www.phoenixcontact.com/pc/products/2967426>

Environmental product compliance

China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com