

2977487

https://www.phoenixcontact.com/us/products/2977487

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Side element, left, with foot, width: 5 mm, length: 72 mm, for mounting on NS 32 or NS 35/7.5



Your advantages

- · Easy installation
- · Flexible size and shape
- Inexpensive as a result of reducing the number of separate housing parts

Commercial data

| Item number | 2977487 |
|--------------------------------------|---------------|
| Packing unit | 10 pc |
| Minimum order quantity | 10 pc |
| Sales key | AC13 |
| Product key | ACHDBA |
| GTIN | 4017918281465 |
| Weight per piece (including packing) | 6.37 g |
| Weight per piece (excluding packing) | 6.42 g |
| Customs tariff number | 39269097 |
| Country of origin | PL |



2977487

https://www.phoenixcontact.com/us/products/2977487

Technical data

Product properties

| Product type | Panel mounting base side part |
|------------------------------|-------------------------------|
| Product family | UM72 |
| Housing series | UM |
| Туре | Lateral element (left) |
| Housing type | Press-drawn section housings |
| Ventilation openings present | no |

Dimensions

| Width | 5 mm |
|--------|---------|
| Height | 89.6 mm |
| Depth | 37.6 mm |

Material specifications

| Color (Housing) | black (RAL 9005) |
|--|------------------|
| Flammability rating according to UL 94 | V0 |
| Surface characteristics | untreated |

Environmental and real-life conditions

Ambient conditions

| Ambient temperature (operation) | -40 °C 105 °C (depending on power dissipation) |
|---|--|
| Ambient temperature (storage/transport) | -40 °C 55 °C |
| Ambient temperature (assembly) | -5 °C 100 °C |
| Relative humidity (storage/transport) | 80 % |

Mounting

| Mounting type D | DIN rail mounting |
|-----------------|-------------------|
|-----------------|-------------------|



2977487

https://www.phoenixcontact.com/us/products/2977487

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/2977487



UL RecognizedApproval ID: FILE E 240868



2977487

https://www.phoenixcontact.com/us/products/2977487

Classifications

UNSPSC 21.0

ECLASS

| | ECLASS-11.0 | 27182701 |
|------|-------------|----------|
| | ECLASS-13.0 | 27190602 |
| ETIM | | |
| | ETIM 8.0 | EC002779 |
| UN | ISPSC | |

31261500



2977487

https://www.phoenixcontact.com/us/products/2977487

Environmental product compliance

EU RoHS

| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|---|--|
| China RoHS | |
| Environment friendly use period (EFUP) | EFUP-E |
| | No hazardous substances above the limits |
| EU REACH SVHC | |
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com