

Switched interlocked socket-outlet IP67 16-32 A

Enclosure : Thermoplastic
 Cable entry : Knock-out Ø25mm
 Cable area for 16A : 1.5 - 4 mm²
 Cable area for 32A : 2.5 - 10 mm²

Terminals/ Poles	Type	Earthing position	Color code	Voltage V	Frequency Hz	Order Code	Pack. Qty	Weight kg/pce	Rated Current
2P+E	216MVS4W	4h	Yellow	100-130	50/60	2CMA167823R1000	1	0.63	16
2P+E	216MVS6W	6h	Blue	200-250	50/60	2CMA167824R1000	1	0.63	16
3P+E	316MVS6W	6h	Red	380-415	50/60	2CMA167832R1000	1	0.67	16
3P+N+E	416MVS6W	6h	Red	346-415	50/60	2CMA167842R1000	1	0.70	16
2P+E	232MVS4W	4h	Yellow	100-130	50/60	2CMA167870R1000	1	0.69	32
2P+E	232MVS6W	6h	Blue	200-250	50/60	2CMA167871R1000	1	0.69	32
3P+E	332MVS6W	6h	Red	380-415	50/60	2CMA167879R1000	1	0.72	32
3P+N+E	432MVS6W	6h	Red	346-415	50/60	2CMA167888R1000	1	0.76	32

Dimensions

