



PRODUCT-DETAILS

Sentry SSR32

Sentry SSR32 Safety relay



General Information	
Extended Product Type	Sentry SSR32
Product ID	2TLA010052R0400
EAN	7350024483321
Catalog Description	Sentry SSR32 Safety relay
Long Description	Sentry SSR32 Safety relay with relay outputs 2NO+2 delayed NO, +24 VDC supply voltage and screw terminals.
	For monitoring of safety devices with contacts, 1 or 2 equivalent channels, and safety devices with OSSD outputs.
	Manual or automatic reset selectable by switch on front. The two delayed NO relay outputs have an OFF-delay time of 0,5 second.
	Sentry safety relays cover various types of safety applications up to PLe / SIL3. Basic models provide reliable supervision of simpler safety functions, while universal models provide advanced features and high flexibility.
	Models with display offer preset configurations and extensive information to further simplify troubleshooting.
Additional variants offer a high accuracy timer function of ± 1% and an adjustable time setting range from 0-999 s.	
High output current capacity of up to 6 A can save the use of an intermediary contactor.	
Multi-reset allows up to 10 safety relays connected to one reset light-button.	
All models are available with detachable push-in or screw terminals. Terminals and coding kit to mark removed terminals are available as accessories.	

Ordering	
EAN	7350024483321
Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads	
Data Sheet, Technical Information	2TLC010037L0201
Instructions and Manuals	2TLC010067M0201
CAD Dimensional Drawing	2CDC001079B0201
Dimension Diagram	2TLC010001U0201
Wiring Diagram	2TLC010011T0001
Marketing Video	2TLC010019N0201 2TLC010018N0201

Dimensions	
Product Net Width	22.5 mm
Product Net Height	120 mm
Product Net Depth / Length	120 mm
Product Net Weight	0.207 kg

Technical	
Function	Safety relay for monitoring of safety devices
Sub-Function	Start/test input, Manual/Auto reset selectable by switch
Timer Relay Type	OFF-Delay
Time Range	0.5 second
Rated Control Supply Voltage (U _s)	24 V DC
Rated Operational Current AC-15 (I _ø)	3 A
Rated Operational Current DC-13 (I _ø)	3 A
Degree of Protection	IP20
Connecting Capacity	Crimped Pin 1x0.2...3.3 mm² Crimped Pin 2x0.2...1.5 mm² Flexible with Ferrule 1x0.2...3.3 mm² Flexible with Ferrule 2x0.2...1.5 mm² Solid 1x0.2...3.3 mm² Solid 2x0.2...1.5 mm²
Tightening Torque	0.7 N·m
Wire Stripping Length	6.5 mm
Recommended Screw Driver	M3.5
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Standards	ISO 13849

Technical UL/CSA	
Connecting Capacity UL/CSA	Crimped Pin 1x 24-12 AWG Crimped Pin 2x 24-16 AWG Flexible with Ferrule 1x 24-12 AWG Flexible with Ferrule 2x 24-16 AWG Solid 1x 24-12 AWG Solid 2x 24-16 AWG

Environmental

Ambient Air Temperature

Operation -25 ... +65 °C

Storage -40 ... +70 °C

Material Compliance

Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658

REACH Declaration 2CMT2022-006480

RoHS Information 2CMT2022-006499

RoHS Status Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Toxic Substances Control Act - TSCA 2CMT2023-006522

Certificates and Declarations

CQC Certificate CQC2017010303977544

cUL Certificate 2TLC010006D0201

cULus Certificate 2TLC010007D0201

Declaration of Conformity - CCC 2020980303000244

Declaration of Conformity - CE 2TLC010010D0201

Declaration of Conformity - UKCA 2TLC010190D0201

KC Certificate 2TLC010048D0201

TÜV Certificate 2TLC010008D0201

Container Information

Package Level 1 Units box 1 piece

Package Level 1 Width 125 mm

Package Level 1 Depth / Length 31 mm

Package Level 1 Height 129 mm

Package Level 1 Gross Weight 0.268 kg

Package Level 1 EAN 7350024483321

Package Level 2 Units 36 piece

Package Level 2 Width 280 mm

Package Level 2 Depth / Length 395 mm

Package Level 2 Height 210 mm

Package Level 2 Gross Weight 9.9 kg

External Classifications and Standards

Object Classification Code K

ETIM 7 EC001449 - Device for monitoring of safety-related circuits

ETIM 8 EC001449 - Device for monitoring of safety-related circuits

ETIM 9 EC001449 - Device for monitoring of safety-related circuits

eClass V11.0 : 27371819

UNSPSC 39122331

E-Number (Finland) 2712526

E-Number (Sweden)

3860823

Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
2TLA010099R0000	Sentry S30A Terminal block	Sentry S30A	1	piece
2TLA010099R0100	Sentry S30B Coding kit	Sentry S30B	1	piece
2TLA010099R0001	Sentry S30C Terminal block	Sentry S30C	1	piece

Categories

Low Voltage Products and Systems → Control Products → Electronic Relays and Controls → Safety Relays → Single Function Safety Relays

Low Voltage Products and Systems → Control Products → Safety Products → Safety Relays → Single Function Safety Relays

