Pluto D45



PRODUCT-DETAILS

Pluto D45

Pluto D45 Programmable safety controller



,360

General Information	
Extended Product Type	Pluto D45
Product ID	2TLA020070R6600
EAN	7320500410646
Catalog Description	Pluto D45 Programmable safety controller
	Pluto is a cost effective, powerful and compact safety PLC for all machine safety applications. Most safety devices on the market can be connected directly to Pluto and multiple safety sensors can be connected to a single input and still achieve the highest safety level. Programming is done easily in the accompanying software Pluto Manager.
Long Description	Safety PLC with Pluto safety bus and analogue inputs. Totally 45 I/O: 8 combined

Safety PLC with Pluto safety bus and analogue inputs. Totally 45 I/O: 8 combined failsafe analogue and digital inputs + 16 failsafe inputs + 15 non-failsafe outputs/failsafe inputs + 4 individually failsafe relay outputs + 2 individually failsafe transistor outputs. Analogue input range 0-10V/4-20mA.

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	8536411090
Product Main Type	Pluto
Product Name	Programmable safety controller

Pluto D45 2/4

Popular Downloads	
Data Sheet, Technical Information	2TLC010035L0201
Data Sheet, Technical Information (Part 2)	2TLC172227D0201
Instructions and Manuals	2TLC172001M0210
CAD Dimensional Drawing	2CDC001079B0201
Marketing Video	2TLC010032N0201 2TLC010018N0201

Dimensions	
Product Net Depth / Length	120 mm
Product Net Height	84 mm
Product Net Width	90 mm
Product Net Weight	0.65 kg

Safety Information	
Performance Level (PL)	Up to e
Safety Integrity Level	1
(SIL)	2
	3

Technical	
Diagnostic Coverage	High
Number of Inputs	Analog (0 10 V / 4 20 mA) 8 Counter 4 Failsafe 39
Number of Outputs	Failsafe (Transistor) 2 Failsafe (Relay) 4 Non-Failsafe 15
Protocol Type	MODBUS ASCII, Pluto Safety Bus, StatusBus
Rated Control Supply Voltage (U _s)	24 V DC
Supply Voltage	24 V DC

Material Compliance	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2022-006480
RoHS Information	2CMT2022-006499
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances	2CMT2023-006522
Control Act - TSCA	
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Pluto D45 3/4

Certificates and Declarations	
CQC Certificate	No declaration needed
Declaration of Conformity - CCC	No declaration needed
Declaration of Conformity - CE	2TLC172011D0202
Declaration of Conformity - UKCA	2TLC010187D0201
TÜV Certificate	2TLC172005D0201

Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	90 mm
Package Level 1 Depth / Length	130 mm
Package Level 1 Height	105 mm
Package Level 1 Gross Weight	0.7 kg
Package Level 1 EAN	7320500410646

External Classifications and Standards	
eClass	V11.0 : 27242207
ETIM 7	EC000236 - PLC CPU-module
ETIM 8	EC000236 - PLC CPU-module
ETIM 9	EC000236 - PLC CPU-module
IDEA Granular Category Code (IGCC)	3561 >> Programmable Logic Controller Module
UNSPSC	32151705
Object Classification Code	К
E-Number (Finland)	2712237
E-Number (Sweden)	3860082

Categories

 $Low\ Voltage\ Products\ \rightarrow\ Control\ Products\ \rightarrow\ Safety\ Products\ \rightarrow\ Programmable\ Safety\ Controllers\ \rightarrow\ Pluto\ Products\ \rightarrow\ Programmable\ Safety\ Controllers\ \rightarrow\ Pluto\ Products\ \rightarrow\ Products\ \rightarrow\$

Pluto D45 4/4









360