

Catalog No. 2TLA050007R1512

Description: MKEY9, SOL NPT, 24V SS FLEX KEY

UPC No 804325832106

Home > Machine Safety > Safety Sensors, Switches, Locks & Gate Boxes

Mechanical Solenoid Safety interlock switch, rugged polyester housing and stainlesss steel head, spring lock (power to unlock), 1800N holding force. 24VDC coil, 2NC+ 1NO(locked)+2NC+ 1NO (actuator inserted). 1x 1/2NPT conduit entry. Delivered with stainless steel flex key.

Descriptors	
Category	Safety Sensors, Switches, Locks & Gate Boxes
Туре	Safety Lock
6 10 11	

Specifications		
Product Class	Safety Locks & Process Locks	
Product Main Type	MKey	
Supply Voltage	24VDC	
Outputs	Contact	
Number of Outputs	2NC + 2NO	
Degree of Protection	IP67	

Classifications	
ETIM 4	EC002593 - Position switch with interlocking
ETIM 5.0	EC002593 - Position switch with interlocking
ETIM 6.0	EC002593 - Position switch with interlocking
ETIM 7	EC002593 - Position switch with guard locking
ETIM 8 (Etim8)	EC002593 - Position switch with guard locking

Dimensions		
Product Net Depth / Length	46 mm	
Product Net Height	160 mm	
Product Net Width	46 mm	
Product Net Weight	0.603kg	

Safety Information	
Performance Level	Up to e



Created on: 06/09/2025