

## Catalog No. 2TLA050011R1224

Description: MKEY8Z, SS SOL NPT, 230V FLAT KEY

UPC No 804325833332

Home > Machine Safety > Safety Sensors, Switches, Locks & Gate Boxes

Mechanical Solenoid Safety interlock switch, stainless steel housing and head, spring lock (power to unlock), 2000N holding force. 230VAC coil, 2NC+ 1NO(locked)+2NC+ 1NO (actuator inserted). 3x 1/2NPT conduit entries. Delivered with flat key.

Descriptors	
Category	Safety Sensors, Switches, Locks & Gate Boxes
Туре	Safety Lock
Specifications	
Product Class	Safety Locks & Process Locks
Product Main Type	MKey
Supply Voltage	230VAC
Outputs	Contact
Number of Outputs	4NC + 2NO
Degree of Protection	IP67, IP69K
	ECONOTION
ETIM 4	EC002593 - Position switch with interlocking
ETIM 5.0	EC002593 - Position switch with interlocking
ETIM 5.0 ETIM 6.0	EC002593 - Position switch with interlocking EC002593 - Position switch with interlocking
ETIM 5.0	EC002593 - Position switch with interlocking
ETIM 5.0 ETIM 6.0 ETIM 7	EC002593 - Position switch with interlocking EC002593 - Position switch with interlocking EC002593 - Position switch with guard locking
ETIM 5.0 ETIM 6.0 ETIM 7 ETIM 8 (Etim8)  Dimensions	EC002593 - Position switch with interlocking EC002593 - Position switch with interlocking EC002593 - Position switch with guard locking
ETIM 5.0 ETIM 6.0 ETIM 7 ETIM 8 (Etim8)  Dimensions Product Net Depth / Length	EC002593 - Position switch with interlocking EC002593 - Position switch with interlocking EC002593 - Position switch with guard locking EC002593 - Position switch with guard locking
ETIM 5.0 ETIM 6.0 ETIM 7 ETIM 8 (Etim8)	EC002593 - Position switch with interlocking EC002593 - Position switch with interlocking EC002593 - Position switch with guard locking EC002593 - Position switch with guard locking  47 mm



Created on: 06/25/2025

Up to e

Catalog No. 2TLA050011R1224

Performance Level