

## Catalog No. 2TLA050011R1443

Description: MKEY8, SOL NPT, 110V MET. FLEX KEY

UPC No 804325833479

Home > Machine Safety > Safety Sensors, Switches, Locks & Gate Boxes

Mechanical Solenoid Safety interlock switch, die cast housing and stainless steel head, spring lock (power to unlock), 2000N holding force. 110VAC coil, 2NC+ 1NO(locked)+2NC+ 1NO (actuator inserted). 3x 1/2NPT conduit entries. Delivered with metal flex key.

_	
Category	Safety Sensors, Switches, Locks & Gate Boxes
<sup>Т</sup> уре	Safety Lock
pecifications	
Product Class	Safety Locks & Process Locks
roduct Main Type	MKey
upply Voltage	110VAC
utputs	Contact
lumber of Outputs	4NC + 2NO
Degree of Protection	IP67
TIM 4 TIM 5.0 TIM 6.0 TIM 7	EC002593 - Position switch with interlocking EC002593 - Position switch with interlocking EC002593 - Position switch with interlocking EC002593 - Position switch with guard locking
ГІМ 5.0 ГІМ 6.0 ГІМ 7	EC002593 - Position switch with interlocking EC002593 - Position switch with interlocking
TIM 5.0 TIM 6.0 TIM 7 TIM 8 (Etim8)	EC002593 - Position switch with interlocking EC002593 - Position switch with interlocking EC002593 - Position switch with guard locking
TIM 5.0 TIM 6.0 TIM 7 TIM 8 (Etim8)	EC002593 - Position switch with interlocking EC002593 - Position switch with interlocking EC002593 - Position switch with guard locking
TIM 5.0 TIM 6.0 TIM 7 TIM 8 (Etim8) TIM 8 (Etim8) TIM 8 Depth / Length	EC002593 - Position switch with interlocking EC002593 - Position switch with interlocking EC002593 - Position switch with guard locking EC002593 - Position switch with guard locking
TIM 5.0 TIM 6.0	EC002593 - Position switch with interlocking EC002593 - Position switch with interlocking EC002593 - Position switch with guard locking EC002593 - Position switch with guard locking

Up to e



Performance Level