

Catalog No. 2TLA050011R2132

Description: MKEY8, SOL QC, 24V STD. KEY

UPC No 804325629805

Home > Machine Safety > Safety Sensors, Switches, Locks & Gate Boxes

Mechanical Solenoid Safety interlock switch, die cast housing and head, spring lock (power to unlock), 2000N holding force. 24VDC coil, 2NC+ 1NO(locked)+2NC+ 1NO (actuator inserted). QC M23 quick connect. Delivered with standard key.

| Descriptors | |
|-------------|--|
| Category | Safety Sensors, Switches, Locks & Gate Boxes |
| Туре | Safety Lock |
| | |

| Specifications | | |
|----------------------|------------------------------|--|
| Product Class | Safety Locks & Process Locks | |
| Product Main Type | MKey | |
| Supply Voltage | 24VDC | |
| Outputs | Contact | |
| Number of Outputs | 4NC + 2NO | |
| Degree of Protection | IP67 | |

| Classifications | |
|-----------------|---|
| ETIM 4 | EC002593 - Position switch with interlocking |
| ETIM 5.0 | EC002593 - Position switch with interlocking |
| ETIM 6.0 | EC002593 - Position switch with interlocking |
| ETIM 7 | EC002593 - Position switch with guard locking |
| ETIM 8 (Etim8) | EC002593 - Position switch with guard locking |

| Dimensions | | |
|----------------------------|--------|--|
| Product Net Depth / Length | 47 mm | |
| Product Net Height | 176 mm | |
| Product Net Width | 46 mm | |
| Product Net Weight | 0.78kg | |

| Safety Information | |
|--------------------|---------|
| Performance Level | Up to e |



Created on: 06/25/2025