

Catalog No. 2TLA050013R1144

Description: MKEY8M, SOL NPT, 230V STD. KEY

UPC No 804325834414

Home > Machine Safety > Safety Sensors, Switches, Locks & Gate Boxes

Mechanical Solenoid Safety interlock switch, die cast housing and stainless steel head, electro-magnetic lock (power to lock), 2000N holding force. 230VAC coil, 2NC(locked)+2NC(actuator inserted). 3x 1/2NPT conduit entries. Delivered with standard key.

Descriptors	
Category	Safety Sensors, Switches, Locks & Gate Boxes
Туре	Process Lock
Specifications	
Product Class	Safety Locks & Process Locks
Product Main Type	МКеу
Supply Voltage	230VAC
Outputs	Contact
Number of Outputs	3NC + 1NO
Degree of Protection	IP67
ETIM 4	EC002593 - Position switch with interlocking
ETIM 4	EC002593 - Position switch with interlocking
ETIM 5.0	EC002593 - Position switch with interlocking
ETIM 6.0	EC002593 - Position switch with interlocking
ETIM 7	EC002593 - Position switch with guard locking
ETIM 8 (Etim8)	EC002593 - Position switch with guard locking
Dimensions	
Product Net Depth / Length	47 mm
Product Net Height	176 mm
Product Net Width	46 mm
Product Net Weight	0.74kg
Safety Information	
Performance Level	Up to e



Created on: 06/26/2025