

## Catalog No. 2TLA050013R1533

Description: MKEY8M, SOL NPT, 110V SS FLEX KEY

UPC No 804325834551

Home > Machine Safety > Safety Sensors, Switches, Locks & Gate Boxes

Mechanical Solenoid Safety interlock switch, die cast housing and head, electro-magnetic lock (power to lock), 2000N holding force. 110VAC coil, 2NC(locked) + 2NC(actuator inserted). 3x 1/2NPT conduit entries. Delivered with stainless steel flex key.

Descriptors	
Category	Safety Sensors, Switches, Locks & Gate Boxes
Type	Process Lock
-71	1
Specifications	
Product Class	Safety Locks & Process Locks
Product Main Type	МКеу
Supply Voltage	110VAC
Outputs	Contact
Number of Outputs	3NC + 1NO
Degree of Protection	IP67
Classifications ETIM 4	EC002593 - Position switch with interlocking
ETIM 5.0	EC002593 - Position switch with interlocking
ETIM 6.0	EC002593 - Position switch with interlocking
ETIM 7	EC002593 - Position switch with guard locking
ETIM 8 (Etim8)	EC002593 - Position switch with guard locking
Dimensions	
Product Net Depth / Length	47 mm
Product Net Height	176 mm
Product Net Width	46 mm
Product Net Weight	0.74kg
Safety Information	



Created on: 06/13/2025

electrification.us.abb.com