

Catalog No. 2TLA050015R1434

Description: MKEY8ER SOL NPT 230V MET.FLX KEY

UPC No 804325835428

Home > Machine Safety > Safety Sensors, Switches, Locks & Gate Boxes

Mechanical Solenoid Safety interlock switch with escape release, die cast housing and head, electro-magnetic lock (power to lock), 2000N holding force. 230VAC coil, 2NC+ 1NO(locked)+2NC+ 1NO (actuator inserted). 3x 1/2NPT conduit entries. Delivered with metal flex key.

Descriptors	
Category	Safety Sensors, Switches, Locks & Gate Boxes
Туре	Safety Lock

Specifications		
Product Class	Safety Locks & Process Locks	
Product Main Type	MKey	
Supply Voltage	230VAC	
Outputs	Contact	
Number of Outputs	4NC + 2NO	
Degree of Protection	IP67	

Classifications	
ETIM 4	EC002593 - Position switch with interlocking
ETIM 5.0	EC002593 - Position switch with interlocking
ETIM 6.0	EC002593 - Position switch with interlocking
ETIM 7	EC002593 - Position switch with guard locking
ETIM 8 (Etim8)	EC002593 - Position switch with guard locking

Dimensions		
Product Net Depth / Length	120 mm	
Product Net Height	176 mm	
Product Net Width	46 mm	
Product Net Weight	0.79kg	

Safety Information	
Performance Level	Up to e



Created on: 07/04/2025