Sense7Z 5M 1/4



PRODUCT-DETAILS

## Sense7Z 5M Sense7Z 5M Sensor



**360**°

General Information	
Extended Product Type	Sense7Z 5M
Product ID	2TLA050056R5120
EAN	7350024466737

Safety magnetic switch complete with actuator, 2NC+1NO (guard closed and actuator present), stainless steel, LED, 5m cable (8 leads).

Long Description

Catalog Description

Sense7 is a coded magnetic non-contact switch for interlocking gates and hatches, or other moveable parts. Sense7 has a stainless steel housing that is designed for harsh environments and extreme temperatures. Sense7 offers an interlocking function reaching up to PL e/SIL3 with low level coding.

+105°C is accepted for short duration during CIP/SIP cleaning.

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	8536500500
Product Main Type	Sense
Product Name	Sensor
Function	Safety magnetic switch for interlocking gates and hatches - Complete

Sense7Z 5M 2/4

Status Indicator		Yes
Popular Downloada		
Popular Downloads  Data Sheet, Technical		2TLC010001C0202
Information		
Instructions and Manuals		2TLC172249M0201
CAD Dimensional Drawing		2CDC001079B0201
Marketing Video		2TLC010018N0201
<u>Dimensions</u>		
Product Net Depth / Length		14 mm
Product Net Height		50 mm
Product Net Width		88 mm
Product Net Weight		0.438 kg
Safety Information		
Certification Agency		cCSAus
Safety Category		4
Performance Level (PL)		Up to e
Safety Integrity Level (SIL)		3
Technical		
Communication Interface		PNP
Connection Configuration		Cable, 5 m
Minimum Switching		10 VDC 1mA
Capacity Number of Outputs		Failsafe (Transistor) 3
Operating Distance (S <sub>n</sub> )		5 mm
Probability of Dangerous		2.6 10 <sup>-8</sup> hour
Failure per Hour (PFDH)		
Rated Control Supply Voltage (U <sub>s</sub> )		24 V DC
Technical UL/CSA		
Enclosure Type UL/CSA		1
Environmental		
Ambient Air Temperature		Operation -25 +70 °C
Degree of Protection		IP67
Material		IP69K Housing: Stainless steel 316
		Coating housing: Uncoated
Material Compliance		
Conflict Minerals Reporting Template (CMRT)		9AKK108467A5658
© 2024 ABB All rights reserved	2024/12/03	Subject to change

Sense7Z 5M 3/4

REACH Declaration	2CMT2022-006480
RoHS Information	2CMT2022-006499
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	2CMT2023-006522
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations	
cULus Certificate	2TLC010041D0201
Declaration of Conformity - CCC	No declaration needed
Declaration of Conformity - CE	2TLC010060D0201
Declaration of Conformity - UKCA	2TLC010184D0201
TÜV Certificate	2TLC172125D0201
UL Certificate	2TLC010041D0201

Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	77 mm
Package Level 1 Depth / Length	103 mm
Package Level 1 Height	192 mm
Package Level 1 Gross Weight	500 g
Package Level 1 EAN	7350024466737

Classifications	
eClass	V11.0 : 27272402
ETIM 7	EC002544 - Magnetic proximity switch
ETIM 8	EC002544 - Magnetic proximity switch
ETIM 9	EC002544 - Magnetic proximity switch
IDEA Granular Category Code (IGCC)	6147 >> Non contact sensors
UNSPSC	41111916
Object Classification Code	<u>B</u>
E-Number (Sweden)	3861452

## Categories

Sense7Z 5M 4/4

