

FBSR 4-8 - Plug-in bridge

3000585

<https://www.phoenixcontact.com/sg/products/3000585>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Plug-in bridge, pitch: 8.2 mm, number of positions: 4, color: red

Commercial data

| | |
|--------------------------------------|---------------------|
| Item number | 3000585 |
| Packing unit | 10 pc |
| Minimum order quantity | 10 pc |
| Sales key | ***** |
| Product key | BE2Z2X |
| Catalog page | Page 110 (C-1-2019) |
| GTIN | 4055626057088 |
| Weight per piece (including packing) | 5.14 g |
| Weight per piece (excluding packing) | 5.14 g |
| Customs tariff number | 85366990 |
| Country of origin | CN |

FBSR 4-8 - Plug-in bridge

3000585

<https://www.phoenixcontact.com/sg/products/3000585>



Technical data

Product properties

| | |
|---------------------|--------|
| Product type | Jumper |
| Number of positions | 4 |
| Pitch | 8.2 mm |

Electrical properties

| | |
|----------------------|---|
| Maximum load current | 32 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.) |
|----------------------|---|

Connection data

| | |
|----------------------|---|
| Maximum load current | 32 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.) |
|----------------------|---|

Dimensions

| | |
|--------|---------|
| Width | 31.1 mm |
| Height | 30 mm |
| Depth | 30 mm |
| Pitch | 8.2 mm |

Material specifications

| | |
|--|--------|
| Color | red |
| Material | Copper |
| Flammability rating according to UL 94 | V0 |
| Insulating material | PA |

Mounting

| | |
|---------------|------------------|
| Mounting type | Plug-in mounting |
|---------------|------------------|

Drawings

Schematic diagram



FBSR 4-8 - Plug-in bridge

3000585

<https://www.phoenixcontact.com/sg/products/3000585>



Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27141140 |
| ECLASS-12.0 | 27141140 |
| ECLASS-13.0 | 27250303 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC000489 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

FBSR 4-8 - Plug-in bridge

3000585
<https://www.phoenixcontact.com/sg/products/3000585>



Environmental product compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT SEA Pte. Ltd.
105 Eunos Avenue 3, #04-00
Singapore 409836
+65 6228 4900
marketing@phoenixcontact.com.sg