

EC 1 12DC/4A S-C - Electronic circuit breaker



3000757

<https://www.phoenixcontact.com/us/products/3000757>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Electronic circuit breaker, on/off control input, nominal current: 4 A

Commercial data

Item number	3000757
Packing unit	10 pc
Sales key	CL04
Product key	CLA131
GTIN	4046356708500
Weight per piece (including packing)	70.07 g
Weight per piece (excluding packing)	70 g
Customs tariff number	85362010
Country of origin	DE

EC 1 12DC/4A S-C - Electronic circuit breaker



3000757

<https://www.phoenixcontact.com/us/products/3000757>

Technical data

Product properties

Type	DIN rail module, one-piece
Product type	Device circuit breakers
Product family	EC-E
Number of positions	1

Electrical properties

Maximum load current	4 A (100% duty cycle, 40°C)
	4 A (100% duty cycle, 50°C)
Service life electrical	10000

General

Fuse	electronic
------	------------

Connection data

Maximum load current	4 A (100% duty cycle, 40°C)
	4 A (100% duty cycle, 50°C)

Line+ / LOAD+ /0V

Screw thread	M4
Tightening torque	1.5 ... 1.8 Nm
Stripping length	10 mm
Conductor cross section rigid	0.5 mm² ... 10 mm²
Conductor cross section flexible	0.5 mm² ... 10 mm²
2 conductors with same cross section, solid	0.5 mm² ... 4 mm²
2 conductors with same cross section, flexible	0.5 mm² ... 4 mm²
Nominal current	4 A
Nominal voltage	12 V DC

Signal connections

Screw thread	M3
Tightening torque	0.5 ... 0.6 Nm
Conductor cross section flexible	0.25 mm² ... 2.5 mm²

Dimensions

Width	12.5 mm
Height	80 mm

Material specifications

Color	black (RAL 9005)
-------	------------------

Environmental and real-life conditions

Ambient conditions

EC 1 12DC/4A S-C - Electronic circuit breaker



3000757

<https://www.phoenixcontact.com/us/products/3000757>

Ambient temperature (operation)	-20 °C ... 60 °C (ordinary locations)
Ambient temperature (storage/transport)	-20 °C ... 70 °C

Mounting

Mounting type	DIN rail: 35 mm
---------------	-----------------

EC 1 12DC/4A S-C - Electronic circuit breaker



3000757

<https://www.phoenixcontact.com/us/products/3000757>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/3000757>

	cUL Recognized Approval ID: FILE E 140324
	UL Recognized Approval ID: FILE E 317172
	DNV GL Approval ID: TAE00002HC
	UL Recognized Approval ID: FILE E 140324
	UL Listed Approval ID: FILE E 140324
	cUL Listed Approval ID: FILE E 140324
	UL Recognized Approval ID: FILE E 324415
	cULus Listed

EC 1 12DC/4A S-C - Electronic circuit breaker



3000757

<https://www.phoenixcontact.com/us/products/3000757>

Classifications

ECLASS

ECLASS-11.0	27141116
ECLASS-12.0	27141116
ECLASS-13.0	27140401

ETIM

ETIM 9.0	EC000899
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

EC 1 12DC/4A S-C - Electronic circuit breaker



3000757

<https://www.phoenixcontact.com/us/products/3000757>

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 25;
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

EC 1 12DC/4A S-C - Electronic circuit breaker

3000757

<https://www.phoenixcontact.com/us/products/3000757>



Accessories

FBST 500 TMC-N GY - Continuous plug-in bridge

0901028

<https://www.phoenixcontact.com/us/products/0901028>



Continuous plug-in bridge, mounting type: Plug-in mounting

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com