

# UK 2,5 B BU - Feed-through terminal block



3001048

<https://www.phoenixcontact.com/ca/products/3001048>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Feed-through terminal block, nom. voltage: 690 V, nominal current: 24 A, number of connections: 2, connection method: Screw connection, cross section: 0.2 mm<sup>2</sup> - 4 mm<sup>2</sup>, mounting type: NS 35/7,5, NS 35/15, color: blue

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 3001048       |
| Packing unit                         | 50 pc         |
| Minimum order quantity               | 50 pc         |
| Sales key                            | BE01          |
| Product key                          | BE1211        |
| GTIN                                 | 4017918089795 |
| Weight per piece (including packing) | 7.2 g         |
| Weight per piece (excluding packing) | 7 g           |
| Customs tariff number                | 85369010      |
| Country of origin                    | CN            |

# UK 2,5 B BU - Feed-through terminal block



3001048

<https://www.phoenixcontact.com/ca/products/3001048>

## Technical data

### Product properties

|                       |                             |
|-----------------------|-----------------------------|
| Product type          | Feed-through terminal block |
| Number of connections | 2                           |
| Number of rows        | 1                           |
| Potentials            | 1                           |

### Insulation characteristics

|                      |     |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution  | 3   |

### Electrical properties

|                                                 |      |
|-------------------------------------------------|------|
| Rated surge voltage                             | 8 kV |
| Maximum power dissipation for nominal condition | 0 W  |

### Connection data

|                                 |   |
|---------------------------------|---|
| Number of connections per level | 2 |
|---------------------------------|---|

#### Level 1 above 1 below 1

|                                                                                           |                                              |
|-------------------------------------------------------------------------------------------|----------------------------------------------|
| Screw thread                                                                              | M3                                           |
| Tightening torque                                                                         | 0.6 ... 0.8 Nm                               |
| Stripping length                                                                          | 7 mm                                         |
| Internal cylindrical gage                                                                 | A3                                           |
| Conductor cross section rigid                                                             | 0.2 mm <sup>2</sup> ... 4 mm <sup>2</sup>    |
| Cross section AWG                                                                         | 24 ... 12 (converted acc. to IEC)            |
| Conductor cross section flexible                                                          | 0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>  |
| Conductor cross section, flexible [AWG]                                                   | 24 ... 14 (converted acc. to IEC)            |
| Conductor cross-section flexible (ferrule without plastic sleeve)                         | 0.25 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> |
| Flexible conductor cross section (ferrule with plastic sleeve)                            | 0.25 mm <sup>2</sup> ... 1 mm <sup>2</sup>   |
| 2 conductors with same cross section, solid                                               | 0.2 mm <sup>2</sup> ... 1 mm <sup>2</sup>    |
| 2 conductors with same cross section, flexible                                            | 0.25 mm <sup>2</sup> ... 1 mm <sup>2</sup>   |
| 2 conductors with same cross section, flexible, with ferrule without plastic sleeve       | 0.25 mm <sup>2</sup> ... 1 mm <sup>2</sup>   |
| 2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve | 0.5 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>  |
| Nominal current                                                                           | 24 A                                         |
| Nominal voltage                                                                           | 690 V                                        |
| Connection in acc. with standard                                                          | UL                                           |
| Cross section AWG                                                                         | 30 ... 12 (converted acc. to IEC)            |
| Nominal current                                                                           | 20 A                                         |
| Nominal voltage                                                                           | 300 V                                        |
| Connection in acc. with standard                                                          | CSA                                          |
| Cross section AWG                                                                         | 22 ... 12 (converted acc. to IEC)            |
| Nominal current                                                                           | 25 A                                         |

# UK 2,5 B BU - Feed-through terminal block



3001048

<https://www.phoenixcontact.com/ca/products/3001048>

|                 |       |
|-----------------|-------|
| Nominal voltage | 300 V |
|-----------------|-------|

## Dimensions

|                    |         |
|--------------------|---------|
| Width              | 6.2 mm  |
| End cover width    | 1.5 mm  |
| Height             | 42.5 mm |
| Depth on NS 32     | 47 mm   |
| Depth on NS 35/7,5 | 42 mm   |
| Depth on NS 35/15  | 49.5 mm |

## Material specifications

|                                                                         |             |
|-------------------------------------------------------------------------|-------------|
| Color                                                                   | blue        |
| Flammability rating according to UL 94                                  | V0          |
| Insulating material group                                               | I           |
| Insulating material                                                     | PA          |
| Static insulating material application in cold                          | -60 °C      |
| Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) | 130 °C      |
| Relative insulation material temperature index (Elec., UL 746 B)        | 130 °C      |
| Fire protection for rail vehicles (DIN EN 45545-2) R22                  | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R23                  | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R24                  | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R26                  | HL 1 - HL 3 |
| Calorimetric heat release NFPA 130 (ASTM E 1354)                        | 28 MJ/kg    |
| Surface flammability NFPA 130 (ASTM E 162)                              | passed      |
| Specific optical density of smoke NFPA 130 (ASTM E 662)                 | passed      |
| Smoke gas toxicity NFPA 130 (SMP 800C)                                  | passed      |

## Electrical tests

### Surge voltage test

|                       |             |
|-----------------------|-------------|
| Test voltage setpoint | 9.8 kV      |
| Result                | Test passed |

### Temperature-rise test

|                                                  |                                     |
|--------------------------------------------------|-------------------------------------|
| Requirement temperature-rise test                | Increase in temperature $\leq 45$ K |
| Result                                           | Test passed                         |
| Short-time withstand current 2.5 mm <sup>2</sup> | 0.3 kA                              |
| Short-time withstand current 4 mm <sup>2</sup>   | 0.48 kA                             |
| Result                                           | Test passed                         |

### Power-frequency withstand voltage

|                       |             |
|-----------------------|-------------|
| Test voltage setpoint | 1.89 kV     |
| Result                | Test passed |

## Mechanical properties

# UK 2,5 B BU - Feed-through terminal block



3001048

<https://www.phoenixcontact.com/ca/products/3001048>

## Mechanical data

|                 |     |
|-----------------|-----|
| Open side panel | Yes |
|-----------------|-----|

## Mechanical tests

### Mechanical strength

|        |             |
|--------|-------------|
| Result | Test passed |
|--------|-------------|

### Attachment on the carrier

|                         |             |
|-------------------------|-------------|
| DIN rail/fixing support | NS 32/NS 35 |
| Test force setpoint     | 1 N         |
| Result                  | Test passed |

### Test for conductor damage and slackening

|                                |                              |
|--------------------------------|------------------------------|
| Rotation speed                 | 10 rpm                       |
| Revolutions                    | 135                          |
| Conductor cross section/weight | 0.2 mm <sup>2</sup> / 0.2 kg |
|                                | 2.5 mm <sup>2</sup> / 0.7 kg |
|                                | 4 mm <sup>2</sup> / 0.9 kg   |
| Result                         | Test passed                  |

## Environmental and real-life conditions

### Needle-flame test

|                  |             |
|------------------|-------------|
| Time of exposure | 30 s        |
| Result           | Test passed |

### Ambient conditions

|                                          |                                                                                                                              |
|------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Ambient temperature (operation)          | -60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.) |
| Ambient temperature (storage/transport)  | -25 °C ... 60 °C (for a short time, no longer than 24 h, -60°C to +70°C)                                                     |
| Ambient temperature (assembly)           | -5 °C ... 70 °C                                                                                                              |
| Ambient temperature (actuation)          | -5 °C ... 70 °C                                                                                                              |
| Permissible humidity (operation)         | 20 % ... 90 %                                                                                                                |
| Permissible humidity (storage/transport) | 30 % ... 70 %                                                                                                                |

## Standards and regulations

|                                  |     |
|----------------------------------|-----|
| Connection in acc. with standard | UL  |
|                                  | CSA |

## Mounting

|               |           |
|---------------|-----------|
| Mounting type | NS 35/7,5 |
|               | NS 35/15  |

# UK 2,5 B BU - Feed-through terminal block

3001048

<https://www.phoenixcontact.com/ca/products/3001048>



## Drawings

Circuit diagram



# UK 2,5 B BU - Feed-through terminal block



3001048

<https://www.phoenixcontact.com/ca/products/3001048>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/ca/products/3001048>

### DNV

Approval ID: TAE00001CT



### CSA

Approval ID: 13631

|             | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|-------------|-----------------------|-----------------------|-------------------|-----------------------------|
| Use group B |                       |                       |                   |                             |
|             | 600 V                 | 25 A                  | 28 - 12           | -                           |
| Use group C |                       |                       |                   |                             |
|             | 600 V                 | 25 A                  | 28 - 12           | -                           |



### EAC

Approval ID: RU C-DE.BL08.B.00534



### cULus Recognized

Approval ID: E60425

|             | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|-------------|-----------------------|-----------------------|-------------------|-----------------------------|
| Use group B |                       |                       |                   |                             |
|             | 300 V                 | 20 A                  | 30 - 12           | -                           |
| Use group C |                       |                       |                   |                             |
|             | 300 V                 | 20 A                  | 30 - 12           | -                           |
| Use group F |                       |                       |                   |                             |
|             | 600 V                 | 20 A                  | 30 - 12           | -                           |
| Use group D |                       |                       |                   |                             |
|             | 600 V                 | 5 A                   | 30 - 12           | -                           |

# UK 2,5 B BU - Feed-through terminal block



3001048

<https://www.phoenixcontact.com/ca/products/3001048>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27141120 |
| ECLASS-13.0 | 27250101 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC000897 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

Environmental product compliance

|                                         |                                                                                                                                                                                                                                   |
|-----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EU RoHS                                 |                                                                                                                                                                                                                                   |
| Fulfills EU RoHS substance requirements | Yes                                                                                                                                                                                                                               |
| Exemption                               | 6(c)                                                                                                                                                                                                                              |
| China RoHS                              |                                                                                                                                                                                                                                   |
| Environment friendly use period (EFUP)  | EFUP-50                                                                                                                                                                                                                           |
|                                         | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |
| EU REACH SVHC                           |                                                                                                                                                                                                                                   |
| REACH candidate substance (CAS No.)     | Lead(CAS: 7439-92-1)                                                                                                                                                                                                              |
| SCIP                                    | 3efba958-aac6-40c5-af57-7fb71b332c15                                                                                                                                                                                              |

# UK 2,5 B BU - Feed-through terminal block



3001048

<https://www.phoenixcontact.com/ca/products/3001048>

## Accessories

### ISSBI 10- 6 - Bridge

0301505

<https://www.phoenixcontact.com/ca/products/0301505>



Bridge, pitch: 6 mm, number of positions: 10, color: silver

---

### IS-K 4 - Bridge bar isolator

1302338

<https://www.phoenixcontact.com/ca/products/1302338>



Bridge bar isolator, color: gray

# UK 2,5 B BU - Feed-through terminal block

3001048

<https://www.phoenixcontact.com/ca/products/3001048>



## LB 10-6 BU - Bridge

0202280

<https://www.phoenixcontact.com/ca/products/0202280>



Bridge, pitch: 6 mm, number of positions: 10, color: blue

---

## LB 10-6 GY - Bridge

0202358

<https://www.phoenixcontact.com/ca/products/0202358>



Bridge, pitch: 6 mm, number of positions: 10, color: gray

# UK 2,5 B BU - Feed-through terminal block

3001048

<https://www.phoenixcontact.com/ca/products/3001048>



## KB- 6-EX - Chain bridge

0201485

<https://www.phoenixcontact.com/ca/products/0201485>

Chain bridge, number of positions: 1, color: silver



---

## FBI 10- 6 - Fixed bridge

0203250

<https://www.phoenixcontact.com/ca/products/0203250>

Fixed bridge, pitch: 6.2 mm, number of positions: 10, color: silver



# UK 2,5 B BU - Feed-through terminal block

3001048

<https://www.phoenixcontact.com/ca/products/3001048>



## FB 3- 6-EX - Fixed bridge

0201469

<https://www.phoenixcontact.com/ca/products/0201469>



Fixed bridge, pitch: 6.2 mm, number of positions: 3, color: silver

---

## FB 2- 6-EX - Fixed bridge

0201456

<https://www.phoenixcontact.com/ca/products/0201456>



Fixed bridge, pitch: 6.2 mm, number of positions: 2, color: silver

# UK 2,5 B BU - Feed-through terminal block

3001048

<https://www.phoenixcontact.com/ca/products/3001048>



## FB 10- 6-EX - Fixed bridge

0201281

<https://www.phoenixcontact.com/ca/products/0201281>

Fixed bridge, pitch: 6.2 mm, number of positions: 10, color: silver



---

## FBI 100- 6 - Fixed bridge

0201650

<https://www.phoenixcontact.com/ca/products/0201650>

Fixed bridge, pitch: 6.2 mm, number of positions: 100, color: silver



# UK 2,5 B BU - Feed-through terminal block

3001048

<https://www.phoenixcontact.com/ca/products/3001048>



## FBI 20- 6 - Fixed bridge

0201867

<https://www.phoenixcontact.com/ca/products/0201867>



Fixed bridge, pitch: 6.2 mm, number of positions: 20, color: silver

---

## FB 10- 6 - Fixed bridge

0201184

<https://www.phoenixcontact.com/ca/products/0201184>



Fixed bridge, pitch: 6.2 mm, number of positions: 10, color: silver

# UK 2,5 B BU - Feed-through terminal block

3001048

<https://www.phoenixcontact.com/ca/products/3001048>



## FB 5- 6 - Fixed bridge

0201029

<https://www.phoenixcontact.com/ca/products/0201029>



Fixed bridge, pitch: 6.2 mm, number of positions: 5, color: silver

---

## EB 3- 6 - Insertion bridge

0201142

<https://www.phoenixcontact.com/ca/products/0201142>



Insertion bridge, pitch: 6.2 mm, number of positions: 3, color: gray

# UK 2,5 B BU - Feed-through terminal block

3001048

<https://www.phoenixcontact.com/ca/products/3001048>



## EB 2- 6 - Insertion bridge

0201155

<https://www.phoenixcontact.com/ca/products/0201155>

Insertion bridge, pitch: 6.2 mm, number of positions: 2, color: gray




---

## EB 10- 6 - Insertion bridge

0201139

<https://www.phoenixcontact.com/ca/products/0201139>

Insertion bridge, pitch: 6.2 mm, number of positions: 10, color: gray



## UK 2,5 B BU - Feed-through terminal block

3001048

<https://www.phoenixcontact.com/ca/products/3001048>



## USBR 2-7 - Switching jumper

2303239

<https://www.phoenixcontact.com/ca/products/2303239>



Switching jumper, pitch: 7 mm, number of positions: 2, color: silver

---

## USBRJ 2-7 - Switching jumper

2305538

<https://www.phoenixcontact.com/ca/products/2305538>



Switching jumper, number of positions: 2, color: silver

## UK 2,5 B BU - Feed-through terminal block

3001048

<https://www.phoenixcontact.com/ca/products/3001048>



## SBRN 2-7 - Switching jumper

1413230

<https://www.phoenixcontact.com/ca/products/1413230>




Switching jumper, pitch: 7 mm, number of positions: 2, color: silver

---

## D-UK 2,5 BU - End cover

3001103

<https://www.phoenixcontact.com/ca/products/3001103>



End cover, depth: 30.7 mm, width: 1.5 mm, height: 42.5 mm, color: blue

# UK 2,5 B BU - Feed-through terminal block



3001048

<https://www.phoenixcontact.com/ca/products/3001048>

## D-UK 2,5 - End cover

3001022

<https://www.phoenixcontact.com/ca/products/3001022>

End cover, depth: 30.7 mm, width: 1.5 mm, height: 42.5 mm, color: gray



---

## WS 5- 6 - Warning label

1004403

<https://www.phoenixcontact.com/ca/products/1004403>

Warning plate, with 2 plastic screws, across 5 terminal blocks, pitch 6 mm



# UK 2,5 B BU - Feed-through terminal block



3001048

<https://www.phoenixcontact.com/ca/products/3001048>

## WS 4- 6 - Warning label

1004209

<https://www.phoenixcontact.com/ca/products/1004209>

Warning plate, with 2 plastic screws, across 4 terminal blocks, pitch 6 mm



---

## WS 3- 6 - Warning label

1004115

<https://www.phoenixcontact.com/ca/products/1004115>

Warning plate, with 2 plastic screws, across 3 terminal blocks, pitch 6 mm



# UK 2,5 B BU - Feed-through terminal block

3001048

<https://www.phoenixcontact.com/ca/products/3001048>



## ZSR-EX - Screw

0200017

<https://www.phoenixcontact.com/ca/products/0200017>

Screw



---

## FB-150

## METER - Fixed bridge

0201595

<https://www.phoenixcontact.com/ca/products/0201595>



Cross connection rail, for fixed bridging of identical inputs and outputs, made of Cu, nickel-plated, 1 m long

# UK 2,5 B BU - Feed-through terminal block

3001048

<https://www.phoenixcontact.com/ca/products/3001048>



## KSS 3- 6 - Short-circuit connector

0309523

<https://www.phoenixcontact.com/ca/products/0309523>



Short-circuit connector, pitch: 6 mm, number of positions: 3, color: black

---

## KSS 6 - Short-circuit connector

0301547

<https://www.phoenixcontact.com/ca/products/0301547>



Short-circuit connector, pitch: 6 mm, number of positions: 2, color: black

# UK 2,5 B BU - Feed-through terminal block

3001048


<https://www.phoenixcontact.com/ca/products/3001048>



## PS-UK 2,5 B/Z-6 - Test plug

3001239

<https://www.phoenixcontact.com/ca/products/3001239>



Test plug, number of positions: 1, color: red

---

## PS-UK 2,5 B/E - Test plug

3001132

<https://www.phoenixcontact.com/ca/products/3001132>



Test plug, number of positions: 1, color: red

# UK 2,5 B BU - Feed-through terminal block

3001048

<https://www.phoenixcontact.com/ca/products/3001048>



## RPS - Reducing plug

0201647

<https://www.phoenixcontact.com/ca/products/0201647>



Reducing plug, number of positions: 1, color: gray

---

## TS-KK 3 - Separating plate

2770215

<https://www.phoenixcontact.com/ca/products/2770215>



Separating plate, depth: 16 mm, width: 0.5 mm, height: 14 mm, color: gray

## UK 2,5 B BU - Feed-through terminal block

3001048

<https://www.phoenixcontact.com/ca/products/3001048>



## ATP-UK - Partition plate

3003224

<https://www.phoenixcontact.com/ca/products/3003224>



Partition plate, depth: 45.7 mm, width: 1.5 mm, height: 56 mm, color: gray

---

## NS 32 PERF 2000MM-VPE 10 - DIN rail perforated

1201002

<https://www.phoenixcontact.com/ca/products/1201002>



DIN rail perforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, G profile, color: silver

# UK 2,5 B BU - Feed-through terminal block

3001048

<https://www.phoenixcontact.com/ca/products/3001048>



## NS 32 UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201015

<https://www.phoenixcontact.com/ca/products/1201015>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, G profile, color: silver

---

## NS 35/ 7,5 PERF 2000MM - DIN rail perforated

0801733

<https://www.phoenixcontact.com/ca/products/0801733>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

## UK 2,5 B BU - Feed-through terminal block

3001048

<https://www.phoenixcontact.com/ca/products/3001048>



## NS 35/ 7,5 UNPERF 2000MM - DIN rail, unperforated

0801681

<https://www.phoenixcontact.com/ca/products/0801681>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

---

## NS 35/ 7,5 WH PERF 2000MM - DIN rail perforated

1204119

<https://www.phoenixcontact.com/ca/products/1204119>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

# UK 2,5 B BU - Feed-through terminal block

3001048

<https://www.phoenixcontact.com/ca/products/3001048>



## NS 35/ 7,5 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204122

<https://www.phoenixcontact.com/ca/products/1204122>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

---

## NS 35/ 7,5 AL UNPERF 2000MM - DIN rail, unperforated

0801704

<https://www.phoenixcontact.com/ca/products/0801704>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

# UK 2,5 B BU - Feed-through terminal block

3001048

<https://www.phoenixcontact.com/ca/products/3001048>



## NS 35/ 7,5 ZN PERF 2000MM - DIN rail perforated

1206421

<https://www.phoenixcontact.com/ca/products/1206421>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

---

## NS 35/ 7,5 ZN UNPERF 2000MM - DIN rail, unperforated

1206434

<https://www.phoenixcontact.com/ca/products/1206434>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

## UK 2,5 B BU - Feed-through terminal block

3001048

<https://www.phoenixcontact.com/ca/products/3001048>



## NS 35/ 7,5 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

0801762

<https://www.phoenixcontact.com/ca/products/0801762>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

---

## NS 35/ 7,5 CAP - End cap

1206560

<https://www.phoenixcontact.com/ca/products/1206560>

DIN rail end piece, for DIN rail NS 35/7.5



# UK 2,5 B BU - Feed-through terminal block

3001048

<https://www.phoenixcontact.com/ca/products/3001048>



## NS 35/15 PERF 2000MM - DIN rail perforated

1201730

<https://www.phoenixcontact.com/ca/products/1201730>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

---

## NS 35/15 UNPERF 2000MM - DIN rail, unperforated

1201714

<https://www.phoenixcontact.com/ca/products/1201714>



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

## UK 2,5 B BU - Feed-through terminal block

3001048

<https://www.phoenixcontact.com/ca/products/3001048>



## NS 35/15 WH PERF 2000MM - DIN rail perforated

0806602

<https://www.phoenixcontact.com/ca/products/0806602>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: white

---

## NS 35/15 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204135

<https://www.phoenixcontact.com/ca/products/1204135>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

## UK 2,5 B BU - Feed-through terminal block

3001048

<https://www.phoenixcontact.com/ca/products/3001048>



### NS 35/15 AL UNPERF 2000MM - DIN rail, unperforated

1201756

<https://www.phoenixcontact.com/ca/products/1201756>



DIN rail, unperforated, similar to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

---

### NS 35/15 ZN PERF 2000MM - DIN rail perforated

1206599

<https://www.phoenixcontact.com/ca/products/1206599>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver

## UK 2,5 B BU - Feed-through terminal block

3001048

<https://www.phoenixcontact.com/ca/products/3001048>



### NS 35/15 ZN UNPERF 2000MM - DIN rail, unperforated

1206586

<https://www.phoenixcontact.com/ca/products/1206586>



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver

---

### NS 35/15 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201895

<https://www.phoenixcontact.com/ca/products/1201895>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

# UK 2,5 B BU - Feed-through terminal block

3001048

<https://www.phoenixcontact.com/ca/products/3001048>



## NS 35/15 CAP - End cap

1206573

<https://www.phoenixcontact.com/ca/products/1206573>

DIN rail end piece, for DIN rail NS 35/15



---

## NS 35/15-2,3 UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201798

<https://www.phoenixcontact.com/ca/products/1201798>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile 2.3 mm, color: silver

# UK 2,5 B BU - Feed-through terminal block



3001048

<https://www.phoenixcontact.com/ca/products/3001048>

## ZB 6:UNBEDRUCKT - Zack marker strip

1051003

<https://www.phoenixcontact.com/ca/products/1051003>



Zack marker strip, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 6.15 x 10.5 mm, Number of individual labels: 10

---

## ZB 6,LGS:FORTL.ZAHLEN - Zack marker strip

1051016

<https://www.phoenixcontact.com/ca/products/1051016>



Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, printed horizontally: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 491 ... 500, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 6.15 x 10.5 mm, Number of individual labels: 10

# UK 2,5 B BU - Feed-through terminal block



3001048

<https://www.phoenixcontact.com/ca/products/3001048>

## ZB 6,QR:FORTL.ZAHLEN - Zack marker strip

1051029

<https://www.phoenixcontact.com/ca/products/1051029>



Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, Printed vertically: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 491 ... 500, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 6.15 x 10.5 mm, Number of individual labels: 10

---

## ZB 6,LGS:GLEICHE ZAHLEN - Zack marker strip

1051032

<https://www.phoenixcontact.com/ca/products/1051032>



Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, printed horizontally: Identical numbers 1 or 2, etc. up to 100, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 6.15 x 10.5 mm, Number of individual labels: 10

# UK 2,5 B BU - Feed-through terminal block



3001048

<https://www.phoenixcontact.com/ca/products/3001048>

## ZB 6,LGS:L1-N,PE - Marker for terminal blocks

1051414

<https://www.phoenixcontact.com/ca/products/1051414>



Marker for terminal blocks, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, horizontal: L1, L2, L3, N, PE, L1, L2, L3, N, PE, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 6.15 x 10.5 mm, Number of individual labels: 10

---

## ZB 6,LGS:U-N - Marker for terminal blocks

1051430

<https://www.phoenixcontact.com/ca/products/1051430>



Marker for terminal blocks, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, printed horizontally: U, V, W, N, GND, U, V, W, N, GND, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 6.15 x 10.5 mm, Number of individual labels: 10

## UK 2,5 B BU - Feed-through terminal block

3001048

<https://www.phoenixcontact.com/ca/products/3001048>



### UC-TM 6 - Marker for terminal blocks

0818085

<https://www.phoenixcontact.com/ca/products/0818085>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 5.6 x 10.5 mm, Number of individual labels: 80

---

### UCT-TM 6 - Marker for terminal blocks

0828736

<https://www.phoenixcontact.com/ca/products/0828736>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 5.6 x 10.5 mm, Number of individual labels: 60

# UK 2,5 B BU - Feed-through terminal block

3001048

<https://www.phoenixcontact.com/ca/products/3001048>



## CLIPFIX 35 - End bracket

3022218

<https://www.phoenixcontact.com/ca/products/3022218>

Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, width: 9.5 mm, color: gray



---

## CLIPFIX 35-5 - End bracket

3022276

<https://www.phoenixcontact.com/ca/products/3022276>

Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, with parking option for FBS...5, FBS...6, KSS 5, KSS 6, width: 5.15 mm, color: gray



# UK 2,5 B BU - Feed-through terminal block

3001048

<https://www.phoenixcontact.com/ca/products/3001048>




## E/NS 35 N - End bracket

0800886

<https://www.phoenixcontact.com/ca/products/0800886>

End clamp, width: 9.5 mm, color: gray



---

## E/UK - End bracket

1201442

<https://www.phoenixcontact.com/ca/products/1201442>

End bracket, Mounting on a DIN rail NS 32 or NS 35, material: PA, color: gray



## UK 2,5 B BU - Feed-through terminal block

3001048

<https://www.phoenixcontact.com/ca/products/3001048>



### E/UK 1 - End bracket

1201413

<https://www.phoenixcontact.com/ca/products/1201413>



End clamps, for supporting the ends of double-level and three-level terminal blocks, width: 10 mm, color: gray

---

### PSBJ 3/13/4 - Test plug strip

0201304

<https://www.phoenixcontact.com/ca/products/0201304>



Test plug strip, number of positions: 1, color: silver

## UK 2,5 B BU - Feed-through terminal block

3001048

<https://www.phoenixcontact.com/ca/products/3001048>



## PSB 3/10/4 - Test plug strip

0601292

<https://www.phoenixcontact.com/ca/products/0601292>

Test plug strip, number of positions: 1, color: silver



---

## SF-SL 0,6X3,5-100 S-VDE - Screwdriver

1212587

<https://www.phoenixcontact.com/ca/products/1212587>

Actuation tool, for ST terminal blocks, VDE insulated, with slimmer insulation integrated in the blade, also suitable for use as a bladed screwdriver, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip



---

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd  
8240 Parkhill Drive  
Milton, Ontario L9T 5V7  
1-800-890-2820  
[cdinfo@phoenixcontact.ca](mailto:cdinfo@phoenixcontact.ca)