

# UK 10 N RD - Feed-through terminal block



3022315

<https://www.phoenixcontact.com/us/products/3022315>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Feed-through terminal block, nom. voltage: 800 V, nominal current: 57 A, number of connections: 2, number of positions: 1, connection method: Screw connection, Rated cross section: 10 mm<sup>2</sup>, cross section: 0.5 mm<sup>2</sup> - 16 mm<sup>2</sup>, mounting type: NS 35/7,5, NS 35/15, color: red

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 3022315       |
| Packing unit                         | 1 pc          |
| Minimum order quantity               | 50 pc         |
| Sales key                            | BE12          |
| Product key                          | BE1211        |
| GTIN                                 | 4017918433390 |
| Weight per piece (including packing) | 17.22 g       |
| Weight per piece (excluding packing) | 16.312 g      |
| Customs tariff number                | 85369010      |
| Country of origin                    | CN            |

# UK 10 N RD - Feed-through terminal block



3022315

<https://www.phoenixcontact.com/us/products/3022315>

## Technical data

### Product properties

|                       |                             |
|-----------------------|-----------------------------|
| Product type          | Feed-through terminal block |
| Number of positions   | 1                           |
| Number of connections | 2                           |
| Number of rows        | 1                           |

### Insulation characteristics

|                      |     |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution  | 3   |

### Electrical properties

|                                                 |        |
|-------------------------------------------------|--------|
| Rated surge voltage                             | 8 kV   |
| Maximum power dissipation for nominal condition | 1.82 W |

### Connection data

|                                 |                    |
|---------------------------------|--------------------|
| Number of connections per level | 2                  |
| Nominal cross section           | 10 mm <sup>2</sup> |

### Level 1 above 1 below 1

|                                                                                           |                                                        |
|-------------------------------------------------------------------------------------------|--------------------------------------------------------|
| Screw thread                                                                              | M4                                                     |
| Tightening torque                                                                         | 1.5 ... 1.8 Nm                                         |
| Stripping length                                                                          | 10 mm                                                  |
| Internal cylindrical gage                                                                 | B6                                                     |
| Connection in acc. with standard                                                          | IEC 60947-7-1                                          |
| Conductor cross section rigid                                                             | 0.5 mm <sup>2</sup> ... 16 mm <sup>2</sup>             |
| Cross section AWG                                                                         | 20 ... 6 (converted acc. to IEC)                       |
| Conductor cross section flexible                                                          | 0.5 mm <sup>2</sup> ... 10 mm <sup>2</sup>             |
| Conductor cross section, flexible [AWG]                                                   | 20 ... 8 (converted acc. to IEC)                       |
| Conductor cross-section flexible (ferrule without plastic sleeve)                         | 0.5 mm <sup>2</sup> ... 10 mm <sup>2</sup>             |
| Flexible conductor cross section (ferrule with plastic sleeve)                            | 0.5 mm <sup>2</sup> ... 6 mm <sup>2</sup>              |
| Cross-section with insertion bridge, rigid                                                | 10 mm <sup>2</sup>                                     |
| Cross-section with insertion bridge, flexible                                             | 10 mm <sup>2</sup>                                     |
| 2 conductors with same cross section, solid                                               | 0.5 mm <sup>2</sup> ... 4 mm <sup>2</sup>              |
| 2 conductors with same cross section, flexible                                            | 0.5 mm <sup>2</sup> ... 4 mm <sup>2</sup>              |
| 2 conductors with same cross section, flexible, with ferrule without plastic sleeve       | 0.5 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>            |
| 2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve | 0.5 mm <sup>2</sup> ... 6 mm <sup>2</sup>              |
| Nominal current                                                                           | 57 A                                                   |
| Maximum load current                                                                      | 76 A (with 16 mm <sup>2</sup> conductor cross section) |
| Nominal voltage                                                                           | 800 V                                                  |
| Nominal cross section                                                                     | 10 mm <sup>2</sup>                                     |

# UK 10 N RD - Feed-through terminal block



3022315

<https://www.phoenixcontact.com/us/products/3022315>

## Ex data

### Rated data (ATEX/IECEx)

|                                   |                                       |
|-----------------------------------|---------------------------------------|
| Identification                    | Ex II 2 GD Ex eb IIC Gb               |
| Operating temperature range       | -60 °C ... 110 °C                     |
| Ex-certified accessories          | 3003020 D-UK 4/10                     |
|                                   | 3006027 D-UK 16                       |
|                                   | 3004210 ATP-UK 5-MTK                  |
|                                   | 1205066 SZS 1,0X4,0 VDE               |
|                                   | 1201442 E/UK                          |
| List of bridges                   | Fixed bridge / FBI 10-10-EX / 0711690 |
| Bridge data                       | 51.5 A / 10 mm <sup>2</sup>           |
| List of bridges                   | Insertion bridge / EB 2-10 / 0203153  |
|                                   | Insertion bridge / EB 3-10 / 0203328  |
|                                   | Insertion bridge / EB 10-10 / 0203137 |
| Bridge data                       | 50 A / 10 mm <sup>2</sup>             |
| Ex temperature increase           | 40 K (59.1 A / 10 mm <sup>2</sup> )   |
| Rated voltage                     | 690 V                                 |
| at bridging with insertion bridge | 690 V                                 |
| for bridging with bridge          | 690 V                                 |
| Rated insulation voltage          | 630 V                                 |
| output                            | (Permanent)                           |

### Ex level General

|                      |         |
|----------------------|---------|
| Rated current        | 53.5 A  |
| Maximum load current | 67 A    |
| Contact resistance   | 0.12 mΩ |

### Ex connection data General

|                                                       |                                            |
|-------------------------------------------------------|--------------------------------------------|
| Torque range                                          | 1.5 Nm ... 1.8 Nm                          |
| Nominal cross section                                 | 10 mm <sup>2</sup>                         |
| Rated cross section AWG                               | 8                                          |
| Connection capacity rigid                             | 0.5 mm <sup>2</sup> ... 16 mm <sup>2</sup> |
| Connection capacity AWG                               | 20 ... 6                                   |
| Connection capacity flexible                          | 0.5 mm <sup>2</sup> ... 10 mm <sup>2</sup> |
| Connection capacity AWG                               | 20 ... 8                                   |
| 2 conductors with same cross section, solid           | 0.5 mm <sup>2</sup> ... 4 mm <sup>2</sup>  |
| 2 conductors with the same cross-section AWG rigid    | 20 ... 12                                  |
| 2 conductors with same cross section, stranded        | 0.5 mm <sup>2</sup> ... 4 mm <sup>2</sup>  |
| 2 conductors with the same cross-section AWG flexible | 20 ... 12                                  |

## Dimensions

|                 |         |
|-----------------|---------|
| Width           | 10.2 mm |
| End cover width | 1.8 mm  |
| Height          | 42.5 mm |

# UK 10 N RD - Feed-through terminal block



3022315

<https://www.phoenixcontact.com/us/products/3022315>

|                    |         |
|--------------------|---------|
| Depth on NS 32     | 52.3 mm |
| Depth on NS 35/7,5 | 47.3 mm |
| Depth on NS 35/15  | 54.8 mm |

## Material specifications

|                                                                         |             |
|-------------------------------------------------------------------------|-------------|
| Color                                                                   | red         |
| Flammability rating according to UL 94                                  | V0          |
| Insulating material group                                               | I           |
| Insulating material                                                     | PA          |
| Static insulating material application in cold                          | -60 °C      |
| Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) | 130 °C      |
| Relative insulation material temperature index (Elec., UL 746 B)        | 130 °C      |
| Fire protection for rail vehicles (DIN EN 45545-2) R22                  | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R23                  | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R24                  | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R26                  | HL 1 - HL 3 |
| Calorimetric heat release NFPA 130 (ASTM E 1354)                        | 28 MJ/kg    |
| Surface flammability NFPA 130 (ASTM E 162)                              | passed      |
| Specific optical density of smoke NFPA 130 (ASTM E 662)                 | passed      |
| Smoke gas toxicity NFPA 130 (SMP 800C)                                  | passed      |

## Electrical tests

### Surge voltage test

|                       |             |
|-----------------------|-------------|
| Test voltage setpoint | 9.8 kV      |
| Result                | Test passed |

### Temperature-rise test

|                                                 |                                     |
|-------------------------------------------------|-------------------------------------|
| Requirement temperature-rise test               | Increase in temperature $\leq 45$ K |
| Result                                          | Test passed                         |
| Short-time withstand current 10 mm <sup>2</sup> | 1.2 kA                              |
| Short-time withstand current 16 mm <sup>2</sup> | 1.92 kA                             |
| Result                                          | Test passed                         |

### Power-frequency withstand voltage

|                       |             |
|-----------------------|-------------|
| Test voltage setpoint | 2 kV        |
| Result                | Test passed |

## Mechanical properties

### Mechanical data

|                 |     |
|-----------------|-----|
| Open side panel | Yes |
|-----------------|-----|

## Mechanical tests

### Mechanical strength

# UK 10 N RD - Feed-through terminal block



3022315

<https://www.phoenixcontact.com/us/products/3022315>

|        |             |
|--------|-------------|
| Result | Test passed |
|--------|-------------|

## Attachment on the carrier

|                         |             |
|-------------------------|-------------|
| DIN rail/fixing support | NS 32/NS 35 |
| Test force setpoint     | 5 N         |
| Result                  | Test passed |

## Test for conductor damage and slackening

|                                |                              |
|--------------------------------|------------------------------|
| Rotation speed                 | 10 rpm                       |
| Revolutions                    | 135                          |
| Conductor cross section/weight | 0.5 mm <sup>2</sup> / 0.3 kg |
|                                | 10 mm <sup>2</sup> / 2 kg    |
|                                | 16 mm <sup>2</sup> / 2.9 kg  |
| Result                         | Test passed                  |

## Environmental and real-life conditions

### Needle-flame test

|                  |             |
|------------------|-------------|
| Time of exposure | 30 s        |
| Result           | Test passed |

### Ambient conditions

|                                          |                                                                           |
|------------------------------------------|---------------------------------------------------------------------------|
| Ambient temperature (storage/transport)  | -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C) |
| Ambient temperature (assembly)           | -5 °C ... 70 °C                                                           |
| Ambient temperature (actuation)          | -5 °C ... 70 °C                                                           |
| Permissible humidity (storage/transport) | 30 % ... 70 %                                                             |

## Standards and regulations

|                                  |               |
|----------------------------------|---------------|
| Connection in acc. with standard | IEC 60947-7-1 |
|----------------------------------|---------------|

## Mounting

|               |           |
|---------------|-----------|
| Mounting type | NS 35/7,5 |
|               | NS 35/15  |

# UK 10 N RD - Feed-through terminal block



3022315

<https://www.phoenixcontact.com/us/products/3022315>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/3022315>

### DNV

Approval ID: TAE00001CT



### CSA

Approval ID: 13631

|             | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|-------------|-----------------------|-----------------------|-------------------|-----------------------------|
| Use group B |                       |                       |                   |                             |
|             | 600 V                 | 65 A                  | 24 - 6            | -                           |
| Use group C |                       |                       |                   |                             |
|             | 600 V                 | 65 A                  | 24 - 6            | -                           |



### IECEE CB Scheme

Approval ID: NL-39959

|  | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|--|-----------------------|-----------------------|-------------------|-----------------------------|
|  | 800 V                 | 57 A                  | -                 | - 10                        |



### EAC

Approval ID: RU C-DE.BL08.B.00534



### cULus Recognized

Approval ID: E60425

|             | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|-------------|-----------------------|-----------------------|-------------------|-----------------------------|
| Use group B |                       |                       |                   |                             |
|             | 600 V                 | 65 A                  | 24 - 6            | -                           |
| Use group C |                       |                       |                   |                             |
|             | 600 V                 | 65 A                  | 24 - 6            | -                           |
| Use group F |                       |                       |                   |                             |
|             | 800 V                 | 65 A                  | 24 - 6            | -                           |



### RS

Approval ID: 22.44.01.00083.250



### KEMA-KEUR

Approval ID: 71-119849

|  | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|--|-----------------------|-----------------------|-------------------|-----------------------------|
|  | 800 V                 | 57 A                  | -                 | - 10                        |

# UK 10 N RD - Feed-through terminal block



3022315

<https://www.phoenixcontact.com/us/products/3022315>



**ATEX**

Approval ID: KEMA98ATEX1786U



**cUL Recognized**

Approval ID: E192998

|  | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|--|-----------------------|-----------------------|-------------------|-----------------------------|
|  | 600 V                 | 65 A                  | 24 - 6            | -                           |



**EAC Ex**

Approval ID: RU C-DE.HA91.B.00066



**GL**

Approval ID: 98876-96 HH

|                           | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|---------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
| EEx e II part certificate | 690 V                 | 57 A                  | -                 | - 10                        |



**IECEx**

Approval ID: IECEx KEM 06.0029U



**UL Recognized**

Approval ID: E192998

|  | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|--|-----------------------|-----------------------|-------------------|-----------------------------|
|  | 600 V                 | 65 A                  | 24 - 6            | -                           |



**CCC**

Approval ID: 2020322313000623



**DNV GL-EX**

Approval ID: TAE00003K6

|                           | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|---------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
| EEx e II part certificate | 440 V                 | 32 A                  | -                 | - 2.5                       |

**cULus Recognized**

# UK 10 N RD - Feed-through terminal block



3022315

<https://www.phoenixcontact.com/us/products/3022315>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27141120 |
| ECLASS-13.0 | 27250101 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC000897 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# UK 10 N RD - Feed-through terminal block



3022315

<https://www.phoenixcontact.com/us/products/3022315>

## Environmental product compliance

|            |                                                         |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

# UK 10 N RD - Feed-through terminal block

3022315

<https://www.phoenixcontact.com/us/products/3022315>



## Accessories



Note: Applying some accessories below might limit this product.

### KB- 10 - Chain bridge

0203205

<https://www.phoenixcontact.com/us/products/0203205>



Chain bridge, pitch: 10 mm, number of positions: 1, color: silver

### FBI 2-10 - Fixed bridge

0203483

<https://www.phoenixcontact.com/us/products/0203483>



Fixed bridge, pitch: 10 mm, number of positions: 2, color: silver

# UK 10 N RD - Feed-through terminal block

3022315

<https://www.phoenixcontact.com/us/products/3022315>



## FBI 10-10 - Fixed bridge

0203276

<https://www.phoenixcontact.com/us/products/0203276>

Fixed bridge, pitch: 10 mm, number of positions: 10, color: silver



 Max. current carrying capacity: 76 A

---

## FB 10-10-EX - Fixed bridge

0203247

<https://www.phoenixcontact.com/us/products/0203247>

Fixed bridge, pitch: 10 mm, number of positions: 10, color: silver



# UK 10 N RD - Feed-through terminal block

3022315

<https://www.phoenixcontact.com/us/products/3022315>



## FB 4-10 - Fixed bridge

0203182

<https://www.phoenixcontact.com/us/products/0203182>

Fixed bridge, number of positions: 4, color: silver



---

## FB 10-10 - Fixed bridge

0203179

<https://www.phoenixcontact.com/us/products/0203179>

Fixed bridge, pitch: 10 mm, number of positions: 10, color: silver



# UK 10 N RD - Feed-through terminal block

3022315

<https://www.phoenixcontact.com/us/products/3022315>



## FB 3-10 - Fixed bridge

0203140

<https://www.phoenixcontact.com/us/products/0203140>



Fixed bridge, pitch: 10 mm, number of positions: 3, color: silver

---

## EB 2-10 - Insertion bridge

0203153

<https://www.phoenixcontact.com/us/products/0203153>



Insertion bridge, pitch: 10 mm, number of positions: 2, color: gray

 Max. current carrying capacity: 70 A

# UK 10 N RD - Feed-through terminal block

3022315

<https://www.phoenixcontact.com/us/products/3022315>




## EB 3-10 - Insertion bridge

0203328

<https://www.phoenixcontact.com/us/products/0203328>

Insertion bridge, pitch: 10 mm, number of positions: 3, color: gray



 Max. current carrying capacity: 70 A


---

## EB 10-10 - Insertion bridge

0203137

<https://www.phoenixcontact.com/us/products/0203137>

Insertion bridge, pitch: 10 mm, number of positions: 10, color: gray



 Max. current carrying capacity: 70 A

## UK 10 N RD - Feed-through terminal block

3022315

<https://www.phoenixcontact.com/us/products/3022315>



## SB 2- 8/13 N - Switching jumper

0200062

<https://www.phoenixcontact.com/us/products/0200062>

Switching jumper, pitch: 13 mm, number of positions: 2, color: silver



## WS 5-10 - Warning label

1004429

<https://www.phoenixcontact.com/us/products/1004429>

Warning label, Plate, yellow/black, labeled: Lightning flash and warning in English, mounting type: plug in, for terminal block width: 10 mm, diameter: 0 mm



## UK 10 N RD - Feed-through terminal block

3022315

<https://www.phoenixcontact.com/us/products/3022315>



## WS 4-10 - Warning label

1004225

<https://www.phoenixcontact.com/us/products/1004225>

Warning label, Plate, yellow/black, labeled: Lightning flash and warning in English, mounting type: plug in, for terminal block width: 10 mm, diameter: 0 mm



---

## STL 10N/5N - Step bracket

0204110

<https://www.phoenixcontact.com/us/products/0204110>

Step bracket, pitch: 5 mm, number of positions: 2, color: silver



## UK 10 N RD - Feed-through terminal block

3022315

<https://www.phoenixcontact.com/us/products/3022315>



## TS-K - Separating plate

1302215

<https://www.phoenixcontact.com/us/products/1302215>



Separating plate, depth: 22 mm, width: 0.5 mm, height: 22 mm, color: gray

---

## ATP-UK - Partition plate

3003224

<https://www.phoenixcontact.com/us/products/3003224>



Partition plate, depth: 45.7 mm, width: 1.5 mm, height: 56 mm, color: gray

# UK 10 N RD - Feed-through terminal block



3022315

<https://www.phoenixcontact.com/us/products/3022315>

## SBS10:UNBEDRUCKT - Marker card

1007248

<https://www.phoenixcontact.com/us/products/1007248>



Marker card, Card, white, unlabeled, can be labeled with: Marker pen, perforated, mounting type: snapped, snap into flat marker groove, for terminal block width: 10 mm, lettering field size: 6 x 10.1 mm, Number of individual labels: 250

---

## SCP 2-10 - Short-circuit connector

3070412

<https://www.phoenixcontact.com/us/products/3070412>



Short-circuit connector, pitch: 10.15 mm, number of positions: 2, color: orange

# UK 10 N RD - Feed-through terminal block

3022315

<https://www.phoenixcontact.com/us/products/3022315>



## NS 32 PERF 2000MM-VPE 10 - DIN rail perforated

1201002

<https://www.phoenixcontact.com/us/products/1201002>



DIN rail perforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, G profile, color: silver

---

## NS 32 UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201015

<https://www.phoenixcontact.com/us/products/1201015>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, G profile, color: silver

# UK 10 N RD - Feed-through terminal block

3022315

<https://www.phoenixcontact.com/us/products/3022315>



## NS 35/ 7,5 PERF 2000MM - DIN rail perforated

0801733

<https://www.phoenixcontact.com/us/products/0801733>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

---

## NS 35/ 7,5 UNPERF 2000MM - DIN rail, unperforated

0801681

<https://www.phoenixcontact.com/us/products/0801681>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

# UK 10 N RD - Feed-through terminal block

3022315

<https://www.phoenixcontact.com/us/products/3022315>



## NS 35/ 7,5 WH PERF 2000MM - DIN rail perforated

1204119

<https://www.phoenixcontact.com/us/products/1204119>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

---

## NS 35/ 7,5 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204122

<https://www.phoenixcontact.com/us/products/1204122>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

# UK 10 N RD - Feed-through terminal block

3022315

<https://www.phoenixcontact.com/us/products/3022315>



## NS 35/ 7,5 AL UNPERF 2000MM - DIN rail, unperforated

0801704

<https://www.phoenixcontact.com/us/products/0801704>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

---

## NS 35/ 7,5 ZN PERF 2000MM - DIN rail perforated

1206421

<https://www.phoenixcontact.com/us/products/1206421>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

# UK 10 N RD - Feed-through terminal block

3022315

<https://www.phoenixcontact.com/us/products/3022315>



## NS 35/ 7,5 ZN UNPERF 2000MM - DIN rail, unperforated

1206434

<https://www.phoenixcontact.com/us/products/1206434>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

---

## NS 35/ 7,5 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

0801762

<https://www.phoenixcontact.com/us/products/0801762>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

# UK 10 N RD - Feed-through terminal block

3022315

<https://www.phoenixcontact.com/us/products/3022315>



## NS 35/ 7,5 CAP - End cap

1206560

<https://www.phoenixcontact.com/us/products/1206560>

DIN rail end piece, for DIN rail NS 35/7.5



---

## NS 35/15 PERF 2000MM - DIN rail perforated

1201730

<https://www.phoenixcontact.com/us/products/1201730>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

# UK 10 N RD - Feed-through terminal block

3022315

<https://www.phoenixcontact.com/us/products/3022315>



## NS 35/15 UNPERF 2000MM - DIN rail, unperforated

1201714

<https://www.phoenixcontact.com/us/products/1201714>



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

---

## NS 35/15 WH PERF 2000MM - DIN rail perforated

0806602

<https://www.phoenixcontact.com/us/products/0806602>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: white

# UK 10 N RD - Feed-through terminal block

3022315

<https://www.phoenixcontact.com/us/products/3022315>



## NS 35/15 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204135

<https://www.phoenixcontact.com/us/products/1204135>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

---

## NS 35/15 AL UNPERF 2000MM - DIN rail, unperforated

1201756

<https://www.phoenixcontact.com/us/products/1201756>



DIN rail, unperforated, similar to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

# UK 10 N RD - Feed-through terminal block

3022315

<https://www.phoenixcontact.com/us/products/3022315>



## NS 35/15 ZN PERF 2000MM - DIN rail perforated

1206599

<https://www.phoenixcontact.com/us/products/1206599>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver

---

## NS 35/15 ZN UNPERF 2000MM - DIN rail, unperforated

1206586

<https://www.phoenixcontact.com/us/products/1206586>



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver

# UK 10 N RD - Feed-through terminal block

3022315

<https://www.phoenixcontact.com/us/products/3022315>



## NS 35/15 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201895

<https://www.phoenixcontact.com/us/products/1201895>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

---

## NS 35/15 CAP - End cap

1206573

<https://www.phoenixcontact.com/us/products/1206573>

DIN rail end piece, for DIN rail NS 35/15



# UK 10 N RD - Feed-through terminal block

3022315

<https://www.phoenixcontact.com/us/products/3022315>



## NS 35/15-2,3 UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201798

<https://www.phoenixcontact.com/us/products/1201798>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile 2.3 mm, color: silver

---

## ZB 10:UNBEDRUCKT - Zack marker strip

1053001

<https://www.phoenixcontact.com/us/products/1053001>



Zack marker strip, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 10.2 mm, lettering field size: 10.5 x 10.15 mm, Number of individual labels: 10

# UK 10 N RD - Feed-through terminal block

3022315


<https://www.phoenixcontact.com/us/products/3022315>



## ZB 10 CUS - Zack marker strip

0824941

<https://www.phoenixcontact.com/us/products/0824941>



Zack marker strip, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 10.2 mm, lettering field size: 10,15 x 10,5 mm, Number of individual labels: 10

---

## ZB10,LGS:FORTL.ZAHLEN - Zack marker strip

1053014

<https://www.phoenixcontact.com/us/products/1053014>



Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, printed horizontally: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 91 ... 100, mounting type: snapped, for terminal block width: 10.2 mm, lettering field size: 10,15 x 10,5 mm, Number of individual labels: 10

# UK 10 N RD - Feed-through terminal block




3022315

<https://www.phoenixcontact.com/us/products/3022315>

## ZB10,QR:FORTL.ZAHLEN - Zack marker strip

1053027

<https://www.phoenixcontact.com/us/products/1053027>




Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, Printed vertically: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 91 ... 100, mounting type: snapped, for terminal block width: 10.2 mm, lettering field size: 10,15 x 10,5 mm, Number of individual labels: 10

---

## ZB10,LGS:L1-N,PE - Marker for terminal blocks

1053412

<https://www.phoenixcontact.com/us/products/1053412>



Marker for terminal blocks, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, horizontal: L1, L2, L3, N, PE, L1, L2, L3, N, PE, mounting type: snapped, for terminal block width: 10.2 mm, lettering field size: 10,15 x 10,5 mm, Number of individual labels: 10

# UK 10 N RD - Feed-through terminal block



3022315

<https://www.phoenixcontact.com/us/products/3022315>

## ZB10,LGS:U-N - Marker for terminal blocks

1053438

<https://www.phoenixcontact.com/us/products/1053438>



Marker for terminal blocks, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, horizontal: U, V, W, N, GND, U, V, W, N, GND, mounting type: snapped, for terminal block width: 10.2 mm, lettering field size: 10,15 x 10,5 mm, Number of individual labels: 10

---

## UC-TM 10 - Marker for terminal blocks

0818069

<https://www.phoenixcontact.com/us/products/0818069>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 10.2 mm, lettering field size: 9.6 x 10.5 mm, Number of individual labels: 48

## UK 10 N RD - Feed-through terminal block

3022315

<https://www.phoenixcontact.com/us/products/3022315>



## UC-TM 10 CUS - Marker for terminal blocks

0824605

<https://www.phoenixcontact.com/us/products/0824605>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 10.2 mm, lettering field size: 9.6 x 10.5 mm, Number of individual labels: 48

---

## UCT-TM 10 - Marker for terminal blocks

0829142

<https://www.phoenixcontact.com/us/products/0829142>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, for terminal block width: 10.2 mm, lettering field size: 8.9 x 9.6 mm, Number of individual labels: 36

# UK 10 N RD - Feed-through terminal block

3022315

<https://www.phoenixcontact.com/us/products/3022315>



## UCT-TM 10 CUS - Marker for terminal blocks

0829623

<https://www.phoenixcontact.com/us/products/0829623>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 10.2 mm, lettering field size: 8.9 x 9.6 mm, Number of individual labels: 36

---

## PS-MT - Test plug

0311647

<https://www.phoenixcontact.com/us/products/0311647>



Test plug, number of positions: 1, color: silver

# UK 10 N RD - Feed-through terminal block

3022315

<https://www.phoenixcontact.com/us/products/3022315>



## PS-IH WH - Insulating sleeve

0311566

<https://www.phoenixcontact.com/us/products/0311566>

Insulating sleeve, number of positions: 1, color: white



---

## PS-IH RD - Insulating sleeve

0311579

<https://www.phoenixcontact.com/us/products/0311579>

Insulating sleeve, number of positions: 1, color: red



# UK 10 N RD - Feed-through terminal block

3022315

<https://www.phoenixcontact.com/us/products/3022315>



## PS-IH BU - Insulating sleeve

0311582

<https://www.phoenixcontact.com/us/products/0311582>

Insulating sleeve, number of positions: 1, color: blue



---

## PS-IH YE - Insulating sleeve

0311595

<https://www.phoenixcontact.com/us/products/0311595>

Insulating sleeve, number of positions: 1, color: yellow



# UK 10 N RD - Feed-through terminal block

3022315

<https://www.phoenixcontact.com/us/products/3022315>



## PS-IH GN - Insulating sleeve

0311605

<https://www.phoenixcontact.com/us/products/0311605>

Insulating sleeve, number of positions: 1, color: green



---

## PS-IH GY - Insulating sleeve

0311621

<https://www.phoenixcontact.com/us/products/0311621>

Insulating sleeve, number of positions: 1, color: gray



## UK 10 N RD - Feed-through terminal block

3022315

<https://www.phoenixcontact.com/us/products/3022315>



### PS-IH BK - Insulating sleeve

0311634

<https://www.phoenixcontact.com/us/products/0311634>

Insulating sleeve, number of positions: 1, color: black



---

### PS-IH VT - Insulating sleeve

0311618

<https://www.phoenixcontact.com/us/products/0311618>

Insulating sleeve, number of positions: 1, color: violet



# UK 10 N RD - Feed-through terminal block

3022315

<https://www.phoenixcontact.com/us/products/3022315>



## CLIPFIX 35 - End bracket

3022218

<https://www.phoenixcontact.com/us/products/3022218>

Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, width: 9.5 mm, color: gray



---

## CLIPFIX 35-5 - End bracket

3022276

<https://www.phoenixcontact.com/us/products/3022276>

Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, with parking option for FBS...5, FBS...6, KSS 5, KSS 6, width: 5.15 mm, color: gray



# UK 10 N RD - Feed-through terminal block

3022315

<https://www.phoenixcontact.com/us/products/3022315>




## E/NS 35 N - End bracket

0800886

<https://www.phoenixcontact.com/us/products/0800886>

End clamp, width: 9.5 mm, color: gray



---

## E/UK - End bracket

1201442

<https://www.phoenixcontact.com/us/products/1201442>

End bracket, Mounting on a DIN rail NS 32 or NS 35, material: PA, color: gray



# UK 10 N RD - Feed-through terminal block

3022315

<https://www.phoenixcontact.com/us/products/3022315>



## E/UK 1 - End bracket

1201413

<https://www.phoenixcontact.com/us/products/1201413>



End clamps, for supporting the ends of double-level and three-level terminal blocks, width: 10 mm, color: gray

---

## PSBJ 4/15/6 FARBLOS - Test plug strip

0303419

<https://www.phoenixcontact.com/us/products/0303419>



Test plug strip, number of positions: 1, color: transparent

# UK 10 N RD - Feed-through terminal block

3022315

<https://www.phoenixcontact.com/us/products/3022315>



## PSBJ 4/15/6 WH - Test plug strip

0303312

<https://www.phoenixcontact.com/us/products/0303312>



Test plug strip, number of positions: 1, color: white

---

## PSBJ 4/15/6 RD - Test plug strip

0303325

<https://www.phoenixcontact.com/us/products/0303325>



Test plug strip, number of positions: 1, color: red

# UK 10 N RD - Feed-through terminal block

3022315

<https://www.phoenixcontact.com/us/products/3022315>



## PSBJ 4/15/6 BU - Test plug strip

0303354

<https://www.phoenixcontact.com/us/products/0303354>



Test plug strip, number of positions: 1, color: blue

---

## PSBJ 4/15/6 YE - Test plug strip

0303367

<https://www.phoenixcontact.com/us/products/0303367>



Test plug strip, number of positions: 1, color: yellow

# UK 10 N RD - Feed-through terminal block

3022315

<https://www.phoenixcontact.com/us/products/3022315>



## PSBJ 4/15/6 GN - Test plug strip

0303370

<https://www.phoenixcontact.com/us/products/0303370>



Test plug strip, number of positions: 1, color: green

---

## PSBJ 4/15/6 VT - Test plug strip

0303383

<https://www.phoenixcontact.com/us/products/0303383>



Test plug strip, number of positions: 1, color: violet

# UK 10 N RD - Feed-through terminal block

3022315

<https://www.phoenixcontact.com/us/products/3022315>



## PSBJ 4/15/6 GY - Test plug strip

0303396

<https://www.phoenixcontact.com/us/products/0303396>



Test plug strip, number of positions: 1, color: gray

---

## PSBJ 4/15/6 BK - Test plug strip

0303406

<https://www.phoenixcontact.com/us/products/0303406>



Test plug strip, number of positions: 1, color: black

## UK 10 N RD - Feed-through terminal block

3022315

<https://www.phoenixcontact.com/us/products/3022315>



## PSB 4/7/6 - Test plug strip

0303299

<https://www.phoenixcontact.com/us/products/0303299>

Test plug strip, number of positions: 1, color: silver



---

## D-UK 4/10 - End cover

3003020

<https://www.phoenixcontact.com/us/products/3003020>

End cover, depth: 35.9 mm, width: 1.8 mm, height: 42.5 mm, color: gray



# UK 10 N RD - Feed-through terminal block

3022315

<https://www.phoenixcontact.com/us/products/3022315>



## D-UK 4/10 BU - End cover

3003101

<https://www.phoenixcontact.com/us/products/3003101>

End cover, depth: 47 mm, width: 1.8 mm, height: 42.5 mm, color: blue



---

## SZS 1,0X4,0 VDE - Screwdriver

1205066

<https://www.phoenixcontact.com/us/products/1205066>

Screwdriver, slot-headed, VDE insulated, size: 1.0 x 4.0 x 100 mm, 2-component grip, with non-slip grip



---

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)