

FBSTB 2-5 - Plug-in bridge



3024643

<https://www.phoenixcontact.com/ca/products/3024643>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Plug-in bridge, pitch: 5.2 mm, number of positions: 2, color: red

Commercial data

Item number	3024643
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	BE2Z
Product key	BE2Z2X
Catalog page	Page 100 (CL-2007)
GTIN	4017918147082
Weight per piece (including packing)	2.41 g
Weight per piece (excluding packing)	2.41 g
Customs tariff number	85366990
Country of origin	PL

FBSTB 2-5 - Plug-in bridge

3024643

<https://www.phoenixcontact.com/ca/products/3024643>



Technical data

Product properties

Product type	Jumper
Number of positions	2
Pitch	5.2 mm

Data management status

Article revision	04
------------------	----

Electrical properties

Maximum load current	32 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.)
----------------------	---

Connection data

Maximum load current	32 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.)
----------------------	---

Dimensions

Pitch	5.2 mm
-------	--------

Material specifications

Color	red (RAL 3001)
Material	Copper
Flammability rating according to UL 94	V0
Insulating material	PA

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-60 °C ... 105 °C
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (storage/transport)	30 % ... 70 %

Mounting

Mounting type	Plug-in mounting
---------------	------------------

FBSTB 2-5 - Plug-in bridge

3024643

<https://www.phoenixcontact.com/ca/products/3024643>



Classifications

ECLASS

ECLASS-11.0	27141140
ECLASS-12.0	27141140
ECLASS-13.0	27250303

ETIM

ETIM 9.0	EC000489
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

FBSTB 2-5 - Plug-in bridge

3024643

<https://www.phoenixcontact.com/ca/products/3024643>



Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd
8240 Parkhill Drive
Milton, Ontario L9T 5V7
1-800-890-2820
cdinfo@phoenixcontact.ca