

https://www.phoenixcontact.com/sg/products/3032318



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Plug-in bridge, with punched-out middle contact tab, pitch: 5.2 mm, number of positions: 3, pin assignment: 1,3, color: red

Your advantages

• The 2- to 50-pos. jumpers can bridge up to 50 terminal blocks in the two bridge shafts of the CLIPLINE complete system in one step

Commercial data

Item number	3032318
Packing unit	50 pc
Minimum order quantity	50 pc
Sales key	****
Product key	BE2Z2X
GTIN	4046356126168
Weight per piece (including packing)	2.166 g
Weight per piece (excluding packing)	2.16 g
Customs tariff number	85366990
Country of origin	PL



https://www.phoenixcontact.com/sg/products/3032318



Technical data

Product properties

Product type	Jumper
Number of positions	3
Pitch	5.2 mm

Electrical properties

Maximum load current	24 A (The current values for the jumpers can deviate when used
	in different modular terminal blocks. The precise values can be
	found in the accessories data for the respective modular terminal
	blocks.)

Connection data

Maximum load current	24 A (The current values for the jumpers can deviate when used
	in different modular terminal blocks. The precise values can be
	found in the accessories data for the respective modular terminal
	blocks.)

Dimensions

Material specifications

Color	red
Material	Copper
Flammability rating according to UL 94	V0
Insulating material	PA

Mechanical properties

Technical data

Pin assignment	1, 3
· · · · · · · · · · · · · · · · · · ·	•

Mounting

Mounting type	Plug-in mounting
3 3 7	3



https://www.phoenixcontact.com/sg/products/3032318



Classifications

ECLASS

ECLASS-11.0	27141140
ECLASS-12.0	27141140
ECLASS-13.0	27250303
ETIM	
ETIM 9.0	EC000489
LINODOO	

UNSPSC

3032318

https://www.phoenixcontact.com/sg/products/3032318



Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT SEA Pte. Ltd. 105 Eunos Avenue 3, #04-00 Singapore 409836 +65 6228 4900 marketing@phoenixcontact.com.sg