

# S-ME 4 - Switching lock

3035758

<https://www.phoenixcontact.com/us/products/3035758>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Switching lock, width: 6.2 mm, height: 12 mm, color: white



## Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 3035758             |
| Packing unit                         | 10 pc               |
| Minimum order quantity               | 10 pc               |
| Sales key                            | BE29                |
| Product key                          | BE2ZWX              |
| Catalog page                         | Page 105 (C-1-2019) |
| GTIN                                 | 4046356521840       |
| Weight per piece (including packing) | 0.47 g              |
| Weight per piece (excluding packing) | 0.366 g             |
| Customs tariff number                | 39269097            |
| Country of origin                    | PL                  |

# S-ME 4 - Switching lock

3035758

<https://www.phoenixcontact.com/us/products/3035758>



## Technical data

### Product properties

|              |                |
|--------------|----------------|
| Product type | Switching lock |
|--------------|----------------|

### Dimensions

|        |        |
|--------|--------|
| Width  | 6.2 mm |
| Height | 12 mm  |

### Material specifications

|                                        |       |
|----------------------------------------|-------|
| Color                                  | white |
| Material                               | PA    |
| Flammability rating according to UL 94 | V0    |
| Insulating material                    | PA    |

### Environmental and real-life conditions

#### Ambient conditions

|                                          |                                                                           |
|------------------------------------------|---------------------------------------------------------------------------|
| Ambient temperature (operation)          | -60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)       |
| Ambient temperature (storage/transport)  | -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C) |
| Ambient temperature (assembly)           | -5 °C ... 70 °C                                                           |
| Ambient temperature (actuation)          | -5 °C ... 70 °C                                                           |
| Permissible humidity (storage/transport) | 30 % ... 70 %                                                             |

# S-ME 4 - Switching lock

3035758

<https://www.phoenixcontact.com/us/products/3035758>



## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27141190 |
| ECLASS-12.0 | 27141190 |
| ECLASS-13.0 | 27141190 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC002848 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# S-ME 4 - Switching lock

3035758

<https://www.phoenixcontact.com/us/products/3035758>



## Environmental product compliance

|                                         |                                          |
|-----------------------------------------|------------------------------------------|
| EU RoHS                                 |                                          |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |
| China RoHS                              |                                          |
| Environment friendly use period (EFUP)  | EFUP-E                                   |
|                                         | No hazardous substances above the limits |
| EU REACH SVHC                           |                                          |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)