

# C-ME 4/2 - Connecting bridge

3035759

<https://www.phoenixcontact.com/sg/products/3035759>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Connection bridge, for connecting 2 test disconnect terminal blocks

## Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 3035759             |
| Packing unit                         | 10 pc               |
| Minimum order quantity               | 10 pc               |
| Sales key                            | *****               |
| Product key                          | BE2ZWX              |
| Catalog page                         | Page 105 (C-1-2019) |
| GTIN                                 | 4046356521857       |
| Weight per piece (including packing) | 1.047 g             |
| Weight per piece (excluding packing) | 0.815 g             |
| Customs tariff number                | 85389099            |
| Country of origin                    | PL                  |

# C-ME 4/2 - Connecting bridge

3035759

<https://www.phoenixcontact.com/sg/products/3035759>



## Technical data

### Product properties

|                     |               |
|---------------------|---------------|
| Product type        | Switch module |
| Number of positions | 2             |

### Dimensions

|        |         |
|--------|---------|
| Width  | 12.2 mm |
| Height | 5.2 mm  |
| Depth  | 23.8 mm |

### Material specifications

|                                        |        |
|----------------------------------------|--------|
| Color                                  | orange |
| Material                               | PA     |
| Flammability rating according to UL 94 | V0     |

### Environmental and real-life conditions

#### Ambient conditions

|                                          |                                                                           |
|------------------------------------------|---------------------------------------------------------------------------|
| Ambient temperature (operation)          | -60 °C ... 85 °C                                                          |
| Ambient temperature (storage/transport)  | -25 °C ... 55 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C) |
| Ambient temperature (assembly)           | -5 °C ... 70 °C                                                           |
| Ambient temperature (actuation)          | -5 °C ... 70 °C                                                           |
| Permissible humidity (storage/transport) | 30 % ... 70 %                                                             |

# C-ME 4/2 - Connecting bridge

3035759

<https://www.phoenixcontact.com/sg/products/3035759>



## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27141190 |
| ECLASS-12.0 | 27141190 |
| ECLASS-13.0 | 27141190 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC002848 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# C-ME 4/2 - Connecting bridge



3035759

<https://www.phoenixcontact.com/sg/products/3035759>

## Environmental product compliance

|                                         |                                          |
|-----------------------------------------|------------------------------------------|
| EU RoHS                                 |                                          |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |
| China RoHS                              |                                          |
| Environment friendly use period (EFUP)  | EFUP-E                                   |
|                                         | No hazardous substances above the limits |
| EU REACH SVHC                           |                                          |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT SEA Pte. Ltd.  
105 Eunos Avenue 3, #04-00  
Singapore 409836  
+65 6228 4900  
[marketing@phoenixcontact.com.sg](mailto:marketing@phoenixcontact.com.sg)