

# PAI-4-FIX-5/6 OG - Test adapter



3035974

<https://www.phoenixcontact.com/pc/products/3035974>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch



## Your advantages

- Make contact and latch securely to any point in the function shaft
- Test adapter for accommodating safety test plugs with a 4 mm diameter

## Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 3035974             |
| Packing unit                         | 10 pc               |
| Minimum order quantity               | 10 pc               |
| Product key                          | BE2Z3X              |
| Catalog page                         | Page 105 (C-1-2019) |
| GTIN                                 | 4046356520560       |
| Weight per piece (including packing) | 1.41 g              |
| Weight per piece (excluding packing) | 1.2 g               |
| Customs tariff number                | 85366990            |
| Country of origin                    | PL                  |

# PAI-4-FIX-5/6 OG - Test adapter



3035974

<https://www.phoenixcontact.com/pc/products/3035974>

## Technical data

### Notes

|         |  |
|---------|--|
| General | Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in |
| General | Do not plug in while the power is connected  |
| General | Latching testing accessories, therefore only suitable for being plugged in once            |

### Product properties

|                     |             |
|---------------------|-------------|
| Product type        | Test socket |
| Number of positions | 1           |

### Electrical properties

|                      |       |
|----------------------|-------|
| Maximum load current | 10 A  |
| Max. voltage         | 250 V |

### Connection data

|                      |                    |
|----------------------|--------------------|
| Maximum load current | 10 A               |
| Connection method    | Plug-in connection |

### Dimensions

|              |         |
|--------------|---------|
| Width        | 5.8 mm  |
| Height       | 5.8 mm  |
| Depth        | 45.3 mm |
| Diameter     | 5.8 mm  |
| Pin diameter | 2.4 mm  |

### Material specifications

|  |             |
|--|-------------|
| Color  | orange      |
| Material   | Copper      |
| Flammability rating according to UL 94                           | V0          |
| Insulating material  | PA          |
| Static insulating material application in cold                   | -60 °C      |
| Relative insulation material temperature index (Elec., UL 746 B) | 130 °C      |
| Fire protection for rail vehicles (DIN EN 45545-2) R22           | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R23           | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R24           | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R26           | HL 1 - HL 3 |
| Surface flammability NFPA 130 (ASTM E 162)                       | passed      |
| Specific optical density of smoke NFPA 130 (ASTM E 662)          | passed      |
| Smoke gas toxicity NFPA 130 (SMP 800C)                           | passed      |

### Mechanical properties

# PAI-4-FIX-5/6 OG - Test adapter



3035974

<https://www.phoenixcontact.com/pc/products/3035974>

## Mechanical data

|                             |   |
|-----------------------------|---|
| Insertion/withdrawal cycles | 1 |
|-----------------------------|---|

## Environmental and real-life conditions

### Ambient conditions

|  |   |
|--|---|
| Ambient temperature (operation)          | -60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)       |
| Ambient temperature (storage/transport)  | -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C) |
| Ambient temperature (assembly)           | -5 °C ... 70 °C   |
| Ambient temperature (actuation)          | -5 °C ... 70 °C   |
| Permissible humidity (storage/transport) | 30 % ... 70 %   |

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG

Flachsmarktstraße 8

D-32825 Blomberg

+49 (0) 5235-3 00

[info@phoenixcontact.com](mailto:info@phoenixcontact.com)