

Isolating plugs - P-DI - 3036783

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Isolating plugs, Length: 10.8 mm, Width: 3.5 mm, Height: 23.1 mm, Color: orange

Why buy this product

- ✓ Can be used in all ...-TG disconnect terminal blocks from the CLIPLINE complete system
- ✓ The P-DI isolating plug can be easily removed to release the connection and then "parked" back to front in the disconnect zone

Key commercial data

Packing unit	50 pc
GTIN	 4 017918 901998
Weight per Piece (excluding packing)	0.35 g
Custom tariff number	85389099
Country of origin	Germany

Technical data

General

Color	orange
Insulating material	PA
Inflammability class according to UL 94	V2

Dimensions

Width	3.5 mm
Length	10.8 mm
Height	23.1 mm

General

Maximum load current (lower level)	20 A
Temperature index, insulating material (DIN EN 60216-1 (VDE 0304-21))	125 °C

Isolating plugs - P-DI - 3036783

Classifications

eCl@ss

eCl@ss 4.0	27141199
eCl@ss 4.1	27141199
eCl@ss 5.0	27141145
eCl@ss 5.1	27141145
eCl@ss 6.0	27141120
eCl@ss 7.0	27141120
eCl@ss 8.0	27141126

ETIM

ETIM 2.0	EC000897
ETIM 3.0	EC000897
ETIM 4.0	EC000902
ETIM 5.0	EC000902

UNSPSC

UNSPSC 6.01	30211812
UNSPSC 7.0901	39121410
UNSPSC 11	39121411
UNSPSC 12.01	39121411
UNSPSC 13.2	39121411

Approvals

Approvals

Approvals

CSA / BV

Ex Approvals

Approvals submitted

Approval details

CSA 	
Nominal current I _N	15 A

Isolating plugs - P-DI - 3036783

Approvals

BV
