Specifications



Photo is representative





Eaton 303687

IN63H3-63W-1. Switch-disconnector, 3p, 6300 A, withdrawable

General specifications		
PRODUCT NAME	Eaton Moeller series IZMX/INX switch- disconnector	
CATALOG NUMBER	303687	
MODEL CODE	IN63H3-63W-1	
EAN	9010238192225	
PRODUCT LENGTH/DEPTH	474 mm	
PRODUCT HEIGHT	524 mm	
PRODUCT WIDTH	909 mm	
PRODUCT WEIGHT	157.4 kg	
COMPLIANCES	IEC/EN 60947 RoHS conform	
GLOBAL CATALOG	303687	



Dradust spacification	5
Product specification	5
AMPERAGE RATING	6300 A
FRAME	IN63
POLLUTION DEGREE	3
MOUNTING METHOD	Withdrawable
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	8000 V AC
UTILIZATION CATEGORY	В
DIRECTION OF INCOMING SUPPLY	As required
AMBIENT OPERATING TEMPERATURE - MAX	70 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT STORAGE TEMPERATURE - MAX	70 °C
AMBIENT STORAGE TEMPERATURE - MIN	-40 °C
HEAT DISSIPATION AT RATED CURRENT WITH FIXED MOUNTING	620 W
NUMBER OF STANDARD MECHANICAL OPERATIONS PER HOUR - MAX	60
OPENING DELAY (TOTAL)	40 ms
POWER OF WITHDRAWABLE SWITCH WITH CASSETTE	1550 W
RATED INSULATION VOLTAGE (UI)	1000 V
LIFESPAN, MECHANICAL	5000 operations 8000 operations (switching capacity, with maintenance)
OVERVOLTAGE CATEGORY	III
WEIGHT OF CASSETTE VERSION (3-POLE)	103 kg
WEIGHT OF FIXED WITHDRAWABLE VERSION (3-POLE)	157 kg
PROTECTION	None
VOLTAGE RATING AT AC	690 V
NUMBER OF POLES	Three-pole

Resources	
CATALOGS	eaton-acb-izm63-catalog- ca0135003en-en-us.pdf
INSTALLATION VIDEOS	Air Circuit Breakers Series IZMX

DEGREE OF PROTECTION	IP20 IP41 with door sealing frame IP54 with protective cover
CLOSING DELAY VIA SPRING RELEASE	40 ms
LIFESPAN, ELECTRICAL	3000 operations
ТҮРЕ	 Air circuit breakers/switch- disconnector Open switch- disconnector
RATED SHORT-CIRCUIT MAKING CAPACITY UP TO 440 V, 50/60 HZ	220 kA
RATED SHORT-CIRCUIT MAKING CAPACITY UP TO 690 V, 50/60 HZ	220 kA
RATED SHORT-TIME WITHSTAND CURRENT (T = 1 S)	100 kA
RATED SHORT-TIME WITHSTAND CURRENT AT 50/60 HZ (T = 3 S)	65 kA
RATED UNINTERRUPTED CURRENT (IU) AT 50°C	6200 A
RATED UNINTERRUPTED CURRENT (IU) AT 60°C	5600 A
RATED UNINTERRUPTED CURRENT (IU) AT 70°C	5100 A

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	



Eaton Corporation plc

Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.









