

# ST 2,5-TWIN YE - Feed-through terminal block



3037313

<https://www.phoenixcontact.com/ca/products/3037313>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Feed-through terminal block, nom. voltage: 800 V, nominal current: 24 A, number of connections: 3, connection method: Spring-cage connection, Rated cross section: 2.5 mm<sup>2</sup>, cross section: 0.08 mm<sup>2</sup> - 4 mm<sup>2</sup>, mounting type: NS 35/7,5, NS 35/15, color: yellow

## Your advantages

- The consistent double function shaft offers every opportunity for time-saving potential distribution and accommodating test accessories
- User-friendly implementation of all potential branching tasks
- Space-saving and practical multi-conductor connection without additional bridges

## Commercial data

|                                      |                                |
|--------------------------------------|--------------------------------|
| Item number                          | 3037313                        |
| Packing unit                         | 50 pc                          |
| Minimum order quantity               | 50 pc                          |
| Note                                 | Made to order (non-returnable) |
| Sales key                            | BE02                           |
| Product key                          | BE2112                         |
| GTIN                                 | 4017918599690                  |
| Weight per piece (including packing) | 7.876 g                        |
| Weight per piece (excluding packing) | 7.719 g                        |
| Customs tariff number                | 85369010                       |
| Country of origin                    | DE                             |

# ST 2,5-TWIN YE - Feed-through terminal block



3037313

<https://www.phoenixcontact.com/ca/products/3037313>

## Technical data

### Notes

#### General

|      |                                                                                              |
|------|----------------------------------------------------------------------------------------------|
| Note | The max. load current must not be exceeded by the total current of all connected conductors. |
|------|----------------------------------------------------------------------------------------------|

### Product properties

|                       |                                |
|-----------------------|--------------------------------|
| Product type          | Multi-conductor terminal block |
| Number of connections | 3                              |
| Number of rows        | 1                              |
| Potentials            | 1                              |

#### Data management status

|                  |    |
|------------------|----|
| Article revision | 07 |
|------------------|----|

#### Insulation characteristics

|                      |     |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution  | 3   |

### Electrical properties

|                                                 |        |
|-------------------------------------------------|--------|
| Rated surge voltage                             | 8 kV   |
| Maximum power dissipation for nominal condition | 0.77 W |

### Connection data

|                                                                                           |                                                                                                                                                                |
|-------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Number of connections per level                                                           | 3                                                                                                                                                              |
| Nominal cross section                                                                     | 2.5 mm <sup>2</sup>                                                                                                                                            |
| Stripping length                                                                          | 8 mm ... 10 mm                                                                                                                                                 |
| Internal cylindrical gage                                                                 | A3                                                                                                                                                             |
| Connection in acc. with standard                                                          | IEC 60947-7-1                                                                                                                                                  |
| Conductor cross section rigid                                                             | 0.08 mm <sup>2</sup> ... 4 mm <sup>2</sup>                                                                                                                     |
| Cross section AWG                                                                         | 28 ... 12 (converted acc. to IEC)                                                                                                                              |
| Conductor cross section flexible                                                          | 0.08 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>                                                                                                                   |
| Conductor cross section, flexible [AWG]                                                   | 28 ... 14 (converted acc. to IEC)                                                                                                                              |
| Conductor cross-section flexible (ferrule without plastic sleeve)                         | 0.14 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>                                                                                                                   |
| Flexible conductor cross section (ferrule with plastic sleeve)                            | 0.14 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>                                                                                                                   |
| 2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve | 0.5 mm <sup>2</sup>                                                                                                                                            |
| Nominal current                                                                           | 24 A (with 4 mm <sup>2</sup> conductor cross section)                                                                                                          |
| Maximum load current                                                                      | 28 A (in case of a 4 mm <sup>2</sup> conductor cross section, the maximum load current must not be exceeded by the total current of all connected conductors.) |
| Nominal voltage                                                                           | 800 V                                                                                                                                                          |
| Nominal cross section                                                                     | 2.5 mm <sup>2</sup>                                                                                                                                            |

# ST 2,5-TWIN YE - Feed-through terminal block



3037313

<https://www.phoenixcontact.com/ca/products/3037313>

## Ex data

### Rated data (ATEX/IECEx)

|                                                                          |                                      |
|--------------------------------------------------------------------------|--------------------------------------|
| Identification                                                           | Ex II 2 GD Ex eb IIC Gb              |
| Operating temperature range                                              | -60 °C ... 110 °C                    |
| Ex-certified accessories                                                 | 3030488 D-ST 2,5-TWIN                |
|                                                                          | 3030789 ATP-ST-TWIN                  |
|                                                                          | 3036602 DS-ST 2,5                    |
|                                                                          | 1204517 SZF 1-0,6X3,5                |
|                                                                          | 3022276 CLIPFIX 35-5                 |
|                                                                          | 3022218 CLIPFIX 35                   |
| List of bridges                                                          | Plug-in bridge / FBS 2-5 / 3030161   |
|                                                                          | Plug-in bridge / FBS 3-5 / 3030174   |
|                                                                          | Plug-in bridge / FBS 4-5 / 3030187   |
|                                                                          | Plug-in bridge / FBS 5-5 / 3030190   |
|                                                                          | Plug-in bridge / FBS 10-5 / 3030213  |
|                                                                          | Plug-in bridge / FBS 20-5 / 3030226  |
| Bridge data                                                              | 22.5 A / 2.5 mm <sup>2</sup>         |
| Ex temperature increase                                                  | 40 K (23.4 A / 2.5 mm <sup>2</sup> ) |
| Rated voltage                                                            | 550 V                                |
| for bridging with bridge                                                 | 550 V                                |
| - At bridging between non-adjacent terminal blocks                       | 352 V                                |
| - At bridging between non-adjacent terminal blocks via PE terminal block | 352 V                                |
| - At cut-to-length bridging with cover                                   | 220 V                                |
| - At cut-to-length bridging with partition plate                         | 275 V                                |
| Rated insulation voltage                                                 | 500 V                                |
| output                                                                   | (Permanent)                          |

### Ex level General

|                      |         |
|----------------------|---------|
| Rated current        | 21 A    |
| Maximum load current | 24.5 A  |
| Contact resistance   | 1.08 mΩ |

### Ex connection data General

|                              |                                              |
|------------------------------|----------------------------------------------|
| Nominal cross section        | 2.5 mm <sup>2</sup>                          |
| Rated cross section AWG      | 14                                           |
| Connection capacity rigid    | 0.08 mm <sup>2</sup> ... 4 mm <sup>2</sup>   |
| Connection capacity AWG      | 28 ... 12                                    |
| Connection capacity flexible | 0.08 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> |
| Connection capacity AWG      | 28 ... 14                                    |

## Dimensions

|       |        |
|-------|--------|
| Width | 5.2 mm |
|-------|--------|

# ST 2,5-TWIN YE - Feed-through terminal block



3037313

<https://www.phoenixcontact.com/ca/products/3037313>

## Material specifications

|                                                                  |             |
|------------------------------------------------------------------|-------------|
| Color                                                            | yellow      |
| Flammability rating according to UL 94                           | V0          |
| Insulating material group                                        | I           |
| Insulating material                                              | PA          |
| Static insulating material application in cold                   | -60 °C      |
| Relative insulation material temperature index (Elec., UL 746 B) | 130 °C      |
| Fire protection for rail vehicles (DIN EN 45545-2) R22           | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R23           | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R24           | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R26           | HL 1 - HL 3 |
| Surface flammability NFPA 130 (ASTM E 162)                       | passed      |
| Specific optical density of smoke NFPA 130 (ASTM E 662)          | passed      |
| Smoke gas toxicity NFPA 130 (SMP 800C)                           | passed      |

## Electrical tests

### Surge voltage test

|        |             |
|--------|-------------|
| Result | Test passed |
|--------|-------------|

### Temperature-rise test

|                                                  |                                     |
|--------------------------------------------------|-------------------------------------|
| Requirement temperature-rise test                | Increase in temperature $\leq 45$ K |
| Result                                           | Test passed                         |
| Short-time withstand current 2.5 mm <sup>2</sup> | 0.3 kA                              |
| Short-time withstand current 4 mm <sup>2</sup>   | 0.48 kA                             |
| Result                                           | Test passed                         |

### Power-frequency withstand voltage

|                       |             |
|-----------------------|-------------|
| Test voltage setpoint | 2 kV        |
| Result                | Test passed |

## Mechanical properties

### Mechanical data

|                 |     |
|-----------------|-----|
| Open side panel | Yes |
|-----------------|-----|

## Mechanical tests

### Mechanical strength

|        |             |
|--------|-------------|
| Result | Test passed |
|--------|-------------|

### Attachment on the carrier

|                         |             |
|-------------------------|-------------|
| DIN rail/fixing support | NS 32/NS 35 |
| Result                  | Test passed |

### Test for conductor damage and slackening

|                |                |
|----------------|----------------|
| Rotation speed | 10 (+/- 2) rpm |
|----------------|----------------|

# ST 2,5-TWIN YE - Feed-through terminal block



3037313

<https://www.phoenixcontact.com/ca/products/3037313>

|                                |                               |
|--------------------------------|-------------------------------|
| Revolutions                    | 135                           |
| Conductor cross section/weight | 0.14 mm <sup>2</sup> / 0.2 kg |
|                                | 2.5 mm <sup>2</sup> / 0.7 kg  |
|                                | 4 mm <sup>2</sup> / 0.9 kg    |
| Result                         | Test passed                   |

## Environmental and real-life conditions

### Aging

|                    |             |
|--------------------|-------------|
| Temperature cycles | 192         |
| Result             | Test passed |

### Oscillation/broadband noise

|                        |                                                |
|------------------------|------------------------------------------------|
| Specification          | DIN EN 50155 (VDE 0115-200):2008-03            |
| Spectrum               | Service life test category 2, bogie-mounted    |
| Frequency              | $f_1 = 5 \text{ Hz}$ to $f_2 = 250 \text{ Hz}$ |
| ASD level              | 6.12 (m/s <sup>2</sup> ) <sup>2</sup> /Hz      |
| Acceleration           | 3.12g                                          |
| Test duration per axis | 5 h                                            |
| Test directions        | X-, Y- and Z-axis                              |
| Result                 | Test passed                                    |

### Shocks

|                                |                                   |
|--------------------------------|-----------------------------------|
| Pulse shape                    | Half-sine                         |
| Acceleration                   | 5g                                |
| Shock duration                 | 30 ms                             |
| Number of shocks per direction | 3                                 |
| Test directions                | X-, Y- and Z-axis (pos. and neg.) |
| Result                         | Test passed                       |

### Ambient conditions

|                                          |                                                                           |
|------------------------------------------|---------------------------------------------------------------------------|
| Ambient temperature (storage/transport)  | -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C) |
| Ambient temperature (assembly)           | -5 °C ... 70 °C                                                           |
| Ambient temperature (actuation)          | -5 °C ... 70 °C                                                           |
| Permissible humidity (storage/transport) | 30 % ... 70 %                                                             |

## Standards and regulations

|                                  |               |
|----------------------------------|---------------|
| Connection in acc. with standard | IEC 60947-7-1 |
|----------------------------------|---------------|

## Mounting

|               |           |
|---------------|-----------|
| Mounting type | NS 35/7,5 |
|               | NS 35/15  |

# ST 2,5-TWIN YE - Feed-through terminal block



3037313

<https://www.phoenixcontact.com/ca/products/3037313>

## Drawings

Circuit diagram



# ST 2,5-TWIN YE - Feed-through terminal block



3037313

<https://www.phoenixcontact.com/ca/products/3037313>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27141120 |
|-------------|----------|

### ETIM

|          |          |
|----------|----------|
| ETIM 8.0 | EC000897 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# ST 2,5-TWIN YE - Feed-through terminal block



3037313

<https://www.phoenixcontact.com/ca/products/3037313>

## Environmental product compliance

|                                         |                                          |
|-----------------------------------------|------------------------------------------|
| EU RoHS                                 |                                          |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |
| China RoHS                              |                                          |
| Environment friendly use period (EFUP)  | EFUP-E                                   |
|                                         | No hazardous substances above the limits |
| EU REACH SVHC                           |                                          |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |



# ST 2,5-TWIN YE - Feed-through terminal block



3037313

<https://www.phoenixcontact.com/ca/products/3037313>

## Accessories

**i** Note: Applying some accessories below might limit this product.

### FBS 20-5 - Plug-in bridge

3030226

<https://www.phoenixcontact.com/ca/products/3030226>



Plug-in bridge, pitch: 5.2 mm, number of positions: 20, color: red

**i** Max. current carrying capacity: 24 A

### FBS 10-5 - Plug-in bridge

3030213

<https://www.phoenixcontact.com/ca/products/3030213>



Plug-in bridge, pitch: 5.2 mm, number of positions: 10, length: 23 mm, color: red

**i** Max. current carrying capacity: 24 A

# ST 2,5-TWIN YE - Feed-through terminal block



3037313

<https://www.phoenixcontact.com/ca/products/3037313>

## FBS 5-5 - Plug-in bridge

3030190

<https://www.phoenixcontact.com/ca/products/3030190>



Plug-in bridge, pitch: 5.2 mm, number of positions: 5, length: 23 mm, color: red

 Max. current carrying capacity: 24 A

---

## FBS 4-5 - Plug-in bridge

3030187

<https://www.phoenixcontact.com/ca/products/3030187>



Plug-in bridge, pitch: 5.2 mm, number of positions: 4, length: 23 mm, color: red

 Max. current carrying capacity: 24 A

# ST 2,5-TWIN YE - Feed-through terminal block



3037313

<https://www.phoenixcontact.com/ca/products/3037313>

## FBS 3-5 - Plug-in bridge

3030174

<https://www.phoenixcontact.com/ca/products/3030174>



Plug-in bridge, pitch: 5.2 mm, number of positions: 3, length: 23 mm, color: red

 Max. current carrying capacity: 24 A

---

## FBS 2-5 - Plug-in bridge

3030161

<https://www.phoenixcontact.com/ca/products/3030161>



Plug-in bridge, pitch: 5.2 mm, number of positions: 2, length: 23 mm, color: red

 Max. current carrying capacity: 24 A

# ST 2,5-TWIN YE - Feed-through terminal block



3037313

<https://www.phoenixcontact.com/ca/products/3037313>

## FBS 50-5 - Plug-in bridge

3038930

<https://www.phoenixcontact.com/ca/products/3038930>



Plug-in bridge, pitch: 5.2 mm, number of positions: 50, color: red

 Max. current carrying capacity: 24 A

---

## FBSR 2-5 - Plug-in bridge

3033702

<https://www.phoenixcontact.com/ca/products/3033702>



Plug-in bridge, pitch: 5.2 mm, number of positions: 2, color: red

 Max. current carrying capacity: 17.5 A

# ST 2,5-TWIN YE - Feed-through terminal block



3037313

<https://www.phoenixcontact.com/ca/products/3037313>

## FBSR 3-5 - Plug-in bridge

3001591

<https://www.phoenixcontact.com/ca/products/3001591>



Plug-in bridge, pitch: 5.2 mm, number of positions: 3, color: red

 Max. current carrying capacity: 17.5 A

---

## FBSR 4-5 - Plug-in bridge

3001592

<https://www.phoenixcontact.com/ca/products/3001592>



Plug-in bridge, pitch: 5.2 mm, number of positions: 4, color: red

 Max. current carrying capacity: 17.5 A

# ST 2,5-TWIN YE - Feed-through terminal block



3037313

<https://www.phoenixcontact.com/ca/products/3037313>

## FBSR 5-5 - Plug-in bridge

3001593

<https://www.phoenixcontact.com/ca/products/3001593>



Plug-in bridge, pitch: 5.2 mm, number of positions: 5, color: red

 Max. current carrying capacity: 17.5 A

---

## FBSR 10-5 - Plug-in bridge

3033710

<https://www.phoenixcontact.com/ca/products/3033710>



Plug-in bridge, pitch: 5.2 mm, number of positions: 10, color: red

 Max. current carrying capacity: 17.5 A

# ST 2,5-TWIN YE - Feed-through terminal block



3037313

<https://www.phoenixcontact.com/ca/products/3037313>

## FBS 2-5 BU - Plug-in bridge

3036877

<https://www.phoenixcontact.com/ca/products/3036877>



Plug-in bridge, pitch: 5.2 mm, number of positions: 2, color: blue

 Max. current carrying capacity: 24 A

---

## FBS 3-5 BU - Plug-in bridge

3036880

<https://www.phoenixcontact.com/ca/products/3036880>



Plug-in bridge, pitch: 5.2 mm, number of positions: 3, color: blue

 Max. current carrying capacity: 24 A

# ST 2,5-TWIN YE - Feed-through terminal block



3037313

<https://www.phoenixcontact.com/ca/products/3037313>

## FBS 4-5 BU - Plug-in bridge

3036893

<https://www.phoenixcontact.com/ca/products/3036893>



Plug-in bridge, pitch: 5.2 mm, number of positions: 4, color: blue

 Max. current carrying capacity: 24 A

---

## FBS 5-5 BU - Plug-in bridge

3036903

<https://www.phoenixcontact.com/ca/products/3036903>



Plug-in bridge, pitch: 5.2 mm, number of positions: 5, color: blue

 Max. current carrying capacity: 24 A



# ST 2,5-TWIN YE - Feed-through terminal block



3037313

<https://www.phoenixcontact.com/ca/products/3037313>

## FBS 10-5 BU - Plug-in bridge

3036916

<https://www.phoenixcontact.com/ca/products/3036916>



Plug-in bridge, pitch: 5.2 mm, number of positions: 10, color: blue

 Max. current carrying capacity: 24 A

---

## FBS 20-5 BU - Plug-in bridge

3036929

<https://www.phoenixcontact.com/ca/products/3036929>



Plug-in bridge, pitch: 5.2 mm, number of positions: 20, color: blue

 Max. current carrying capacity: 24 A

# ST 2,5-TWIN YE - Feed-through terminal block



3037313

<https://www.phoenixcontact.com/ca/products/3037313>

## FBS 50-5 BU - Plug-in bridge

3032114

<https://www.phoenixcontact.com/ca/products/3032114>



Plug-in bridge, pitch: 5.2 mm, number of positions: 50, color: blue

 Max. current carrying capacity: 24 A

---

## RB ST (2,5/4)-1,5/S - Reducing bridge

3214356

<https://www.phoenixcontact.com/ca/products/3214356>



Reducing bridge, pitch: 6.7 mm, number of positions: 2, length: 23 mm, color: red

 Max. current carrying capacity: 24 A

# ST 2,5-TWIN YE - Feed-through terminal block



3037313

<https://www.phoenixcontact.com/ca/products/3037313>

## RB ST 6-(2,5/4) - Reducing bridge

3030860

<https://www.phoenixcontact.com/ca/products/3030860>



Reducing bridge, pitch: 9 mm, number of positions: 2, length: 30 mm, color: red

 Max. current carrying capacity: 35 A

---

## RB ST 10-(2,5/4) - Reducing bridge

3030873

<https://www.phoenixcontact.com/ca/products/3030873>



Reducing bridge, pitch: 10 mm, number of positions: 2, length: 36 mm, color: red

 Max. current carrying capacity: 35 A

# ST 2,5-TWIN YE - Feed-through terminal block



3037313

<https://www.phoenixcontact.com/ca/products/3037313>

## RB ST 16-(2,5/4) - Reducing bridge

3030886

<https://www.phoenixcontact.com/ca/products/3030886>



Reducing bridge, pitch: 11 mm, number of positions: 2, length: 37 mm, color: red

 Max. current carrying capacity: 35 A

---

## RB ST 35-(2,5/4) - Reducing bridge

3030899

<https://www.phoenixcontact.com/ca/products/3030899>



Reducing bridge, pitch: 11 mm, number of positions: 2, color: red

 Max. current carrying capacity: 35 A

# ST 2,5-TWIN YE - Feed-through terminal block



3037313

<https://www.phoenixcontact.com/ca/products/3037313>

## RB ST (2,5/4)-1,5 - Reducing bridge

3038943

<https://www.phoenixcontact.com/ca/products/3038943>



Reducing bridge, pitch: 7.1 mm, number of positions: 2, length: 23 mm, color: red

 Max. current carrying capacity: 24 A

---

## RB UT 6-ST(2,5/4) - Reducing bridge

3047264

<https://www.phoenixcontact.com/ca/products/3047264>



Reducing bridge, pitch: 9.5 mm, number of positions: 2, length: 33 mm, color: red

 Max. current carrying capacity: 35 A

# ST 2,5-TWIN YE - Feed-through terminal block



3037313

<https://www.phoenixcontact.com/ca/products/3037313>

## RB UT 35-ST(2,5/4) - Reducing bridge

3047280

<https://www.phoenixcontact.com/ca/products/3047280>



Reducing bridge, pitch: 10.8 mm, number of positions: 2, color: red

 Max. current carrying capacity: 40 A

---

## RB UT 10-ST(2,5/4) - Reducing bridge

3047086

<https://www.phoenixcontact.com/ca/products/3047086>



Reducing bridge, pitch: 10.2 mm, number of positions: 2, length: 33 mm, color: red

 Max. current carrying capacity: 40 A

# ST 2,5-TWIN YE - Feed-through terminal block

3037313

<https://www.phoenixcontact.com/ca/products/3037313>



## RB UT 16-ST(2,5/4) - Reducing bridge

3047099

<https://www.phoenixcontact.com/ca/products/3047099>



Reducing bridge, pitch: 11 mm, number of positions: 2, length: 41 mm, color: red

 Max. current carrying capacity: 40 A

---

## B-STIFT - Marker pen

1051993

<https://www.phoenixcontact.com/ca/products/1051993>



Marker pen, for manual labeling of unprinted Zack strips, smear-proof and waterproof, line thickness 0.5 mm

## ST 2,5-TWIN YE - Feed-through terminal block

3037313

<https://www.phoenixcontact.com/ca/products/3037313>



## X-PEN 0,35 - Marker pen

0811228

<https://www.phoenixcontact.com/ca/products/0811228>



Marker pen without ink cartridge, for manual labeling of markers, labeling extremely wipe-proof, line thickness 0.35 mm

---

## D-ST 2,5-TWIN - End cover

3030488

<https://www.phoenixcontact.com/ca/products/3030488>

End cover, depth: 29 mm, width: 2.2 mm, height: 60.5 mm, color: gray





# ST 2,5-TWIN YE - Feed-through terminal block



3037313

<https://www.phoenixcontact.com/ca/products/3037313>

## RPS - Reducing plug

0201647

<https://www.phoenixcontact.com/ca/products/0201647>

Reducing plug, number of positions: 1, color: gray



---

## ATP-ST-TWIN - Partition plate

3030789

<https://www.phoenixcontact.com/ca/products/3030789>

Partition plate, depth: 39 mm, width: 2 mm, height: 75.2 mm, color: gray



# ST 2,5-TWIN YE - Feed-through terminal block



3037313

<https://www.phoenixcontact.com/ca/products/3037313>

## SZF 1-0,6X3,5 - Screwdriver

1204517

<https://www.phoenixcontact.com/ca/products/1204517>



Actuation tool, for ST terminal blocks, also suitable for use as a bladed screwdriver, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip

---

## DS-ST 2,5 - Cover segment

3036602

<https://www.phoenixcontact.com/ca/products/3036602>



End cover segments, large segment: 32.25 x 13.83 x 0.9, small segment: 22.65 x 11.65 x 0.9, color: gray

# ST 2,5-TWIN YE - Feed-through terminal block



3037313

<https://www.phoenixcontact.com/ca/products/3037313>

## D-ST 2,5-TWIN-0,8 OG - End cover

3030512

<https://www.phoenixcontact.com/ca/products/3030512>

End cover, depth: 29 mm, width: 0.8 mm, height: 60.5 mm, color: orange



---

## ST-IL - Mounting material

3039900

<https://www.phoenixcontact.com/ca/products/3039900>

Operating decal for the ST terminal block



# ST 2,5-TWIN YE - Feed-through terminal block



3037313

<https://www.phoenixcontact.com/ca/products/3037313>

## ST-BW - Actuation tool

1207608

<https://www.phoenixcontact.com/ca/products/1207608>

Actuation tool, for all 2.5 mm<sup>2</sup> - 4.0 mm<sup>2</sup> spring-cages



---

## CEC 2,5 - Filler plug

3062757

<https://www.phoenixcontact.com/ca/products/3062757>

Cover for conductor shaft, 10-pos., for spring cage terminal blocks (ST) and terminal blocks with push-in technology (PT) with a width of 5.2 mm



## ST 2,5-TWIN YE - Feed-through terminal block

3037313

<https://www.phoenixcontact.com/ca/products/3037313>



## P-CO 2-5 R47K - Component connector

3032447

<https://www.phoenixcontact.com/ca/products/3032447>



Component connector, with 47 kOhm resistance for wire-break monitoring, pitch: 5.2 mm, depth: 34.8 mm, width: 4.1 mm, height: 8.9 mm, number of positions: 2, color: black

---

## WST 2,5 - Warning cover

3030941

<https://www.phoenixcontact.com/ca/products/3030941>



Warning cover, 5-pos., for terminal width: 5.2 mm

## ST 2,5-TWIN YE - Feed-through terminal block

3037313

<https://www.phoenixcontact.com/ca/products/3037313>



## BST 2,5 - Group cover marker

3061282

<https://www.phoenixcontact.com/ca/products/3061282>



Cover for actuation shaft, 5-pos., for spring-cage terminal blocks with width of 5.2 mm

---

## NS 35/ 7,5 PERF 2000MM - DIN rail perforated

0801733

<https://www.phoenixcontact.com/ca/products/0801733>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

# ST 2,5-TWIN YE - Feed-through terminal block

3037313

<https://www.phoenixcontact.com/ca/products/3037313>



## NS 35/ 7,5 UNPERF 2000MM - DIN rail, unperforated

0801681

<https://www.phoenixcontact.com/ca/products/0801681>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

---

## NS 35/ 7,5 WH PERF 2000MM - DIN rail perforated

1204119

<https://www.phoenixcontact.com/ca/products/1204119>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

## ST 2,5-TWIN YE - Feed-through terminal block

3037313

<https://www.phoenixcontact.com/ca/products/3037313>



### NS 35/ 7,5 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204122

<https://www.phoenixcontact.com/ca/products/1204122>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

---

### NS 35/ 7,5 AL UNPERF 2000MM - DIN rail, unperforated

0801704

<https://www.phoenixcontact.com/ca/products/0801704>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver



# ST 2,5-TWIN YE - Feed-through terminal block

3037313

<https://www.phoenixcontact.com/ca/products/3037313>



## NS 35/ 7,5 ZN PERF 2000MM - DIN rail perforated

1206421

<https://www.phoenixcontact.com/ca/products/1206421>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

---

## NS 35/ 7,5 ZN UNPERF 2000MM - DIN rail, unperforated

1206434

<https://www.phoenixcontact.com/ca/products/1206434>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

# ST 2,5-TWIN YE - Feed-through terminal block

3037313

<https://www.phoenixcontact.com/ca/products/3037313>



## NS 35/ 7,5 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

0801762

<https://www.phoenixcontact.com/ca/products/0801762>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

---

## NS 35/ 7,5 CAP - End cap

1206560

<https://www.phoenixcontact.com/ca/products/1206560>

DIN rail end piece, for DIN rail NS 35/7.5



# ST 2,5-TWIN YE - Feed-through terminal block

3037313

<https://www.phoenixcontact.com/ca/products/3037313>



## NS 35/15 PERF 2000MM - DIN rail perforated

1201730

<https://www.phoenixcontact.com/ca/products/1201730>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

---

## NS 35/15 UNPERF 2000MM - DIN rail, unperforated

1201714

<https://www.phoenixcontact.com/ca/products/1201714>



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

# ST 2,5-TWIN YE - Feed-through terminal block

3037313

<https://www.phoenixcontact.com/ca/products/3037313>



## NS 35/15 WH PERF 2000MM - DIN rail perforated

0806602

<https://www.phoenixcontact.com/ca/products/0806602>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: white

---

## NS 35/15 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204135

<https://www.phoenixcontact.com/ca/products/1204135>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

# ST 2,5-TWIN YE - Feed-through terminal block

3037313

<https://www.phoenixcontact.com/ca/products/3037313>



## NS 35/15 AL UNPERF 2000MM - DIN rail, unperforated

1201756

<https://www.phoenixcontact.com/ca/products/1201756>



DIN rail, unperforated, similar to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

---

## NS 35/15 ZN PERF 2000MM - DIN rail perforated

1206599

<https://www.phoenixcontact.com/ca/products/1206599>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver

# ST 2,5-TWIN YE - Feed-through terminal block

3037313

<https://www.phoenixcontact.com/ca/products/3037313>



## NS 35/15 ZN UNPERF 2000MM - DIN rail, unperforated

1206586

<https://www.phoenixcontact.com/ca/products/1206586>



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver

---

## NS 35/15 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201895

<https://www.phoenixcontact.com/ca/products/1201895>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

# ST 2,5-TWIN YE - Feed-through terminal block

3037313

<https://www.phoenixcontact.com/ca/products/3037313>



## NS 35/15 CAP - End cap

1206573

<https://www.phoenixcontact.com/ca/products/1206573>

DIN rail end piece, for DIN rail NS 35/15



---

## NS 35/15-2,3 UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201798

<https://www.phoenixcontact.com/ca/products/1201798>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile 2.3 mm, color: silver

# ST 2,5-TWIN YE - Feed-through terminal block



3037313

<https://www.phoenixcontact.com/ca/products/3037313>

## ZB 5 :UNBEDRUCKT - Zack marker strip

1050004

<https://www.phoenixcontact.com/ca/products/1050004>



Zack marker strip, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 5.2 mm, lettering field size: 5.1 x 10.5 mm, Number of individual labels: 10

---

## ZB 5,LGS:FORTL.ZAHLEN - Zack marker strip

1050017

<https://www.phoenixcontact.com/ca/products/1050017>



Zack marker strip, Strip, white, labeled, printed horizontally: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 491 ... 500, mounting type: snapped, for terminal block width: 5.2 mm, lettering field size: 5.15 x 10.5 mm, Number of individual labels: 10



# ST 2,5-TWIN YE - Feed-through terminal block



3037313

<https://www.phoenixcontact.com/ca/products/3037313>

## ZB 5,QR:FORTL.ZAHLEN - Zack marker strip

1050020

<https://www.phoenixcontact.com/ca/products/1050020>



Zack marker strip, white, Printed vertically: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 491 ... 500, mounting type: snapped, for terminal block width: 5.2 mm, lettering field size: 5.15 x 10.5 mm

---

## ZB 5,LGS:GLEICHE ZAHLEN - Zack marker strip

1050033

<https://www.phoenixcontact.com/ca/products/1050033>



Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, printed horizontally: Identical numbers 1 or 2, etc. up to 100, mounting type: snapped, for terminal block width: 5.2 mm, lettering field size: 5.15 x 10.5 mm, Number of individual labels: 10

# ST 2,5-TWIN YE - Feed-through terminal block



3037313

<https://www.phoenixcontact.com/ca/products/3037313>

## ZB 5,LGS:L1-N,PE - Zack marker strip

1050415

<https://www.phoenixcontact.com/ca/products/1050415>



Zack marker strip, Strip, white, labeled, horizontal: L1, L2, L3, N, PE, L1, L2, L3, N, PE, mounting type: snapped, for terminal block width: 5.2 mm, lettering field size: 5.15 x 10.5 mm, Number of individual labels: 10

---

## UC-TM 5 - Marker for terminal blocks

0818108

<https://www.phoenixcontact.com/ca/products/0818108>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 5.2 mm, lettering field size: 4.6 x 10.5 mm, Number of individual labels: 96

## ST 2,5-TWIN YE - Feed-through terminal block

3037313

<https://www.phoenixcontact.com/ca/products/3037313>



## UCT-TM 5 - Marker for terminal blocks

0828734

<https://www.phoenixcontact.com/ca/products/0828734>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, for terminal block width: 5.2 mm, lettering field size: 4.6 x 10.5 mm, Number of individual labels: 72

---

## GBS 5-25X12 - Group marker label for terminal marking

0810588

<https://www.phoenixcontact.com/ca/products/0810588>



Group marker label, snaps onto terminal center for screw, spring-cage and quick connection terminal blocks, labeled with a 25 x 12 mm label or manually with the B-STIFT, in the foot part with ZB 5

# ST 2,5-TWIN YE - Feed-through terminal block



3037313

<https://www.phoenixcontact.com/ca/products/3037313>

## GBS 5-25X5 - Group marker label for terminal marking

0829126

<https://www.phoenixcontact.com/ca/products/0829126>



Group marking label, can be snapped into terminal center for screw, spring-cage, push-in, and fast connection terminal blocks, can be labeled with a 24 x 4 mm label or manually using B-STIFT, in the foot part with ZB 5

---

## STP 5-2-ZB - Marker carriers

3037643

<https://www.phoenixcontact.com/ca/products/3037643>



Marker carriers, snaps into ST 2,5 spring-cage terminal blocks, can be marked with UC-TM 5, UC-TMF 5, UCT-TM 5, UCT-TMF 5, ZB 5, or ZBF 5, gray, unlabeled, mounting type: snapped

# ST 2,5-TWIN YE - Feed-through terminal block



3037313

<https://www.phoenixcontact.com/ca/products/3037313>

## ZBF 5:UNBEDRUCKT - Zack Marker strip, flat

0808642

<https://www.phoenixcontact.com/ca/products/0808642>



Zack Marker strip, flat, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 5 mm, lettering field size: 5.1 x 5.2 mm, Number of individual labels: 10

---

## ZBF 5,LGS:FORTL.ZAHLEN - Zack Marker strip, flat

0808671

<https://www.phoenixcontact.com/ca/products/0808671>



Zack Marker strip, flat, Strip, white, labeled, printed horizontally: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 491 ... 500, mounting type: snapped, for terminal block width: 5 mm, lettering field size: 5.15 x 5.15 mm, Number of individual labels: 10

# ST 2,5-TWIN YE - Feed-through terminal block



3037313

<https://www.phoenixcontact.com/ca/products/3037313>

## ZBF 5,QR:FORTL.ZAHLEN - Zack Marker strip, flat

0808697

<https://www.phoenixcontact.com/ca/products/0808697>



Zack Marker strip, flat, Strip, white, labeled, Printed vertically: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 91 ... 100, mounting type: snapped, for terminal block width: 5 mm, lettering field size: 5.15 x 5.15 mm, Number of individual labels: 10

---

## ZBF 5,LGS:GERADE ZAHLEN - Zack Marker strip, flat

0810821

<https://www.phoenixcontact.com/ca/products/0810821>



Zack Marker strip, flat, Strip, white, labeled, printed horizontally: consecutive even numbers 2 ... 20, 22 ... 40, etc. up to 82 ... 100, mounting type: snapped, for terminal block width: 5 mm, lettering field size: 5.15 x 5.15 mm, Number of individual labels: 10

# ST 2,5-TWIN YE - Feed-through terminal block



3037313

<https://www.phoenixcontact.com/ca/products/3037313>

## ZBF 5,LGS:UNGERADE ZAHLEN - Zack Marker strip, flat

0810863

<https://www.phoenixcontact.com/ca/products/0810863>




Zack Marker strip, flat, Strip, white, labeled, printed horizontally: Odd numbers 1 - 19, 21 - 39, etc. up to 81 - 99, mounting type: snapped, for terminal block width: 5 mm, lettering field size: 5.15 x 5.15 mm, Number of individual labels: 10

---

## UC-TMF 5 - Marker for terminal blocks

0818153

<https://www.phoenixcontact.com/ca/products/0818153>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 5.2 mm, lettering field size: 4.6 x 5.1 mm, Number of individual labels: 96

## ST 2,5-TWIN YE - Feed-through terminal block

3037313

<https://www.phoenixcontact.com/ca/products/3037313>



## UCT-TMF 5 - Marker for terminal blocks

0828744

<https://www.phoenixcontact.com/ca/products/0828744>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, for terminal block width: 5.2 mm, lettering field size: 4.4 x 4.7 mm, Number of individual labels: 72

---

## MPS-MT - Test plug

0201744

<https://www.phoenixcontact.com/ca/products/0201744>



Test plug, with solder connection up to 1 mm<sup>2</sup> conductor cross section, number of positions: 1, color: gray



# ST 2,5-TWIN YE - Feed-through terminal block



3037313

<https://www.phoenixcontact.com/ca/products/3037313>

## MPS-IH WH - Insulating sleeve

0201663

<https://www.phoenixcontact.com/ca/products/0201663>

Insulating sleeve, color: white



---

## MPS-IH RD - Insulating sleeve

0201676

<https://www.phoenixcontact.com/ca/products/0201676>

Insulating sleeve, color: red



# ST 2,5-TWIN YE - Feed-through terminal block



3037313


<https://www.phoenixcontact.com/ca/products/3037313>

## MPS-IH BU - Insulating sleeve

0201689

<https://www.phoenixcontact.com/ca/products/0201689>

Insulating sleeve, color: blue



---

## MPS-IH YE - Insulating sleeve

0201692

<https://www.phoenixcontact.com/ca/products/0201692>

Insulating sleeve, color: yellow



# ST 2,5-TWIN YE - Feed-through terminal block

3037313

<https://www.phoenixcontact.com/ca/products/3037313>



## MPS-IH GN - Insulating sleeve

0201702

<https://www.phoenixcontact.com/ca/products/0201702>

Insulating sleeve, color: green



---

## MPS-IH GY - Insulating sleeve

0201728

<https://www.phoenixcontact.com/ca/products/0201728>

Insulating sleeve, color: gray



# ST 2,5-TWIN YE - Feed-through terminal block

3037313

<https://www.phoenixcontact.com/ca/products/3037313>



## MPS-IH BK - Insulating sleeve

0201731

<https://www.phoenixcontact.com/ca/products/0201731>

Insulating sleeve, color: black



---

## ISH 2,5/0,2 - Insulating sleeve

3002843

<https://www.phoenixcontact.com/ca/products/3002843>

Insulating sleeve, color: white



# ST 2,5-TWIN YE - Feed-through terminal block



3037313

<https://www.phoenixcontact.com/ca/products/3037313>

## ISH 2,5/0,5 - Insulating sleeve

3002856

<https://www.phoenixcontact.com/ca/products/3002856>



Insulating sleeve, color: gray

---

## ISH 2,5/1,0 - Insulating sleeve

3002869

<https://www.phoenixcontact.com/ca/products/3002869>



Insulating sleeve, color: black

# ST 2,5-TWIN YE - Feed-through terminal block



3037313

<https://www.phoenixcontact.com/ca/products/3037313>

## PAI-4-FIX-5/6 BU - Test adapter

3035975

<https://www.phoenixcontact.com/ca/products/3035975>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

---

## PAI-4-FIX-5/6 OG - Test adapter

3035974

<https://www.phoenixcontact.com/ca/products/3035974>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

## ST 2,5-TWIN YE - Feed-through terminal block

3037313

<https://www.phoenixcontact.com/ca/products/3037313>



### PAI-4-FIX-5/6 YE - Test adapter

3035977

<https://www.phoenixcontact.com/ca/products/3035977>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

---

### PAI-4-FIX-5/6 RD - Test adapter

3035976

<https://www.phoenixcontact.com/ca/products/3035976>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

# ST 2,5-TWIN YE - Feed-through terminal block



3037313

<https://www.phoenixcontact.com/ca/products/3037313>

## PAI-4-FIX-5/6 GN - Test adapter

3035978

<https://www.phoenixcontact.com/ca/products/3035978>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

---

## PAI-4-FIX-5/6 BK - Test adapter

3035980

<https://www.phoenixcontact.com/ca/products/3035980>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch



# ST 2,5-TWIN YE - Feed-through terminal block



3037313

<https://www.phoenixcontact.com/ca/products/3037313>

## PAI-4-FIX-5/6 GY - Test adapter

3035982

<https://www.phoenixcontact.com/ca/products/3035982>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

---

## PAI-4-FIX-5/6 VT - Test adapter

3035979

<https://www.phoenixcontact.com/ca/products/3035979>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

# ST 2,5-TWIN YE - Feed-through terminal block



3037313

<https://www.phoenixcontact.com/ca/products/3037313>

## PAI-4-FIX-5/6 BN - Test adapter

3035981

<https://www.phoenixcontact.com/ca/products/3035981>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

---

## PAI-4-FIX-5/6 WH - Test adapter

3035983

<https://www.phoenixcontact.com/ca/products/3035983>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

# ST 2,5-TWIN YE - Feed-through terminal block

3037313

<https://www.phoenixcontact.com/ca/products/3037313>



## PS-5 - Test plug

3030983

<https://www.phoenixcontact.com/ca/products/3030983>



Test plug, Modular test plug, number of positions: 1, color: red

---

## DP PS-5 - Spacer plate

3036725

<https://www.phoenixcontact.com/ca/products/3036725>



Spacer plate, depth: 29 mm, width: 5.2 mm, height: 22.4 mm, number of positions: 1, color: red

## ST 2,5-TWIN YE - Feed-through terminal block

3037313

<https://www.phoenixcontact.com/ca/products/3037313>



## PS-5/2,3MM RD - Test plug

3038723

<https://www.phoenixcontact.com/ca/products/3038723>



Test plug, number of positions: 1, color: red

---

## CLIPFIX 35 - End bracket

3022218

<https://www.phoenixcontact.com/ca/products/3022218>



Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, width: 9.5 mm, color: gray

# ST 2,5-TWIN YE - Feed-through terminal block



3037313

<https://www.phoenixcontact.com/ca/products/3037313>

## CLIPFIX 35-5 - End bracket

3022276

<https://www.phoenixcontact.com/ca/products/3022276>




Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, with parking option for FBS...5, FBS...6, KSS 5, KSS 6, width: 5.15 mm, color: gray

---

## E/NS 35 N - End bracket

0800886

<https://www.phoenixcontact.com/ca/products/0800886>



End clamp, width: 9.5 mm, color: gray

# ST 2,5-TWIN YE - Feed-through terminal block



3037313

<https://www.phoenixcontact.com/ca/products/3037313>

## E/UK - End bracket

1201442

<https://www.phoenixcontact.com/ca/products/1201442>

End bracket, Mounting on a DIN rail NS 32 or NS 35, material: PA, color: gray



---

## E/UK 1 - End bracket

1201413

<https://www.phoenixcontact.com/ca/products/1201413>

End clamps, for supporting the ends of double-level and three-level terminal blocks, width: 10 mm, color: gray



---

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd  
8240 Parkhill Drive  
Milton, Ontario L9T 5V7  
1-800-890-2820  
[cdinfo@phoenixcontact.ca](mailto:cdinfo@phoenixcontact.ca)