

STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Protective conductor double-level terminal block, number of connections: 4, connection method: Spring-cage connection, 1st and 2nd level, cross section: 0.08 mm² - 4 mm², mounting type: NS 35/7,5, NS 35/15, color: green-yellow

Your advantages

- Two large-surface labeling options

Commercial data

Item number	3038480
Packing unit	50 pc
Minimum order quantity	50 pc
Sales key	0163*
Product key	BE2124
Catalog page	Page 221 (C-1-2019)
GTIN	4017918906900
Weight per piece (including packing)	17.62 g
Weight per piece (excluding packing)	16.824 g
Customs tariff number	85369010
Country of origin	DE

STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

Technical data

Product properties

Product type	Ground terminal block
Number of connections	4
Number of rows	2

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Electrical properties

Rated surge voltage	6 kV
Maximum power dissipation for nominal condition	0.77 W

Connection data

Grounding foot	Yes
Number of connections per level	2
Nominal cross section	2.5 mm ²

1st and 2nd level

Note	Please observe the current carrying capacity of the DIN rails.
Stripping length	8 mm ... 10 mm
Internal cylindrical gage	A3
Connection in acc. with standard	IEC 60947-7-2
Conductor cross section rigid	0.08 mm ² ... 4 mm ²
Cross section AWG	28 ... 12 (converted acc. to IEC)
Conductor cross section flexible	0.08 mm ² ... 2.5 mm ²
Conductor cross section, flexible [AWG]	28 ... 14 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve)	0.14 mm ² ... 2.5 mm ²
Flexible conductor cross section (ferrule with plastic sleeve)	0.14 mm ² ... 2.5 mm ²

Ex data

Rated data (ATEX/IECEx)

Identification	Ex II 2 G Ex eb IIC Gb
Operating temperature range	-60 °C ... 110 °C
Ex-certified accessories	3038503 D-STTBS 2,5
	1204517 SZF 1-0,6X3,5
	3022276 CLIPFIX 35-5
	3022218 CLIPFIX 35
output	(Permanent)

Ex connection data General

STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

Nominal cross section	2.5 mm²
Rated cross section AWG	14
Connection capacity rigid	0.08 mm² ... 4 mm²
Connection capacity AWG	28 ... 12
Connection capacity flexible	0.08 mm² ... 2.5 mm²
Connection capacity AWG	28 ... 14

Dimensions

Width	5.2 mm
End cover width	2.2 mm
Height	78 mm
Depth on NS 35/7,5	55 mm
Depth on NS 35/15	62.5 mm

Material specifications

Color	green-yellow
Flammability rating according to UL 94	V0
Insulating material group	I
Insulating material	PA
Static insulating material application in cold	-60 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	125 °C
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3
Calorimetric heat release NFPA 130 (ASTM E 1354)	27,5 MJ/kg
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed

Mechanical properties

Mechanical data

Open side panel	Yes
-----------------	-----

Environmental and real-life conditions

Oscillation/broadband noise

Specification	DIN EN 50155 (VDE 0115-200):2008-03
Spectrum	Service life test category 2, bogie-mounted
Frequency	f ₁ = 5 Hz to f ₂ = 250 Hz
ASD level	6.12 (m/s²)²/Hz

STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

Acceleration	3.12g
Test duration per axis	5 h
Test directions	X-, Y- and Z-axis
Result	Test passed

Shocks

Specification	DIN EN 50155 (VDE 0115-200):2008-03
Pulse shape	Half-sine
Acceleration	30g
Shock duration	18 ms
Number of shocks per direction	3
Test directions	X-, Y- and Z-axis (pos. and neg.)
Result	Test passed

Ambient conditions

Ambient temperature (operation)	-60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (operation)	20 % ... 90 %
Permissible humidity (storage/transport)	30 % ... 70 %

Standards and regulations

Connection in acc. with standard	IEC 60947-7-2
----------------------------------	---------------

Mounting

Mounting type	NS 35/7,5
	NS 35/15


STTBS 2,5-PE - Protective conductor double-level terminal block

3038480

<https://www.phoenixcontact.com/sg/products/3038480>

Drawings

Circuit diagram



STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/sg/products/3038480>

 CSA Approval ID: 13631				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
Use group B	-	-	28 - 12	-
Use group C	-	-	28 - 12	-
Use group D	-	-	28 - 12	-

 IECEE CB Scheme Approval ID: DE1-62971_M1				
---	--	--	--	--

 LR Approval ID: LR21234196TA				
--	--	--	--	--

 NK Approval ID: 06ME279				
---	--	--	--	--

ABS Approval ID: 21-2158220-PDA				
---	--	--	--	--

 VDE Zeichengenehmigung Approval ID: 40010331				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	-	-	-	0.2 - 2.5

 cULus Recognized Approval ID: E60425				
--	--	--	--	--

 cULus Recognized Approval ID: E60425				
--	--	--	--	--

STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

DNV

Approval ID: TAE00001CS



EAC Ex

Approval ID: RU C-DE.HA91.B.00066



IEC Ex

Approval ID: IECExPTB07.0024U



ATEX

Approval ID: PTB07ATEX1027U



CCC

Approval ID: 2020322313000621



UKCA-EX

Approval ID: CSAE 22UKEX1141U

STTBS 2,5-PE - Protective conductor double-level terminal block



3038480
<https://www.phoenixcontact.com/sg/products/3038480>

Classifications

ECLASS

ECLASS-11.0	27141141
ECLASS-13.0	27250104

ETIM

ETIM 9.0	EC000901
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

STTBS 2,5-PE - Protective conductor double-level terminal block



3038480
<https://www.phoenixcontact.com/sg/products/3038480>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%
EF3.0 Climate Change	
CO2e kg	0.114 kg CO2e

STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

Accessories

FBS 20-5 - Plug-in bridge

3030226

<https://www.phoenixcontact.com/sg/products/3030226>



Plug-in bridge, pitch: 5.2 mm, number of positions: 20, color: red

FBS 10-5 - Plug-in bridge

3030213

<https://www.phoenixcontact.com/sg/products/3030213>



Plug-in bridge, pitch: 5.2 mm, number of positions: 10, length: 23 mm, color: red

STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

FBS 5-5 - Plug-in bridge

3030190

<https://www.phoenixcontact.com/sg/products/3030190>



Plug-in bridge, pitch: 5.2 mm, number of positions: 5, length: 23 mm, color: red

FBS 4-5 - Plug-in bridge

3030187

<https://www.phoenixcontact.com/sg/products/3030187>



Plug-in bridge, pitch: 5.2 mm, number of positions: 4, length: 23 mm, color: red

STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

FBS 3-5 - Plug-in bridge

3030174

<https://www.phoenixcontact.com/sg/products/3030174>



Plug-in bridge, pitch: 5.2 mm, number of positions: 3, length: 23 mm, color: red

FBS 2-5 - Plug-in bridge

3030161

<https://www.phoenixcontact.com/sg/products/3030161>



Plug-in bridge, pitch: 5.2 mm, number of positions: 2, length: 23 mm, color: red

STTBS 2,5-PE - Protective conductor double-level terminal block

3038480

<https://www.phoenixcontact.com/sg/products/3038480>

FBSR 2-5 - Plug-in bridge

3033702

<https://www.phoenixcontact.com/sg/products/3033702>



Plug-in bridge, pitch: 5.2 mm, number of positions: 2, color: red

FBSR 3-5 - Plug-in bridge

3001591

<https://www.phoenixcontact.com/sg/products/3001591>



Plug-in bridge, pitch: 5.2 mm, number of positions: 3, color: red

STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

FBSR 4-5 - Plug-in bridge

3001592

<https://www.phoenixcontact.com/sg/products/3001592>

Plug-in bridge, pitch: 5.2 mm, number of positions: 4, color: red



FBSR 5-5 - Plug-in bridge

3001593

<https://www.phoenixcontact.com/sg/products/3001593>

Plug-in bridge, pitch: 5.2 mm, number of positions: 5, color: red



STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

FBSR 10-5 - Plug-in bridge

3033710

<https://www.phoenixcontact.com/sg/products/3033710>

Plug-in bridge, pitch: 5.2 mm, number of positions: 10, color: red



FBS 2-5 BU - Plug-in bridge

3036877

<https://www.phoenixcontact.com/sg/products/3036877>

Plug-in bridge, pitch: 5.2 mm, number of positions: 2, color: blue



STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

FBS 3-5 BU - Plug-in bridge

3036880

<https://www.phoenixcontact.com/sg/products/3036880>

Plug-in bridge, pitch: 5.2 mm, number of positions: 3, color: blue



FBS 4-5 BU - Plug-in bridge

3036893

<https://www.phoenixcontact.com/sg/products/3036893>

Plug-in bridge, pitch: 5.2 mm, number of positions: 4, color: blue



STTBS 2,5-PE - Protective conductor double-level terminal block

3038480

<https://www.phoenixcontact.com/sg/products/3038480>

FBS 5-5 BU - Plug-in bridge

3036903

<https://www.phoenixcontact.com/sg/products/3036903>

Plug-in bridge, pitch: 5.2 mm, number of positions: 5, color: blue



FBS 10-5 BU - Plug-in bridge

3036916

<https://www.phoenixcontact.com/sg/products/3036916>

Plug-in bridge, pitch: 5.2 mm, number of positions: 10, color: blue



STTBS 2,5-PE - Protective conductor double-level terminal block

3038480

<https://www.phoenixcontact.com/sg/products/3038480>

FBS 20-5 BU - Plug-in bridge

3036929

<https://www.phoenixcontact.com/sg/products/3036929>

Plug-in bridge, pitch: 5.2 mm, number of positions: 20, color: blue



FBS 50-5 BU - Plug-in bridge

3032114

<https://www.phoenixcontact.com/sg/products/3032114>

Plug-in bridge, pitch: 5.2 mm, number of positions: 50, color: blue



STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

D-STTBS 2,5 - End cover

3038503

<https://www.phoenixcontact.com/sg/products/3038503>

End cover, depth: 54.5 mm, width: 2.2 mm, height: 78 mm, color: gray



WST 2,5 - Warning cover

3030941

<https://www.phoenixcontact.com/sg/products/3030941>

Warning cover, 5-pos., for terminal width: 5.2 mm



STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

CEC 2,5 - Filler plug

3062757

<https://www.phoenixcontact.com/sg/products/3062757>



Cover for conductor shaft, 10-pos., for spring cage terminal blocks (ST) and terminal blocks with push-in technology (PT) with a width of 5.2 mm

LPO 2,5/E - Pick-off plug

3270516

<https://www.phoenixcontact.com/sg/products/3270516>



Pick-off plug, nom. voltage: 800 V, nominal current: 24 A, number of positions: 1, connection method: Push-in connection, Rated cross section: 2.5 mm², cross section: 0.14 mm²- 4 mm², color: gray

STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

LPO 2,5 - Pick-off plug

3270517

<https://www.phoenixcontact.com/sg/products/3270517>



Pick-off plug, nom. voltage: 800 V, nominal current: 24 A, number of positions: 1, connection method: Push-in connection, Rated cross section: 2.5 mm², cross section: 0.14 mm²- 4 mm², color: gray

LPS-5/E - Service connector

3270520

<https://www.phoenixcontact.com/sg/products/3270520>



Service connector, nom. voltage: 800 V, nominal current: 24 A, number of positions: 1, connection method: Push-in connection, Rated cross section: 2.5 mm², cross section: 0.14 mm²- 4 mm², color: red

STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

LPS-5 - Service connector

3270521

<https://www.phoenixcontact.com/sg/products/3270521>



Service connector, nom. voltage: 800 V, nominal current: 24 A, number of positions: 1, connection method: Push-in connection, Rated cross section: 2.5 mm², cross section: 0.14 mm²- 4 mm², color: red

NS 35/ 7,5 PERF 2000MM - DIN rail perforated

0801733

<https://www.phoenixcontact.com/sg/products/0801733>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

NS 35/ 7,5 UNPERF 2000MM - DIN rail, unperforated

0801681

<https://www.phoenixcontact.com/sg/products/0801681>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

NS 35/ 7,5 WH PERF 2000MM - DIN rail perforated

1204119

<https://www.phoenixcontact.com/sg/products/1204119>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

NS 35/ 7,5 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204122

<https://www.phoenixcontact.com/sg/products/1204122>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

NS 35/ 7,5 AL UNPERF 2000MM - DIN rail, unperforated

0801704

<https://www.phoenixcontact.com/sg/products/0801704>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

NS 35/ 7,5 ZN PERF 2000MM - DIN rail perforated

1206421

<https://www.phoenixcontact.com/sg/products/1206421>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

NS 35/ 7,5 ZN UNPERF 2000MM - DIN rail, unperforated

1206434

<https://www.phoenixcontact.com/sg/products/1206434>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

NS 35/ 7,5 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

0801762

<https://www.phoenixcontact.com/sg/products/0801762>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

NS 35/ 7,5 CAP - End cap

1206560

<https://www.phoenixcontact.com/sg/products/1206560>

DIN rail end piece, for DIN rail NS 35/7.5



STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

NS 35/15 PERF 2000MM - DIN rail perforated

1201730

<https://www.phoenixcontact.com/sg/products/1201730>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

NS 35/15 UNPERF 2000MM - DIN rail, unperforated

1201714

<https://www.phoenixcontact.com/sg/products/1201714>



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

NS 35/15 WH PERF 2000MM - DIN rail perforated

0806602

<https://www.phoenixcontact.com/sg/products/0806602>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: white

NS 35/15 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204135

<https://www.phoenixcontact.com/sg/products/1204135>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

NS 35/15 AL UNPERF 2000MM - DIN rail, unperforated

1201756

<https://www.phoenixcontact.com/sg/products/1201756>



DIN rail, unperforated, similar to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

NS 35/15 ZN PERF 2000MM - DIN rail perforated

1206599

<https://www.phoenixcontact.com/sg/products/1206599>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver

STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

NS 35/15 ZN UNPERF 2000MM - DIN rail, unperforated

1206586

<https://www.phoenixcontact.com/sg/products/1206586>



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver

NS 35/15 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201895

<https://www.phoenixcontact.com/sg/products/1201895>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

NS 35/15 CAP - End cap

1206573

<https://www.phoenixcontact.com/sg/products/1206573>

DIN rail end piece, for DIN rail NS 35/15



NS 35/15-2,3 UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201798

<https://www.phoenixcontact.com/sg/products/1201798>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile 2.3 mm, color: silver

STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

ZB 5 :UNBEDRUCKT - Zack marker strip

1050004

<https://www.phoenixcontact.com/sg/products/1050004>



Zack marker strip, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 5.2 mm, lettering field size: 5.1 x 10.5 mm, Number of individual labels: 10

ZB 5 CUS - Zack marker strip

0824962

<https://www.phoenixcontact.com/sg/products/0824962>



Zack marker strip, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 5.2 mm, lettering field size: 5.15 x 10.5 mm, Number of individual labels: 10

STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

ZB 5,LGS:FORTL.ZAHLEN - Zack marker strip

1050017

<https://www.phoenixcontact.com/sg/products/1050017>



Zack marker strip, Strip, white, labeled, printed horizontally: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 491 ... 500, mounting type: snapped, for terminal block width: 5.2 mm, lettering field size: 5.15 x 10.5 mm, Number of individual labels: 10

ZB 5,QR:FORTL.ZAHLEN - Zack marker strip

1050020

<https://www.phoenixcontact.com/sg/products/1050020>



Zack marker strip, white, Printed vertically: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 491 ... 500, mounting type: snapped, for terminal block width: 5.2 mm, lettering field size: 5.15 x 10.5 mm

STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

ZB 5,LGS:GLEICHE ZAHLEN - Zack marker strip

1050033

<https://www.phoenixcontact.com/sg/products/1050033>




Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, printed horizontally: Identical numbers 1 or 2, etc. up to 100, mounting type: snapped, for terminal block width: 5.2 mm, lettering field size: 5.15 x 10.5 mm, Number of individual labels: 10

ZB 5,LGS:L1-N,PE - Zack marker strip

1050415

<https://www.phoenixcontact.com/sg/products/1050415>



Zack marker strip, Strip, white, labeled, horizontal: L1, L2, L3, N, PE, L1, L2, L3, N, PE, mounting type: snapped, for terminal block width: 5.2 mm, lettering field size: 5.15 x 10.5 mm, Number of individual labels: 10

STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

UC-TM 5 - Marker for terminal blocks

0818108

<https://www.phoenixcontact.com/sg/products/0818108>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 5.2 mm, lettering field size: 4.6 x 10.5 mm, Number of individual labels: 96

UC-TM 5 CUS - Marker for terminal blocks

0824581

<https://www.phoenixcontact.com/sg/products/0824581>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 5.2 mm, lettering field size: 10.5 x 4.6 mm, Number of individual labels: 96

STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

UCT-TM 5 - Marker for terminal blocks

0828734

<https://www.phoenixcontact.com/sg/products/0828734>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, for terminal block width: 5.2 mm, lettering field size: 4.6 x 10.5 mm, Number of individual labels: 72

UCT-TM 5 CUS - Marker for terminal blocks

0829595

<https://www.phoenixcontact.com/sg/products/0829595>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 5.2 mm, lettering field size: 4.6 x 10.5 mm, Number of individual labels: 72

STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

GBS 5-25X12 - Group marker label for terminal marking

0810588

<https://www.phoenixcontact.com/sg/products/0810588>



Group marker label, snaps onto terminal center for screw, spring-cage and quick connection terminal blocks, labeled with a 25 x 12 mm label or manually with the B-STIFT, in the foot part with ZB 5

GBS 5-25X5 - Group marker label for terminal marking

0829126

<https://www.phoenixcontact.com/sg/products/0829126>



Group marking label, can be snapped into terminal center for screw, spring-cage, push-in, and fast connection terminal blocks, can be labeled with a 24 x 4 mm label or manually using B-STIFT, in the foot part with ZB 5

STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

STP 5-2-ZB - Marker carriers

3037643

<https://www.phoenixcontact.com/sg/products/3037643>



Marker carriers, snaps into ST 2,5 spring-cage terminal blocks, can be marked with UC-TM 5, UC-TMF 5, UCT-TM 5, UCT-TMF 5, ZB 5, or ZBF 5, gray, unlabeled, mounting type: snapped

ZBF 5:UNBEDRUCKT - Zack Marker strip, flat

0808642

<https://www.phoenixcontact.com/sg/products/0808642>



Zack Marker strip, flat, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 5 mm, lettering field size: 5.1 x 5.2 mm, Number of individual labels: 10

STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

ZBF 5 CUS - Zack Marker strip, flat

0825025

<https://www.phoenixcontact.com/sg/products/0825025>



Zack Marker strip, flat, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 5 mm, lettering field size: 5.15 x 5.15 mm, Number of individual labels: 10

ZBF 5,LGS:FORTL.ZAHLEN - Zack Marker strip, flat

0808671

<https://www.phoenixcontact.com/sg/products/0808671>



Zack Marker strip, flat, Strip, white, labeled, printed horizontally: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 491 ... 500, mounting type: snapped, for terminal block width: 5 mm, lettering field size: 5.15 x 5.15 mm, Number of individual labels: 10

STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

ZBF 5,QR:FORTL.ZAHLEN - Zack Marker strip, flat

0808697

<https://www.phoenixcontact.com/sg/products/0808697>



Zack Marker strip, flat, Strip, white, labeled, Printed vertically: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 91 ... 100, mounting type: snapped, for terminal block width: 5 mm, lettering field size: 5.15 x 5.15 mm, Number of individual labels: 10

ZBF 5,LGS:GERADE ZAHLEN - Zack Marker strip, flat

0810821

<https://www.phoenixcontact.com/sg/products/0810821>



Zack Marker strip, flat, Strip, white, labeled, printed horizontally: consecutive even numbers 2 ... 20, 22 ... 40, etc. up to 82 ... 100, mounting type: snapped, for terminal block width: 5 mm, lettering field size: 5.15 x 5.15 mm, Number of individual labels: 10

STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

ZBF 5,LGS:UNGERADE ZAHLEN - Zack Marker strip, flat

0810863

<https://www.phoenixcontact.com/sg/products/0810863>




Zack Marker strip, flat, Strip, white, labeled, printed horizontally: Odd numbers 1 - 19, 21 - 39, etc. up to 81 - 99, mounting type: snapped, for terminal block width: 5 mm, lettering field size: 5.15 x 5.15 mm, Number of individual labels: 10

UC-TMF 5 - Marker for terminal blocks

0818153

<https://www.phoenixcontact.com/sg/products/0818153>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 5.2 mm, lettering field size: 4.6 x 5.1 mm, Number of individual labels: 96

STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

UC-TMF 5 CUS - Marker for terminal blocks

0824638

<https://www.phoenixcontact.com/sg/products/0824638>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 5.2 mm, lettering field size: 4.6 x 5.1 mm, Number of individual labels: 96

UCT-TMF 5 - Marker for terminal blocks

0828744

<https://www.phoenixcontact.com/sg/products/0828744>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, for terminal block width: 5.2 mm, lettering field size: 4.4 x 4.7 mm, Number of individual labels: 72

STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

UCT-TMF 5 CUS - Marker for terminal blocks

0829658

<https://www.phoenixcontact.com/sg/products/0829658>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 5.2 mm, lettering field size: 4.4 x 4.7 mm, Number of individual labels: 72

ISH 2,5/0,2 - Insulating sleeve

3002843

<https://www.phoenixcontact.com/sg/products/3002843>



Insulating sleeve, color: white

STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

ISH 2,5/0,5 - Insulating sleeve

3002856

<https://www.phoenixcontact.com/sg/products/3002856>

Insulating sleeve, color: gray



ISH 2,5/1,0 - Insulating sleeve

3002869

<https://www.phoenixcontact.com/sg/products/3002869>

Insulating sleeve, color: black



STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

PAI-4-FIX-5/6 BU - Test adapter

3035975

<https://www.phoenixcontact.com/sg/products/3035975>

4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch



PAI-4-FIX-5/6 OG - Test adapter

3035974

<https://www.phoenixcontact.com/sg/products/3035974>

4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch



STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

PAI-4-FIX-5/6 YE - Test adapter

3035977

<https://www.phoenixcontact.com/sg/products/3035977>

4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch



PAI-4-FIX-5/6 RD - Test adapter

3035976

<https://www.phoenixcontact.com/sg/products/3035976>

4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch



STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

PAI-4-FIX-5/6 GN - Test adapter

3035978

<https://www.phoenixcontact.com/sg/products/3035978>

4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch



PAI-4-FIX-5/6 BK - Test adapter

3035980

<https://www.phoenixcontact.com/sg/products/3035980>

4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch



STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

PAI-4-FIX-5/6 GY - Test adapter

3035982

<https://www.phoenixcontact.com/sg/products/3035982>

4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch



PAI-4-FIX-5/6 VT - Test adapter

3035979

<https://www.phoenixcontact.com/sg/products/3035979>

4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch



STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

PAI-4-FIX-5/6 BN - Test adapter

3035981

<https://www.phoenixcontact.com/sg/products/3035981>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

PAI-4-FIX-5/6 WH - Test adapter

3035983

<https://www.phoenixcontact.com/sg/products/3035983>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

PS-5 - Test plug

3030983

<https://www.phoenixcontact.com/sg/products/3030983>

Test plug, Modular test plug, number of positions: 1, color: red



DP PS-5 - Spacer plate

3036725

<https://www.phoenixcontact.com/sg/products/3036725>

Spacer plate, depth: 29 mm, width: 5.2 mm, height: 22.4 mm, number of positions: 1, color: red



STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

PS-5/2,3MM RD - Test plug

3038723

<https://www.phoenixcontact.com/sg/products/3038723>

Test plug, number of positions: 1, color: red



CLIPFIX 35 - End bracket

3022218

<https://www.phoenixcontact.com/sg/products/3022218>

Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, width: 9.5 mm, color: gray



STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

CLIPFIX 35-5 - End bracket

3022276

<https://www.phoenixcontact.com/sg/products/3022276>




Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, with parking option for FBS...5, FBS...6, KSS 5, KSS 6, width: 5.15 mm, color: gray

E/NS 35 N - End bracket

0800886

<https://www.phoenixcontact.com/sg/products/0800886>



End clamp, width: 9.5 mm, color: gray

STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

E/UK - End bracket

1201442

<https://www.phoenixcontact.com/sg/products/1201442>

End bracket, Mounting on a DIN rail NS 32 or NS 35, material: PA, color: gray



E/UK 1 - End bracket

1201413

<https://www.phoenixcontact.com/sg/products/1201413>

End clamps, for supporting the ends of double-level and three-level terminal blocks, width: 10 mm, color: gray



STTBS 2,5-PE - Protective conductor double-level terminal block



3038480

<https://www.phoenixcontact.com/sg/products/3038480>

SZF 1-0,6X3,5 - Screwdriver

1204517

<https://www.phoenixcontact.com/sg/products/1204517>



Actuation tool, for ST terminal blocks, also suitable for use as a bladed screwdriver, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip

ST-BW - Actuation tool

1207608

<https://www.phoenixcontact.com/sg/products/1207608>



Actuation tool, for all 2.5 mm² - 4.0 mm² spring-cages

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT SEA Pte. Ltd.

105 Eunus Avenue 3, #04-00

Singapore 409836

+65 6228 4900

marketing@phoenixcontact.com.sg