

# UT 35 RD - Feed-through terminal block



3044227

<https://www.phoenixcontact.com/pc/products/3044227>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Feed-through terminal block, nom. voltage: 1000 V, nominal current: 125 A, number of connections: 2, connection method: Screw connection, Rated cross section: 35 mm<sup>2</sup>, cross section: 1.5 mm<sup>2</sup> - 50 mm<sup>2</sup>, mounting type: NS 35/7,5, NS 35/15, color: red

## Your advantages

- The flexible options for reducing bridging in the CLIPLINE complete system can be found in "Accessories for the CLIPLINE complete modular terminal block system"
- The reducing bridges can be used to connect terminal blocks with different connection technologies, e.g., UT 35 screw terminal block with Push-in technology 2,5 Push-in terminal blocks, to form power blocks

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 3044227       |
| Packing unit                         | 50 pc         |
| Minimum order quantity               | 1 pc          |
| Product key                          | BE1111        |
| GTIN                                 | 4046356781237 |
| Weight per piece (including packing) | 59.148 g      |
| Weight per piece (excluding packing) | 59.148 g      |
| Customs tariff number                | 85369010      |
| Country of origin                    | TR            |

# UT 35 RD - Feed-through terminal block



3044227

<https://www.phoenixcontact.com/pc/products/3044227>

## Technical data

### Product properties

|                       |                             |
|-----------------------|-----------------------------|
| Product type          | Feed-through terminal block |
| Number of connections | 2                           |
| Number of rows        | 1                           |
| Potentials            | 1                           |

### Insulation characteristics

|                      |     |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution  | 3   |

### Electrical properties

|                                                 |        |
|-------------------------------------------------|--------|
| Rated surge voltage                             | 8 kV   |
| Maximum power dissipation for nominal condition | 4.06 W |

### Connection data

|                                 |                    |
|---------------------------------|--------------------|
| Number of connections per level | 2                  |
| Nominal cross section           | 35 mm <sup>2</sup> |

### Level 1 above 1 below 1

|                                                                                           |                                                                                                                              |
|-------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Screw thread                                                                              | M6                                                                                                                           |
| Tightening torque                                                                         | 3.2 ... 3.7 Nm                                                                                                               |
| Stripping length                                                                          | 18 mm                                                                                                                        |
| Internal cylindrical gage                                                                 | B9                                                                                                                           |
| Connection in acc. with standard                                                          | IEC 60947-7-1                                                                                                                |
| Conductor cross section rigid                                                             | 1.5 mm <sup>2</sup> ... 50 mm <sup>2</sup>                                                                                   |
| Cross section AWG                                                                         | 14 ... 2 (converted acc. to IEC)                                                                                             |
| Conductor cross section flexible                                                          | 1.5 mm <sup>2</sup> ... 50 mm <sup>2</sup>                                                                                   |
| Conductor cross section, flexible [AWG]                                                   | 14 ... 2 (converted acc. to IEC)                                                                                             |
| Conductor cross-section flexible (ferrule without plastic sleeve)                         | 1.5 mm <sup>2</sup> ... 35 mm <sup>2</sup>                                                                                   |
| Flexible conductor cross section (ferrule with plastic sleeve)                            | 1.5 mm <sup>2</sup> ... 35 mm <sup>2</sup>                                                                                   |
| 2 conductors with same cross section, solid                                               | 1.5 mm <sup>2</sup> ... 16 mm <sup>2</sup>                                                                                   |
| 2 conductors with same cross section, flexible                                            | 1.5 mm <sup>2</sup> ... 10 mm <sup>2</sup>                                                                                   |
| 2 conductors with same cross section, flexible, with ferrule without plastic sleeve       | 1.5 mm <sup>2</sup> ... 10 mm <sup>2</sup>                                                                                   |
| 2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve | 1.5 mm <sup>2</sup> ... 16 mm <sup>2</sup>                                                                                   |
| Nominal current                                                                           | 125 A                                                                                                                        |
| Maximum load current                                                                      | 150 A (with 50 mm <sup>2</sup> conductor cross section)                                                                      |
| Nominal voltage                                                                           | 1000 V                                                                                                                       |
| Note                                                                                      | Note: Product releases, connection cross sections and notes on connecting aluminum cables can be found in the download area. |
| Nominal cross section                                                                     | 35 mm <sup>2</sup>                                                                                                           |

# UT 35 RD - Feed-through terminal block



3044227

<https://www.phoenixcontact.com/pc/products/3044227>

## Ex data

### Rated data (ATEX/IECEx)

|                             |                                      |
|-----------------------------|--------------------------------------|
| Identification              | Ex II 2 GD Ex eb IIC Gb              |
| Operating temperature range | -60 °C ... 110 °C                    |
| Ex-certified accessories    | 1205079 SZS 1,0X6,5 VDE              |
|                             | 3022276 CLIPFIX 35-5                 |
|                             | 3022218 CLIPFIX 35                   |
| List of bridges             | Plug-in bridge / FBS 2-16 / 3005963  |
| Bridge data                 | 98.5 A / 35 mm <sup>2</sup>          |
| Ex temperature increase     | 40 K (133.6 A / 35 mm <sup>2</sup> ) |
| Rated voltage               | 690 V                                |
| for bridging with bridge    | 690 V                                |
| Rated insulation voltage    | 630 V                                |
| output                      | (Permanent)                          |

### Ex level General

|                      |         |
|----------------------|---------|
| Rated current        | 123 A   |
| Maximum load current | 129 A   |
| Contact resistance   | 0.08 mΩ |

### Ex connection data General

|                                                       |                                            |
|-------------------------------------------------------|--------------------------------------------|
| Torque range                                          | 3.2 Nm ... 3.7 Nm                          |
| Nominal cross section                                 | 35 mm <sup>2</sup>                         |
| Rated cross section AWG                               | 2                                          |
| Connection capacity rigid                             | 1.5 mm <sup>2</sup> ... 50 mm <sup>2</sup> |
| Connection capacity AWG                               | 16 ... 1/0                                 |
| Connection capacity flexible                          | 1.5 mm <sup>2</sup> ... 35 mm <sup>2</sup> |
| Connection capacity AWG                               | 16 ... 2                                   |
| 2 conductors with same cross section, solid           | 1.5 mm <sup>2</sup> ... 16 mm <sup>2</sup> |
| 2 conductors with the same cross-section AWG rigid    | 16 ... 6                                   |
| 2 conductors with same cross section, stranded        | 1.5 mm <sup>2</sup> ... 10 mm <sup>2</sup> |
| 2 conductors with the same cross-section AWG flexible | 16 ... 8                                   |

## Dimensions

|                    |         |
|--------------------|---------|
| Width              | 16 mm   |
| End cover width    | 2.2 mm  |
| Height             | 61.2 mm |
| Depth              | 65.1 mm |
| Depth on NS 35/7,5 | 65.7 mm |
| Depth on NS 35/15  | 73.2 mm |

## Material specifications

|                                        |     |
|----------------------------------------|-----|
| Color                                  | red |
| Flammability rating according to UL 94 | V0  |

# UT 35 RD - Feed-through terminal block



3044227

<https://www.phoenixcontact.com/pc/products/3044227>

|                                                                         |        |
|-------------------------------------------------------------------------|--------|
| Insulating material group                                               | I      |
| Insulating material                                                     | PA     |
| Static insulating material application in cold                          | -60 °C |
| Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) | 125 °C |
| Relative insulation material temperature index (Elec., UL 746 B)        | 125 °C |

## Electrical tests

### Surge voltage test

|                       |             |
|-----------------------|-------------|
| Test voltage setpoint | 9.8 kV      |
| Result                | Test passed |

### Temperature-rise test

|                                                 |                                     |
|-------------------------------------------------|-------------------------------------|
| Requirement temperature-rise test               | Increase in temperature $\leq 45$ K |
| Result                                          | Test passed                         |
| Short-time withstand current 35 mm <sup>2</sup> | 4.2 kA                              |
| Short-time withstand current 50 mm <sup>2</sup> | 6 kA                                |
| Result                                          | Test passed                         |

### Power-frequency withstand voltage

|                       |             |
|-----------------------|-------------|
| Test voltage setpoint | 2.2 kV      |
| Result                | Test passed |

## Mechanical properties

### Mechanical data

|                 |    |
|-----------------|----|
| Open side panel | No |
|-----------------|----|

## Mechanical tests

### Mechanical strength

|        |             |
|--------|-------------|
| Result | Test passed |
|--------|-------------|

### Attachment on the carrier

|                         |             |
|-------------------------|-------------|
| DIN rail/fixing support | NS 35       |
| Test force setpoint     | 10 N        |
| Result                  | Test passed |

### Test for conductor damage and slackening

|                                |                              |
|--------------------------------|------------------------------|
| Rotation speed                 | 10 rpm                       |
| Revolutions                    | 135                          |
| Conductor cross section/weight | 1.5 mm <sup>2</sup> / 0.4 kg |
|                                | 35 mm <sup>2</sup> / 6.8 kg  |
|                                | 50 mm <sup>2</sup> / 9.5 kg  |
| Result                         | Test passed                  |

## Environmental and real-life conditions

# UT 35 RD - Feed-through terminal block



3044227

<https://www.phoenixcontact.com/pc/products/3044227>

## Needle-flame test

|                  |             |
|------------------|-------------|
| Time of exposure | 30 s        |
| Result           | Test passed |

## Oscillation/broadband noise

|                        |                                                     |
|------------------------|-----------------------------------------------------|
| Specification          | DIN EN 50155 (VDE 0115-200):2008-03                 |
| Spectrum               | Service life test category 1, class B, body mounted |
| Frequency              | $f_1 = 5 \text{ Hz}$ to $f_2 = 150 \text{ Hz}$      |
| ASD level              | $1.857 \text{ (m/s}^2\text{)}^2\text{/Hz}$          |
| Acceleration           | 0.8g                                                |
| Test duration per axis | 5 h                                                 |
| Test directions        | X-, Y- and Z-axis                                   |
| Result                 | Test passed                                         |

## Shocks

|                                |                                     |
|--------------------------------|-------------------------------------|
| Specification                  | DIN EN 50155 (VDE 0115-200):2008-03 |
| Pulse shape                    | Half-sine                           |
| Acceleration                   | 5g                                  |
| Shock duration                 | 30 ms                               |
| Number of shocks per direction | 3                                   |
| Test directions                | X-, Y- and Z-axis (pos. and neg.)   |
| Result                         | Test passed                         |

## Ambient conditions

|                                          |                                                                                                                              |
|------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Ambient temperature (operation)          | -60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.) |
| Ambient temperature (storage/transport)  | -25 °C ... 60 °C ()                                                                                                          |
| Ambient temperature (assembly)           | -5 °C ... 70 °C                                                                                                              |
| Ambient temperature (actuation)          | -5 °C ... 70 °C ()                                                                                                           |
| Permissible humidity (operation)         | 20 % ... 90 %                                                                                                                |
| Permissible humidity (storage/transport) | 30 % ... 70 %                                                                                                                |

## Standards and regulations

|                                  |               |
|----------------------------------|---------------|
| Connection in acc. with standard | IEC 60947-7-1 |
|----------------------------------|---------------|

## Mounting

|               |           |
|---------------|-----------|
| Mounting type | NS 35/7,5 |
|               | NS 35/15  |

# UT 35 RD - Feed-through terminal block


3044227

<https://www.phoenixcontact.com/pc/products/3044227>




## Drawings

Circuit diagram



Schematic diagram



Connecting aluminum cables. Further notes can be found in the download area

# UT 35 RD - Feed-through terminal block



3044227

<https://www.phoenixcontact.com/pc/products/3044227>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/3044227>

### DNV

Approval ID: TAE00001S9



### CSA

Approval ID: 13631

|             | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|-------------|-----------------------|-----------------------|-------------------|-----------------------------|
| Use group B |                       |                       |                   |                             |
|             | 600 V                 | 150 A                 | 14 - 1/0          | -                           |



### IECEE CB Scheme

Approval ID: DE1-65779

|  | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|--|-----------------------|-----------------------|-------------------|-----------------------------|
|  | 1000 V                | 125 A                 | -                 | 1.5 - 35                    |



### cULus Recognized

Approval ID: E60425

|                            | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|----------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
| Use group B                |                       |                       |                   |                             |
|                            | 600 V                 | 150 A                 | 14 - 1/0          | -                           |
| Multi-conductor connection | 600 V                 | 150 A                 | 14                | -                           |
| Use group C                |                       |                       |                   |                             |
|                            | 600 V                 | 150 A                 | 14 - 1/0          | -                           |
| Multi-conductor connection | 600 V                 | 150 A                 | 14                | -                           |
| Use group E                |                       |                       |                   |                             |
|                            | 1000 V                | 150 A                 | 14 - 1/0          | -                           |
| Multi-conductor connection | 1000 V                | 150 A                 | 14                | -                           |



### RS

Approval ID: 22.44.01.00083.250



### VDE Zeichengenehmigung

Approval ID: 40020166

|  | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|--|-----------------------|-----------------------|-------------------|-----------------------------|
|  | 1000 V                | 125 A                 | -                 | 1.5 - 35                    |

# UT 35 RD - Feed-through terminal block



3044227

<https://www.phoenixcontact.com/pc/products/3044227>



## ATEX

Approval ID: KEMA04ATEX2048U

|                          | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|--------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
| Only flexible conductors | 690 V                 | 123 A                 | -                 | 1.5 - 35                    |
| Only rigid conductors    | 690 V                 | 129 A                 | -                 | 1.5 - 50                    |



## cUL Recognized

Approval ID: E192998

|  | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|--|-----------------------|-----------------------|-------------------|-----------------------------|
|  | 600 V                 | 150 A                 | 14 - 1/0          | -                           |



## EAC Ex

Approval ID: RU C-DE.HA91.B.00066



## IECEx

Approval ID: IECEx KEM 06.0027U

|                          | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|--------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
| Only flexible conductors | 690 V                 | 123 A                 | -                 | 1.5 - 35                    |
| Only rigid conductors    | 690 V                 | 129 A                 | -                 | 1.5 - 50                    |



## UL Recognized

Approval ID: E192998

|  | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|--|-----------------------|-----------------------|-------------------|-----------------------------|
|  | 600 V                 | 150 A                 | 14 - 1/0          | -                           |



## CCC

Approval ID: 2020322313000622



## UKCA-EX

Approval ID: DEKRA 21UKEX0304U

cULus Recognized



# UT 35 RD - Feed-through terminal block



3044227

<https://www.phoenixcontact.com/pc/products/3044227>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27141120 |
| ECLASS-13.0 | 27250101 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC000897 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# UT 35 RD - Feed-through terminal block



3044227

<https://www.phoenixcontact.com/pc/products/3044227>

## Environmental product compliance

|            |                                                         |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

# UT 35 RD - Feed-through terminal block



3044227

<https://www.phoenixcontact.com/pc/products/3044227>

## Accessories

**i** Note: Applying some accessories below might limit this product.

### FBS 2-16 - Plug-in bridge

3005963

<https://www.phoenixcontact.com/pc/products/3005963>



Plug-in bridge, pitch: 16 mm, number of positions: 2, length: 44 mm, color: red

**i** Max. current carrying capacity: 101 A

---

### RB UT 35-10 - Reducing bridge

3032168

<https://www.phoenixcontact.com/pc/products/3032168>



Reducing bridge, pitch: 13.2 mm, number of positions: 2, color: red

**i** Max. current carrying capacity: 57 A

# UT 35 RD - Feed-through terminal block

3044227

<https://www.phoenixcontact.com/pc/products/3044227>



## RB 35-16 - Reducing bridge

3032169

<https://www.phoenixcontact.com/pc/products/3032169>



Reducing bridge, pitch: 14 mm, number of positions: 2, color: red

 Max. current carrying capacity: 90 A

---

## RB UT 35-(2,5/4) - Reducing bridge

3047277

<https://www.phoenixcontact.com/pc/products/3047277>



Reducing bridge, pitch: 11 mm, number of positions: 2, color: red

 Max. current carrying capacity: 40 A

# UT 35 RD - Feed-through terminal block

3044227

<https://www.phoenixcontact.com/pc/products/3044227>



## RB UT 35-ST(2,5/4) - Reducing bridge

3047280

<https://www.phoenixcontact.com/pc/products/3047280>

Reducing bridge, pitch: 10.8 mm, number of positions: 2, color: red



 Max. current carrying capacity: 40 A

---

## AGK 4-UT 35 - Pick-off terminal block

3047138

<https://www.phoenixcontact.com/pc/products/3047138>



Pick-off terminal block, nom. voltage: 1000 V, nominal current: 32 A, number of connections: 1, connection method: Screw connection, cross section: 0.14 mm<sup>2</sup> - 6 mm<sup>2</sup>, mounting type: on base element, color: gray

## UT 35 RD - Feed-through terminal block

3044227

<https://www.phoenixcontact.com/pc/products/3044227>



## TPNS-UK - Partition plate

0706647

<https://www.phoenixcontact.com/pc/products/0706647>

Partition plate, depth: 70 mm, width: 2 mm, height: 80 mm, color: gray



---

## WS UT 35 - Warning label

3047387

<https://www.phoenixcontact.com/pc/products/3047387>

Warning sign for UT terminal blocks



# UT 35 RD - Feed-through terminal block

3044227

<https://www.phoenixcontact.com/pc/products/3044227>



## LPS-16/E - Service connector

3270620

<https://www.phoenixcontact.com/pc/products/3270620>



Service connector, cross section: 0.14 mm<sup>2</sup>- 4 mm<sup>2</sup>, color: red

---

## LPS-16 - Service connector

3270621

<https://www.phoenixcontact.com/pc/products/3270621>



Service connector, cross section: 0.14 mm<sup>2</sup>- 4 mm<sup>2</sup>, color: red

# UT 35 RD - Feed-through terminal block



3044227

<https://www.phoenixcontact.com/pc/products/3044227>

## LPO 35/E - Pick-up plug

3270542

<https://www.phoenixcontact.com/pc/products/3270542>



Pick-up plug, nom. voltage: 800 V, nominal current: 24 A, number of positions: 1, connection method: Push-in connection, Rated cross section: 2.5 mm<sup>2</sup>, cross section: 0.14 mm<sup>2</sup>- 4 mm<sup>2</sup>, color: gray

---

## LPO 35 - Pick-up plug

3270543

<https://www.phoenixcontact.com/pc/products/3270543>



Pick-up plug, nom. voltage: 800 V, nominal current: 24 A, number of positions: 1, connection method: Push-in connection, Rated cross section: 2.5 mm<sup>2</sup>, cross section: 0.14 mm<sup>2</sup>- 4 mm<sup>2</sup>, color: gray



# UT 35 RD - Feed-through terminal block

3044227

<https://www.phoenixcontact.com/pc/products/3044227>



## NS 35/ 7,5 PERF 2000MM - DIN rail perforated

0801733

<https://www.phoenixcontact.com/pc/products/0801733>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

---

## NS 35/ 7,5 UNPERF 2000MM - DIN rail, unperforated

0801681

<https://www.phoenixcontact.com/pc/products/0801681>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

# UT 35 RD - Feed-through terminal block

3044227

<https://www.phoenixcontact.com/pc/products/3044227>



## NS 35/ 7,5 WH PERF 2000MM - DIN rail perforated

1204119

<https://www.phoenixcontact.com/pc/products/1204119>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

---

## NS 35/ 7,5 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204122

<https://www.phoenixcontact.com/pc/products/1204122>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

# UT 35 RD - Feed-through terminal block

3044227

<https://www.phoenixcontact.com/pc/products/3044227>



## NS 35/ 7,5 AL UNPERF 2000MM - DIN rail, unperforated

0801704

<https://www.phoenixcontact.com/pc/products/0801704>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

---

## NS 35/ 7,5 ZN PERF 2000MM - DIN rail perforated

1206421

<https://www.phoenixcontact.com/pc/products/1206421>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

# UT 35 RD - Feed-through terminal block

3044227

<https://www.phoenixcontact.com/pc/products/3044227>



## NS 35/ 7,5 ZN UNPERF 2000MM - DIN rail, unperforated

1206434

<https://www.phoenixcontact.com/pc/products/1206434>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

---

## NS 35/ 7,5 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

0801762

<https://www.phoenixcontact.com/pc/products/0801762>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

## UT 35 RD - Feed-through terminal block

3044227

<https://www.phoenixcontact.com/pc/products/3044227>



## NS 35/ 7,5 CAP - End cap

1206560

<https://www.phoenixcontact.com/pc/products/1206560>

DIN rail end piece, for DIN rail NS 35/7.5



---

## NS 35/15 PERF 2000MM - DIN rail perforated

1201730

<https://www.phoenixcontact.com/pc/products/1201730>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

# UT 35 RD - Feed-through terminal block

3044227

<https://www.phoenixcontact.com/pc/products/3044227>



## NS 35/15 UNPERF 2000MM - DIN rail, unperforated

1201714

<https://www.phoenixcontact.com/pc/products/1201714>



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

---

## NS 35/15 WH PERF 2000MM - DIN rail perforated

0806602

<https://www.phoenixcontact.com/pc/products/0806602>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: white

# UT 35 RD - Feed-through terminal block

3044227

<https://www.phoenixcontact.com/pc/products/3044227>



## NS 35/15 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204135

<https://www.phoenixcontact.com/pc/products/1204135>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

---

## NS 35/15 AL UNPERF 2000MM - DIN rail, unperforated

1201756

<https://www.phoenixcontact.com/pc/products/1201756>



DIN rail, unperforated, similar to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

# UT 35 RD - Feed-through terminal block

3044227

<https://www.phoenixcontact.com/pc/products/3044227>



## NS 35/15 ZN PERF 2000MM - DIN rail perforated

1206599

<https://www.phoenixcontact.com/pc/products/1206599>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver

---

## NS 35/15 ZN UNPERF 2000MM - DIN rail, unperforated

1206586

<https://www.phoenixcontact.com/pc/products/1206586>



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver



# UT 35 RD - Feed-through terminal block

3044227

<https://www.phoenixcontact.com/pc/products/3044227>



## NS 35/15 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201895

<https://www.phoenixcontact.com/pc/products/1201895>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

---

## NS 35/15 CAP - End cap

1206573

<https://www.phoenixcontact.com/pc/products/1206573>



DIN rail end piece, for DIN rail NS 35/15

## UT 35 RD - Feed-through terminal block

3044227

<https://www.phoenixcontact.com/pc/products/3044227>



## NS 35/15-2,3 UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201798

<https://www.phoenixcontact.com/pc/products/1201798>




DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile 2.3 mm, color: silver

---

## ZB 16:UNPRINTED - Zack marker strip

0827461

<https://www.phoenixcontact.com/pc/products/0827461>



Zack marker strip, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 16 mm, lettering field size: 16 x 10.5 mm, Number of individual labels: 50

# UT 35 RD - Feed-through terminal block

3044227


<https://www.phoenixcontact.com/pc/products/3044227>



## ZB 16 CUS - Zack marker strip

0827463

<https://www.phoenixcontact.com/pc/products/0827463>




Zack marker strip, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 16 mm, lettering field size: 10.5 x 16 mm, Number of individual labels: 5

---

## ZB 16,LGS:L1-N,PE - Zack marker strip

0827462

<https://www.phoenixcontact.com/pc/products/0827462>



Zack marker strip, Strip, white, labeled, printed horizontally: L1, L2, L3, N, PE, mounting type: snapped, for terminal block width: 16.3 mm, lettering field size: 10.5 x 16.25 mm, Number of individual labels: 5

# UT 35 RD - Feed-through terminal block

3044227

<https://www.phoenixcontact.com/pc/products/3044227>



## UC-TM 16 - Marker for terminal blocks

0819217

<https://www.phoenixcontact.com/pc/products/0819217>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 16 mm, lettering field size: 15.45 x 10.5 mm, Number of individual labels: 32

---

## UC-TM 16 CUS - Marker for terminal blocks

0824621

<https://www.phoenixcontact.com/pc/products/0824621>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 16 mm, lettering field size: 15.45 x 10.5 mm, Number of individual labels: 32

# UT 35 RD - Feed-through terminal block

3044227

<https://www.phoenixcontact.com/pc/products/3044227>



## UCT-TM 16 - Marker for terminal blocks

0829146

<https://www.phoenixcontact.com/pc/products/0829146>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, for terminal block width: 16 mm, lettering field size: 14.8 x 9.6 mm, Number of individual labels: 18

---

## UCT-TM 16 CUS - Marker for terminal blocks

0829637

<https://www.phoenixcontact.com/pc/products/0829637>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 16 mm, lettering field size: 14.8 x 9.6 mm, Number of individual labels: 18

## UT 35 RD - Feed-through terminal block

3044227

<https://www.phoenixcontact.com/pc/products/3044227>



## X-PEN 0,35 - Marker pen

0811228

<https://www.phoenixcontact.com/pc/products/0811228>



Marker pen without ink cartridge, for manual labeling of markers, labeling extremely wipe-proof, line thickness 0.35 mm

---

## SZS 1,0X6,5 VDE - Screwdriver

1205079

<https://www.phoenixcontact.com/pc/products/1205079>



Screwdriver, slot-headed, VDE insulated, size: 1.0 x 6.5 x 150 mm, 2-component grip, with non-slip grip

# UT 35 RD - Feed-through terminal block

3044227

<https://www.phoenixcontact.com/pc/products/3044227>



## PROJECT COMPLETE - Software

1050453

<https://www.phoenixcontact.com/pc/products/1050453>



Intuitive planning and marking software for configuring terminal strips and for professional marking of marking materials for terminal blocks, conductors, cables, devices, and systems. The software is available for download

---

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG

Flachsmarktstraße 8

D-32825 Blomberg

+49 (0) 5235-3 00

[info@phoenixcontact.com](mailto:info@phoenixcontact.com)