


UT 6-MTL P/P KNIFE-WH - Knife-disconnect terminal block

3046151
<https://www.phoenixcontact.com/ae/products/3046151>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Knife-disconnect terminal block, with actuation latch, white disconnect knife, and test socket screws for insertion of test plugs, nom. voltage: 500 V, nominal current: 20 A, connection method: Screw connection, Rated cross section: 2.5 mm², cross section: 0.2 mm² - 10 mm², mounting: NS 35/7,5, NS 35/15, color: gray

Your advantages

- Compact design and high current carrying capacity of 20 A
- Double bridge shaft enables individual potential distribution and supply

Commercial data

Item number	3046151
Packing unit	50 pc
Minimum order quantity	50 pc
Note	Made to order (non-returnable)
Sales key	BE1
Product key	BE1131
Catalog page	Page 175 (C-1-2019)
GTIN	4055626063416
Weight per piece (including packing)	18.48 g
Weight per piece (excluding packing)	18.48 g
Customs tariff number	85369010
Country of origin	PL

UT 6-MTL P/P KNIFE-WH - Knife-disconnect terminal block



3046151

<https://www.phoenixcontact.com/ae/products/3046151>

Technical data

Product properties

Product type	Disconnect terminal block
Number of connections	2
Number of rows	1
Potentials	1

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Electrical properties

Rated surge voltage	6 kV
Maximum power dissipation for nominal condition	1.31 W

Connection data

Number of connections per level	2
Nominal cross section	6 mm ²

Level 1 above 1 below 1

Screw thread	M4
Tightening torque	1.5 ... 1.8 Nm
Stripping length	10 mm
Internal cylindrical gage	A5
Connection in acc. with standard	IEC 60947-7-1
Conductor cross section rigid	0.2 mm ² ... 10 mm ²
Cross section AWG	24 ... 8 (converted acc. to IEC)
Conductor cross section flexible	0.2 mm ² ... 10 mm ²
Conductor cross section, flexible [AWG]	24 ... 8 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve)	0.25 mm ² ... 6 mm ²
Flexible conductor cross section (ferrule with plastic sleeve)	0.25 mm ² ... 6 mm ²
2 conductors with same cross section, solid	0.2 mm ² ... 2.5 mm ²
2 conductors with same cross section, flexible	0.2 mm ² ... 2.5 mm ²
2 conductors with same cross section, flexible, with ferrule without plastic sleeve	0.25 mm ² ... 1.5 mm ²
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve	0.5 mm ² ... 4 mm ²
Nominal current	20 A
Maximum load current	20 A (with 10 mm ² conductor cross section)
Nominal voltage	500 V
Nominal cross section	2.5 mm ²

Dimensions

Width	8.2 mm
-------	--------

UT 6-MTL P/P KNIFE-WH - Knife-disconnect terminal block



3046151

<https://www.phoenixcontact.com/ae/products/3046151>

Material specifications

Color	gray
Flammability rating according to UL 94	V0
Insulating material group	I
Insulating material	PA
Static insulating material application in cold	-60 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	125 °C
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3
Calorimetric heat release NFPA 130 (ASTM E 1354)	27,5 MJ/kg
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed

Mechanical properties

Mechanical data

Open side panel	No
-----------------	----

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (storage/transport)	30 % ... 70 %

Standards and regulations

Connection in acc. with standard	IEC 60947-7-1
----------------------------------	---------------

Mounting

Mounting type	NS 35/7,5
	NS 35/15

UT 6-MTL P/P KNIFE-WH - Knife-disconnect terminal block




3046151

<https://www.phoenixcontact.com/ae/products/3046151>

Drawings

Circuit diagram



3046151
<https://www.phoenixcontact.com/ae/products/3046151>

Classifications

ECLASS	
ECLASS-11.0	27141126
ETIM	
ETIM 8.0	EC000902
UNSPSC	
UNSPSC 21.0	39121400

3046151
<https://www.phoenixcontact.com/ae/products/3046151>

Environmental product compliance

China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

UT 6-MTL P/P KNIFE-WH - Knife-disconnect terminal block



3046151

<https://www.phoenixcontact.com/ae/products/3046151>

Accessories



Note: Applying some accessories below might limit this product.

FBS 2-8 - Plug-in bridge

3030284

<https://www.phoenixcontact.com/ae/products/3030284>



Plug-in bridge, pitch: 8.2 mm, number of positions: 2, color: red



Max. current carrying capacity: 20 A

FBS 3-8 - Plug-in bridge

3030297

<https://www.phoenixcontact.com/ae/products/3030297>



Plug-in bridge, pitch: 8.2 mm, number of positions: 3, color: red



Max. current carrying capacity: 20 A

UT 6-MTL P/P KNIFE-WH - Knife-disconnect terminal block



3046151

<https://www.phoenixcontact.com/ae/products/3046151>

FBS 4-8 - Plug-in bridge

3030307

<https://www.phoenixcontact.com/ae/products/3030307>

Plug-in bridge, pitch: 8.2 mm, number of positions: 4, color: red



 Max. current carrying capacity: 20 A

FBS 5-8 - Plug-in bridge

3030310

<https://www.phoenixcontact.com/ae/products/3030310>

Plug-in bridge, pitch: 8.2 mm, number of positions: 5, color: red



 Max. current carrying capacity: 20 A

UT 6-MTL P/P KNIFE-WH - Knife-disconnect terminal block



3046151

<https://www.phoenixcontact.com/ae/products/3046151>

FBS 6-8 - Plug-in bridge

3032470

<https://www.phoenixcontact.com/ae/products/3032470>



Plug-in bridge, pitch: 8.2 mm, number of positions: 6, color: red

 Max. current carrying capacity: 20 A

FBSRH 2-8 - Short-circuit connector

3033802

<https://www.phoenixcontact.com/ae/products/3033802>



Short-circuit connector, pitch: 8.2 mm, number of positions: 2, color: red

 Max. current carrying capacity: 20 A

UT 6-MTL P/P KNIFE-WH - Knife-disconnect terminal block



3046151

<https://www.phoenixcontact.com/ae/products/3046151>

FBSRH 3-8 - Short-circuit connector

3033803

<https://www.phoenixcontact.com/ae/products/3033803>



Short-circuit connector, pitch: 8.2 mm, number of positions: 3, color: red

 Max. current carrying capacity: 20 A

FBSRH 4-8 - Short-circuit connector

3033804

<https://www.phoenixcontact.com/ae/products/3033804>



Short-circuit connector, pitch: 8.2 mm, number of positions: 4, color: red

 Max. current carrying capacity: 20 A

UT 6-MTL P/P KNIFE-WH - Knife-disconnect terminal block



3046151

<https://www.phoenixcontact.com/ae/products/3046151>

FBSR 2-8 - Plug-in bridge

3033808

<https://www.phoenixcontact.com/ae/products/3033808>



Plug-in bridge, pitch: 8.2 mm, number of positions: 2, color: red

 Max. current carrying capacity: 20 A

FBSR 3-8 - Plug-in bridge

3001597

<https://www.phoenixcontact.com/ae/products/3001597>



Plug-in bridge, pitch: 8.2 mm, number of positions: 3, color: red

 Max. current carrying capacity: 20 A

UT 6-MTL P/P KNIFE-WH - Knife-disconnect terminal block



3046151

<https://www.phoenixcontact.com/ae/products/3046151>

FBSR 4-8 - Plug-in bridge

3000585

<https://www.phoenixcontact.com/ae/products/3000585>



Plug-in bridge, pitch: 8.2 mm, number of positions: 4, color: red

 Max. current carrying capacity: 20 A

FBSR 5-8 - Plug-in bridge

3033809

<https://www.phoenixcontact.com/ae/products/3033809>



Plug-in bridge, pitch: 8.2 mm, number of positions: 5, color: red

 Max. current carrying capacity: 20 A

UT 6-MTL P/P KNIFE-WH - Knife-disconnect terminal block



3046151

<https://www.phoenixcontact.com/ae/products/3046151>

FBSR 10-8 - Plug-in bridge

3001599

<https://www.phoenixcontact.com/ae/products/3001599>



Plug-in bridge, pitch: 8.2 mm, number of positions: 10, color: red

 Max. current carrying capacity: 20 A

FBS 2-8 CT - Plug-in bridge

3033830

<https://www.phoenixcontact.com/ae/products/3033830>



Plug-in bridge, pitch: 8.2 mm, number of positions: 2, color: orange

 Max. current carrying capacity: 20 A

UT 6-MTL P/P KNIFE-WH - Knife-disconnect terminal block



3046151

<https://www.phoenixcontact.com/ae/products/3046151>

FBS 3-8 CT - Plug-in bridge

3033831

<https://www.phoenixcontact.com/ae/products/3033831>



Plug-in bridge, pitch: 8.2 mm, number of positions: 3, color: orange

 Max. current carrying capacity: 20 A

FBS 4-8 CT - Plug-in bridge

3033832

<https://www.phoenixcontact.com/ae/products/3033832>



Plug-in bridge, pitch: 8.2 mm, number of positions: 4, color: orange

 Max. current carrying capacity: 20 A

UT 6-MTL P/P KNIFE-WH - Knife-disconnect terminal block



3046151

<https://www.phoenixcontact.com/ae/products/3046151>

FBS 10-8 CT - Plug-in bridge

3033833

<https://www.phoenixcontact.com/ae/products/3033833>



Plug-in bridge, pitch: 8.2 mm, number of positions: 10, color: orange

 Max. current carrying capacity: 20 A

SB-MER 2-8 - Switching jumper

3000587

<https://www.phoenixcontact.com/ae/products/3000587>



Switching jumper, pitch: 8.2 mm, number of positions: 2, length: 25 mm, color: gray/orange

 Max. current carrying capacity: 25 A

UT 6-MTL P/P KNIFE-WH - Knife-disconnect terminal block



3046151

<https://www.phoenixcontact.com/ae/products/3046151>

SB-MER 3-8 - Switching jumper

3000588

<https://www.phoenixcontact.com/ae/products/3000588>



Switching jumper, pitch: 8.2 mm, number of positions: 3, length: 25 mm, color: gray/orange

 Max. current carrying capacity: 25 A

SB-MER 4-8 - Switching jumper

3000589

<https://www.phoenixcontact.com/ae/products/3000589>



Switching jumper, pitch: 8.2 mm, number of positions: 4, length: 25 mm, color: gray/orange

 Max. current carrying capacity: 25 A

UT 6-MTL P/P KNIFE-WH - Knife-disconnect terminal block



3046151

<https://www.phoenixcontact.com/ae/products/3046151>

FBS 2-8 BU - Plug-in bridge

3032567

<https://www.phoenixcontact.com/ae/products/3032567>



Plug-in bridge, pitch: 8.2 mm, number of positions: 2, color: blue

 Max. current carrying capacity: 20 A

FBS 3-8 BU - Plug-in bridge

3032570

<https://www.phoenixcontact.com/ae/products/3032570>



Plug-in bridge, pitch: 8.2 mm, number of positions: 3, color: blue

 Max. current carrying capacity: 20 A

UT 6-MTL P/P KNIFE-WH - Knife-disconnect terminal block



3046151

<https://www.phoenixcontact.com/ae/products/3046151>

FBS 4-8 BU - Plug-in bridge

3032583

<https://www.phoenixcontact.com/ae/products/3032583>



Plug-in bridge, pitch: 8.2 mm, number of positions: 4, color: blue

 Max. current carrying capacity: 20 A

FBS 5-8 BU - Plug-in bridge

3032596

<https://www.phoenixcontact.com/ae/products/3032596>



Plug-in bridge, pitch: 8.2 mm, number of positions: 5, color: blue

 Max. current carrying capacity: 20 A

UT 6-MTL P/P KNIFE-WH - Knife-disconnect terminal block



3046151

<https://www.phoenixcontact.com/ae/products/3046151>

FBS 6-8 BU - Plug-in bridge

3032677

<https://www.phoenixcontact.com/ae/products/3032677>

Plug-in bridge, pitch: 8.2 mm, number of positions: 6, color: blue



 Max. current carrying capacity: 20 A

FBS 10-8 BU - Plug-in bridge

3032606

<https://www.phoenixcontact.com/ae/products/3032606>

Plug-in bridge, pitch: 8.2 mm, number of positions: 10, color: blue



 Max. current carrying capacity: 20 A

UT 6-MTL P/P KNIFE-WH - Knife-disconnect terminal block



3046151

<https://www.phoenixcontact.com/ae/products/3046151>

RB 16-6 - Reducing bridge

3047072

<https://www.phoenixcontact.com/ae/products/3047072>



Reducing bridge, pitch: 12.2 mm, number of positions: 2, color: red

 Max. current carrying capacity: 37 A

RB UT 6-ST(2,5/4) - Reducing bridge

3047264

<https://www.phoenixcontact.com/ae/products/3047264>



Reducing bridge, pitch: 9.5 mm, number of positions: 2, length: 33 mm, color: red

 Max. current carrying capacity: 35 A

UT 6-MTL P/P KNIFE-WH - Knife-disconnect terminal block



3046151

<https://www.phoenixcontact.com/ae/products/3046151>

RB UT 6-(2,5/4) - Reducing bridge

3047251

<https://www.phoenixcontact.com/ae/products/3047251>

Reducing bridge, pitch: 9.5 mm, number of positions: 2, length: 25 mm, color: red



 Max. current carrying capacity: 40 A

ATP-UT-TWIN - Partition plate

3047183

<https://www.phoenixcontact.com/ae/products/3047183>

Partition plate, depth: 52.5 mm, width: 2.2 mm, height: 62.1 mm, color: gray



UT 6-MTL P/P KNIFE-WH - Knife-disconnect terminal block



3046151

<https://www.phoenixcontact.com/ae/products/3046151>

SZS 1,0X4,0 VDE - Screwdriver

1205066

<https://www.phoenixcontact.com/ae/products/1205066>



Screwdriver, slot-headed, VDE insulated, size: 1.0 x 4.0 x 100 mm, 2-component grip, with non-slip grip

X-PEN 0,35 - Marker pen

0811228

<https://www.phoenixcontact.com/ae/products/0811228>



Marker pen without ink cartridge, for manual labeling of markers, labeling extremely wipe-proof, line thickness 0.35 mm

UT 6-MTL P/P KNIFE-WH - Knife-disconnect terminal block



3046151

<https://www.phoenixcontact.com/ae/products/3046151>

NS 35/ 7,5 PERF 2000MM - DIN rail perforated

0801733

<https://www.phoenixcontact.com/ae/products/0801733>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

NS 35/ 7,5 UNPERF 2000MM - DIN rail, unperforated

0801681

<https://www.phoenixcontact.com/ae/products/0801681>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

UT 6-MTL P/P KNIFE-WH - Knife-disconnect terminal block



3046151

<https://www.phoenixcontact.com/ae/products/3046151>

NS 35/ 7,5 WH PERF 2000MM - DIN rail perforated

1204119

<https://www.phoenixcontact.com/ae/products/1204119>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

NS 35/ 7,5 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204122

<https://www.phoenixcontact.com/ae/products/1204122>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

UT 6-MTL P/P KNIFE-WH - Knife-disconnect terminal block



3046151

<https://www.phoenixcontact.com/ae/products/3046151>

NS 35/ 7,5 AL UNPERF 2000MM - DIN rail, unperforated

0801704

<https://www.phoenixcontact.com/ae/products/0801704>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

NS 35/ 7,5 ZN PERF 2000MM - DIN rail perforated

1206421

<https://www.phoenixcontact.com/ae/products/1206421>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

UT 6-MTL P/P KNIFE-WH - Knife-disconnect terminal block



3046151

<https://www.phoenixcontact.com/ae/products/3046151>

NS 35/ 7,5 ZN UNPERF 2000MM - DIN rail, unperforated

1206434

<https://www.phoenixcontact.com/ae/products/1206434>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

NS 35/ 7,5 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

0801762

<https://www.phoenixcontact.com/ae/products/0801762>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

UT 6-MTL P/P KNIFE-WH - Knife-disconnect terminal block



3046151

<https://www.phoenixcontact.com/ae/products/3046151>

NS 35/ 7,5 CAP - End cap

1206560

<https://www.phoenixcontact.com/ae/products/1206560>

DIN rail end piece, for DIN rail NS 35/7.5



NS 35/15 PERF 2000MM - DIN rail perforated

1201730

<https://www.phoenixcontact.com/ae/products/1201730>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

UT 6-MTL P/P KNIFE-WH - Knife-disconnect terminal block



3046151

<https://www.phoenixcontact.com/ae/products/3046151>

NS 35/15 UNPERF 2000MM - DIN rail, unperforated

1201714

<https://www.phoenixcontact.com/ae/products/1201714>



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

NS 35/15 WH PERF 2000MM - DIN rail perforated

0806602

<https://www.phoenixcontact.com/ae/products/0806602>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: white

UT 6-MTL P/P KNIFE-WH - Knife-disconnect terminal block



3046151

<https://www.phoenixcontact.com/ae/products/3046151>

NS 35/15 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204135

<https://www.phoenixcontact.com/ae/products/1204135>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

NS 35/15 AL UNPERF 2000MM - DIN rail, unperforated

1201756

<https://www.phoenixcontact.com/ae/products/1201756>



DIN rail, unperforated, similar to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

UT 6-MTL P/P KNIFE-WH - Knife-disconnect terminal block



3046151

<https://www.phoenixcontact.com/ae/products/3046151>

NS 35/15 ZN PERF 2000MM - DIN rail perforated

1206599

<https://www.phoenixcontact.com/ae/products/1206599>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver

NS 35/15 ZN UNPERF 2000MM - DIN rail, unperforated

1206586

<https://www.phoenixcontact.com/ae/products/1206586>



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver

UT 6-MTL P/P KNIFE-WH - Knife-disconnect terminal block



3046151

<https://www.phoenixcontact.com/ae/products/3046151>

NS 35/15 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201895

<https://www.phoenixcontact.com/ae/products/1201895>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

NS 35/15 CAP - End cap

1206573

<https://www.phoenixcontact.com/ae/products/1206573>

DIN rail end piece, for DIN rail NS 35/15



UT 6-MTL P/P KNIFE-WH - Knife-disconnect terminal block



3046151

<https://www.phoenixcontact.com/ae/products/3046151>

NS 35/15-2,3 UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201798

<https://www.phoenixcontact.com/ae/products/1201798>




DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile 2.3 mm, color: silver

ZB 8:UNBEDRUCKT - Zack marker strip

1052002

<https://www.phoenixcontact.com/ae/products/1052002>



Zack marker strip, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 10.5 x 8.15 mm, Number of individual labels: 10

UT 6-MTL P/P KNIFE-WH - Knife-disconnect terminal block




3046151

<https://www.phoenixcontact.com/ae/products/3046151>

ZB 8 CUS - Zack marker strip

0825011

<https://www.phoenixcontact.com/ae/products/0825011>



Zack marker strip, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 8.2 mm, lettering field size: 10.5 x 8.15 mm, Number of individual labels: 10

UC-TM 8 - Marker for terminal blocks

0818072

<https://www.phoenixcontact.com/ae/products/0818072>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 7.6 x 10.5 mm, Number of individual labels: 56

UT 6-MTL P/P KNIFE-WH - Knife-disconnect terminal block



3046151

<https://www.phoenixcontact.com/ae/products/3046151>

UC-TM 8 CUS - Marker for terminal blocks

0824597

<https://www.phoenixcontact.com/ae/products/0824597>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 8.2 mm, lettering field size: 7.6 x 10.5 mm, Number of individual labels: 56

UCT-TM 8 - Marker for terminal blocks

0828740

<https://www.phoenixcontact.com/ae/products/0828740>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 7.6 x 10.5 mm, Number of individual labels: 42

UT 6-MTL P/P KNIFE-WH - Knife-disconnect terminal block



3046151

<https://www.phoenixcontact.com/ae/products/3046151>

UCT-TM 8 CUS - Marker for terminal blocks

0829616

<https://www.phoenixcontact.com/ae/products/0829616>




Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 8.2 mm, lettering field size: 7.6 x 10.5 mm, Number of individual labels: 42

ZB 8,LGS:FORTL.ZAHLEN - Zack marker strip

1052015

<https://www.phoenixcontact.com/ae/products/1052015>



Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, printed horizontally: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 91 ... 100, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 10.5 x 8.15 mm, Number of individual labels: 10

UT 6-MTL P/P KNIFE-WH - Knife-disconnect terminal block



3046151

<https://www.phoenixcontact.com/ae/products/3046151>

ZB 8,QR:FORTL.ZAHLEN - Zack marker strip

1052028

<https://www.phoenixcontact.com/ae/products/1052028>




Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, Printed vertically: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 91 ... 100, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 10.5 x 8.15 mm, Number of individual labels: 10

ZB 8,LGS:L1-N,PE - Marker for terminal blocks

1052413

<https://www.phoenixcontact.com/ae/products/1052413>



Marker for terminal blocks, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, horizontal: L1, L2, L3, N, PE, L1, L2, L3, N, PE, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 10.5 x 8.15 mm, Number of individual labels: 10

UT 6-MTL P/P KNIFE-WH - Knife-disconnect terminal block



3046151

<https://www.phoenixcontact.com/ae/products/3046151>

MPS-MT - Test plug

0201744

<https://www.phoenixcontact.com/ae/products/0201744>



Test plug, with solder connection up to 1 mm² conductor cross section, number of positions: 1, color: gray

MPS-IH WH - Insulating sleeve

0201663

<https://www.phoenixcontact.com/ae/products/0201663>

Insulating sleeve, color: white



UT 6-MTL P/P KNIFE-WH - Knife-disconnect terminal block



3046151

<https://www.phoenixcontact.com/ae/products/3046151>

MPS-IH RD - Insulating sleeve

0201676

<https://www.phoenixcontact.com/ae/products/0201676>

Insulating sleeve, color: red




MPS-IH BU - Insulating sleeve

0201689

<https://www.phoenixcontact.com/ae/products/0201689>

Insulating sleeve, color: blue



UT 6-MTL P/P KNIFE-WH - Knife-disconnect terminal block



3046151

<https://www.phoenixcontact.com/ae/products/3046151>

MPS-IH YE - Insulating sleeve

0201692

<https://www.phoenixcontact.com/ae/products/0201692>

Insulating sleeve, color: yellow



MPS-IH GN - Insulating sleeve

0201702

<https://www.phoenixcontact.com/ae/products/0201702>

Insulating sleeve, color: green



UT 6-MTL P/P KNIFE-WH - Knife-disconnect terminal block



3046151

<https://www.phoenixcontact.com/ae/products/3046151>

MPS-IH GY - Insulating sleeve

0201728

<https://www.phoenixcontact.com/ae/products/0201728>

Insulating sleeve, color: gray



MPS-IH BK - Insulating sleeve

0201731

<https://www.phoenixcontact.com/ae/products/0201731>

Insulating sleeve, color: black



UT 6-MTL P/P KNIFE-WH - Knife-disconnect terminal block



3046151

<https://www.phoenixcontact.com/ae/products/3046151>

CLIPFIX 35 - End bracket

3022218

<https://www.phoenixcontact.com/ae/products/3022218>



Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, width: 9.5 mm, color: gray

CLIPFIX 35-5 - End bracket

3022276

<https://www.phoenixcontact.com/ae/products/3022276>



Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, with parking option for FBS...5, FBS...6, KSS 5, KSS 6, width: 5.15 mm, color: gray

UT 6-MTL P/P KNIFE-WH - Knife-disconnect terminal block



3046151


<https://www.phoenixcontact.com/ae/products/3046151>

E/NS 35 N - End bracket

0800886

<https://www.phoenixcontact.com/ae/products/0800886>

End clamp, width: 9.5 mm, color: gray



PAI-4-N GY - Test adapter

3032871

<https://www.phoenixcontact.com/ae/products/3032871>

4 mm test adapter, for terminal blocks with 5.2 mm, 6.2 mm and 8.2 mm pitch



Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT Middle East FZ LLC
1201N-1206N, Dubai Science Park Towers – North
P.O. Box 345002, Dubai, United Arab Emirates
(+971) 4 437-0324
info-me@phoenixcontact.com