


# QTCS 1,5 BU - Feed-through terminal block



3050141

<https://www.phoenixcontact.com/us/products/3050141>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Feed-through terminal block, nom. voltage: 800 V, nominal current: 17.5 A, 1 level, connection method: Quick connection, Rated cross section: 1.5 mm<sup>2</sup>, cross section: 0.25 mm<sup>2</sup> - 1.5 mm<sup>2</sup>, connection method: Spring-cage connection, Rated cross section: 1.5 mm<sup>2</sup>, cross section: 0.08 mm<sup>2</sup> - 4 mm<sup>2</sup>, mounting: NS 35/7,5, NS 35/15, color: blue

## Your advantages

- The hybrid versions combine the advantages of the different connection technologies
- The time-saving QUICKON fast connection is used on the control cabinet side
- The spring-cage connection is used on the connection side

## Commercial data

|                                      |                                |
|--------------------------------------|--------------------------------|
| Item number                          | 3050141                        |
| Packing unit                         | 1 pc                           |
| Note                                 | Made to order (non-returnable) |
| Sales key                            | BE03                           |
| Product key                          | BE3119                         |
| Catalog page                         | Page 261 (C-1-2019)            |
| GTIN                                 | 4017918975821                  |
| Weight per piece (including packing) | 7.37 g                         |
| Weight per piece (excluding packing) | 6 g                            |
| Customs tariff number                | 85369010                       |
| Country of origin                    | CN                             |

# QTCS 1,5 BU - Feed-through terminal block



3050141

<https://www.phoenixcontact.com/us/products/3050141>

## Technical data

### Product properties

|                       |                       |
|-----------------------|-----------------------|
| Product type          | Hybrid terminal block |
| Number of connections | 2                     |
| Number of rows        | 1                     |
| Potentials            | 1                     |

### Data management status

|                  |    |
|------------------|----|
| Article revision | 05 |
|------------------|----|

### Insulation characteristics

|                      |     |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution  | 3   |

### Electrical properties

|                                                 |        |
|-------------------------------------------------|--------|
| Rated surge voltage                             | 8 kV   |
| Maximum power dissipation for nominal condition | 0.56 W |

### Connection data

|                                                      |                     |
|------------------------------------------------------|---------------------|
| Number of connections per level                      | 2                   |
| Frequency of connections with the same cross section | 100                 |
| Nominal cross section                                | 1.5 mm <sup>2</sup> |

#### 1 level

|                                         |                                                           |
|-----------------------------------------|-----------------------------------------------------------|
| Stripping length                        | 10 mm                                                     |
| Material wire insulation                | PVC / PE                                                  |
| Connection in acc. with standard        | IEC 60947-7-1                                             |
| Conductor cross section rigid           | 0.25 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>              |
| Cross section AWG                       | 24 ... 16 (converted acc. to IEC)                         |
| Conductor cross section flexible        | 0.25 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>              |
| Conductor cross section, flexible [AWG] | 24 ... 16 (converted acc. to IEC)                         |
| Cross section, sensor conductors        | 0.25 mm <sup>2</sup> ... 0.34 mm <sup>2</sup>             |
| Nominal current                         | 17.5 A                                                    |
| Maximum load current                    | 17.5 A (with 1.5 mm <sup>2</sup> conductor cross section) |
| Nominal voltage                         | 800 V                                                     |
| Nominal cross section                   | 1.5 mm <sup>2</sup>                                       |

#### Level 1 below 1

|                                                                   |                                              |
|-------------------------------------------------------------------|----------------------------------------------|
| Internal cylindrical gage                                         | A3                                           |
| Connection in acc. with standard                                  | IEC 60947-7-1                                |
| Conductor cross section rigid                                     | 0.08 mm <sup>2</sup> ... 4 mm <sup>2</sup>   |
| Cross section AWG                                                 | 28 ... 12 (converted acc. to IEC)            |
| Conductor cross section flexible                                  | 0.08 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> |
| Conductor cross-section flexible (ferrule without plastic sleeve) | 0.14 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> |

# QTCS 1,5 BU - Feed-through terminal block



3050141

<https://www.phoenixcontact.com/us/products/3050141>

|                                                                                           |                                                           |
|-------------------------------------------------------------------------------------------|-----------------------------------------------------------|
| Flexible conductor cross section (ferrule with plastic sleeve)                            | 0.14 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>              |
| 2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve | 0.5 mm <sup>2</sup>                                       |
| Nominal current                                                                           | 17.5 A                                                    |
| Maximum load current                                                                      | 17.5 A (with 1.5 mm <sup>2</sup> conductor cross section) |
| Nominal voltage                                                                           | 800 V                                                     |
| Nominal cross section                                                                     | 1.5 mm <sup>2</sup>                                       |

## Ex data

### Rated data (ATEX/IECEx)

|                                                    |                                      |
|----------------------------------------------------|--------------------------------------|
| Identification                                     | Ⓔ II 2 GD Ex eb IIC Gb               |
| Operating temperature range                        | -45 °C ... 90 °C                     |
| Ex-certified accessories                           | 3206270 D-QTCS 1,5                   |
|                                                    | 3206209 ATP-QTC                      |
|                                                    | 1204517 SZF 1-0,6X3,5                |
|                                                    | 3022276 CLIPFIX 35-5                 |
|                                                    | 3022218 CLIPFIX 35                   |
| List of bridges                                    | Plug-in bridge / FBS 2-5 / 3030161   |
|                                                    | Plug-in bridge / FBS 3-5 / 3030174   |
|                                                    | Plug-in bridge / FBS 4-5 / 3030187   |
|                                                    | Plug-in bridge / FBS 5-5 / 3030190   |
|                                                    | Plug-in bridge / FBS 10-5 / 3030213  |
|                                                    | Plug-in bridge / FBS 20-5 / 3030226  |
| Ex temperature increase                            | 40 K (17.6 A / 1.5 mm <sup>2</sup> ) |
| Rated voltage                                      | 550 V                                |
| for bridging with bridge                           | 550 V                                |
| - At bridging between non-adjacent terminal blocks | 275 V                                |
| - At cut-to-length bridging with cover             | 220 V                                |
| - At cut-to-length bridging with partition plate   | 275 V                                |
| Rated insulation voltage                           | 500 V                                |
| output                                             | (Permanent)                          |

### Ex level General

|                      |         |
|----------------------|---------|
| Rated current        | 16 A    |
| Maximum load current | 16 A    |
| Contact resistance   | 1.25 mΩ |

### Ex connection data Fast connection

|                                                      |                                              |
|------------------------------------------------------|----------------------------------------------|
| Nominal cross section                                | 1.5 mm <sup>2</sup>                          |
| Rated cross section AWG                              | 16                                           |
| Connection capacity rigid                            | 0.25 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> |
| Connection capacity AWG                              | 24 ... 16                                    |
| Connection capacity flexible                         | 0.25 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> |
| Connection capacity AWG                              | 24 ... 16                                    |
| Frequency of connections with the same cross section | 100                                          |

# QTCS 1,5 BU - Feed-through terminal block



3050141

<https://www.phoenixcontact.com/us/products/3050141>

## Ex connection data Spring-cage connection

|                              |                                              |
|------------------------------|----------------------------------------------|
| Stripping length             | 10 mm                                        |
| Nominal cross section        | 1.5 mm <sup>2</sup>                          |
| Rated cross section AWG      | 16                                           |
| Connection capacity rigid    | 0.08 mm <sup>2</sup> ... 4 mm <sup>2</sup>   |
| Connection capacity AWG      | 28 ... 12                                    |
| Connection capacity flexible | 0.08 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> |
| Connection capacity AWG      | 28 ... 14                                    |

## Dimensions

|                 |        |
|-----------------|--------|
| Width           | 5.2 mm |
| End cover width | 2.2 mm |

## Material specifications

|                                                                         |                 |
|-------------------------------------------------------------------------|-----------------|
| Color                                                                   | blue (RAL 5015) |
| Flammability rating according to UL 94                                  | V0              |
| Insulating material group                                               | I               |
| Insulating material                                                     | PA              |
| Static insulating material application in cold                          | -60 °C          |
| Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) | 130 °C          |
| Relative insulation material temperature index (Elec., UL 746 B)        | 130 °C          |
| Fire protection for rail vehicles (DIN EN 45545-2) R22                  | HL 1 - HL 3     |
| Fire protection for rail vehicles (DIN EN 45545-2) R23                  | HL 1 - HL 3     |
| Fire protection for rail vehicles (DIN EN 45545-2) R24                  | HL 1 - HL 3     |
| Fire protection for rail vehicles (DIN EN 45545-2) R26                  | HL 1 - HL 3     |
| Calorimetric heat release NFPA 130 (ASTM E 1354)                        | 28 MJ/kg        |
| Surface flammability NFPA 130 (ASTM E 162)                              | passed          |
| Specific optical density of smoke NFPA 130 (ASTM E 662)                 | passed          |

## Cable/line

|                                |      |
|--------------------------------|------|
| Wire diameter incl. insulation | 3 mm |
|--------------------------------|------|

## Electrical tests

### Surge voltage test

|                       |             |
|-----------------------|-------------|
| Test voltage setpoint | 9.8 kV      |
| Result                | Test passed |

### Temperature-rise test

|                                                  |                                |
|--------------------------------------------------|--------------------------------|
| Requirement temperature-rise test                | Increase in temperature ≤ 45 K |
| Result                                           | Test passed                    |
|                                                  | Test passed                    |
| Short-time withstand current 1.5 mm <sup>2</sup> | 0.18 kA                        |
| Result                                           | Test passed                    |

# QTCS 1,5 BU - Feed-through terminal block



3050141

<https://www.phoenixcontact.com/us/products/3050141>

## Power-frequency withstand voltage

|                       |             |
|-----------------------|-------------|
| Test voltage setpoint | 0.002 kV    |
| Result                | Test passed |

## Mechanical properties

### Mechanical data

|                 |     |
|-----------------|-----|
| Open side panel | Yes |
|-----------------|-----|

## Mechanical tests

### Mechanical strength

|        |             |
|--------|-------------|
| Result | Test passed |
|--------|-------------|

### Attachment on the carrier

|                         |             |
|-------------------------|-------------|
| DIN rail/fixing support | NS 35       |
| Test force setpoint     | 1 N         |
| Result                  | Test passed |

### Test for conductor damage and slackening

|                                |                               |
|--------------------------------|-------------------------------|
| Rotation speed                 | 10 (+/- 2) rpm                |
| Revolutions                    | 135                           |
| Conductor cross section/weight | 0.14 mm <sup>2</sup> / 0.2 kg |
|                                | 1.5 mm <sup>2</sup> / 0.4 kg  |
|                                | 4 mm <sup>2</sup> / 0.9 kg    |
| Result                         | Test passed                   |

## Environmental and real-life conditions

### Aging

|                    |             |
|--------------------|-------------|
| Temperature cycles | 192         |
| Result             | Test passed |

### Needle-flame test

|                  |      |
|------------------|------|
| Time of exposure | 30 s |
|------------------|------|

### Oscillation/broadband noise

|                        |                                                |
|------------------------|------------------------------------------------|
| Specification          | DIN EN 50155 (VDE 0115-200):2018-05            |
| Spectrum               | Service life test category 2, bogie-mounted    |
| Frequency              | $f_1 = 5 \text{ Hz}$ to $f_2 = 250 \text{ Hz}$ |
| ASD level              | 6.12 (m/s <sup>2</sup> ) <sup>2</sup> /Hz      |
| Acceleration           | 3.12g                                          |
| Test duration per axis | 5 h                                            |
| Test directions        | X-, Y- and Z-axis                              |

### Shocks

|              |           |
|--------------|-----------|
| Pulse shape  | Half-sine |
| Acceleration | 30g       |

# QTCS 1,5 BU - Feed-through terminal block



3050141

<https://www.phoenixcontact.com/us/products/3050141>

|                                |                                   |
|--------------------------------|-----------------------------------|
| Shock duration                 | 18 ms                             |
| Number of shocks per direction | 3                                 |
| Test directions                | X-, Y- and Z-axis (pos. and neg.) |

## Ambient conditions

|                                          |                                                                           |
|------------------------------------------|---------------------------------------------------------------------------|
| Ambient temperature (operation)          | -60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)       |
| Ambient temperature (storage/transport)  | -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C) |
| Ambient temperature (assembly)           | -5 °C ... 70 °C                                                           |
| Ambient temperature (actuation)          | -5 °C ... 70 °C                                                           |
| Permissible humidity (storage/transport) | 30 % ... 70 %                                                             |

## Standards and regulations

|                                  |               |
|----------------------------------|---------------|
| Connection in acc. with standard | IEC 60947-7-1 |
|                                  | IEC 60947-7-1 |

## Mounting

|               |           |
|---------------|-----------|
| Mounting type | NS 35/7,5 |
|               | NS 35/15  |

# QTCS 1,5 BU - Feed-through terminal block

3050141

<https://www.phoenixcontact.com/us/products/3050141>



## Drawings

Circuit diagram



# QTCS 1,5 BU - Feed-through terminal block



3050141

<https://www.phoenixcontact.com/us/products/3050141>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27141120 |
|-------------|----------|

### ETIM

|          |          |
|----------|----------|
| ETIM 8.0 | EC000897 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|



# QTCS 1,5 BU - Feed-through terminal block



3050141

<https://www.phoenixcontact.com/us/products/3050141>

## Environmental product compliance

|                                         |                                          |
|-----------------------------------------|------------------------------------------|
| EU RoHS                                 |                                          |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |
| China RoHS                              |                                          |
| Environment friendly use period (EFUP)  | EFUP-E                                   |
|                                         | No hazardous substances above the limits |
| EU REACH SVHC                           |                                          |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)