


RBO 5-F/4 - Bolt connection terminal block



3058237
<https://www.phoenixcontact.com/pc/products/3058237>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Feed-through terminal block with bolt connection method, cross section: 0.1 - 6 mm², AWG: 26 - 10, width 13 mm, color: gray

Your advantages

- Direct mounting in control boxes
- Compact connection with ring and fork-type cable lugs
- Bridge shaft for potential distribution using standard screw bridges
- Isolator bridge bar for switchable cross connections

Commercial data

Item number	3058237
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	BE4415
Catalog page	Page 387 (C-1-2019)
GTIN	4046356534765
Weight per piece (including packing)	117.1 g
Weight per piece (excluding packing)	117 g
Customs tariff number	85369010
Country of origin	IN

RBO 5-F/4 - Bolt connection terminal block



3058237

<https://www.phoenixcontact.com/pc/products/3058237>

Technical data

Product properties

Product type	Bolt connection terminal block
Pitch	13 mm
Number of connections	8
Number of rows	1
Potentials	4

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Electrical properties

Rated surge voltage	8 kV
Maximum power dissipation for nominal condition	1.82 W

Connection data

Number of connections per level	8
Nominal cross section	10 mm ²

1 level

Stripping length	The stripping length depends on the specification provided by the cable lug manufacturer.
Connection in acc. with standard	IEC 60947-7-1
Nominal current	57 A
Maximum load current	57 A (with 10 mm ² conductor cross section)
Nominal voltage	800 V
Nominal cross section	10 mm ²

Cable lug connection DIN 46234:1980-03

Connection in acc. with standard	DIN 46234:1980-03
Cross section	0.1 mm ² ... 10 mm ²
Cross section range AWG	26 ... 8 (converted acc. to IEC)
Hole diameter	5.3 mm
Width	10 mm
Bolt diameter	5 mm
Screw thread	M5
Tightening torque	2 ... 2.2 Nm
Connection in acc. with standard	DIN 46237:1970-07
Cross section	0.5 mm ² ... 6 mm ²
Cross section range AWG	20 ... 10 (converted acc. to IEC)
Hole diameter	5.3 mm
Width	10 mm
Bolt diameter	5 mm

RBO 5-F/4 - Bolt connection terminal block



3058237

<https://www.phoenixcontact.com/pc/products/3058237>

Tightening torque	2 ... 2.2 Nm
Identification color of ring cable lugs : red	1 mm ²
Identification color of ring cable lugs : blue	2.5 mm ²
Identification color of ring cable lugs : yellow	6 mm ²

Dimensions

Width	69.7 mm
Height	53.3 mm
Depth	37 mm
Hole diameter	5.2 mm
Pitch	13 mm

Material specifications

Color	gray
Flammability rating according to UL 94	V0
Insulating material group	I
Insulating material	PA
Static insulating material application in cold	-60 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	130 °C
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3
Calorimetric heat release NFPA 130 (ASTM E 1354)	28 MJ/kg
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed

Mechanical properties

Mechanical data

Open side panel	No
-----------------	----

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C ()
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (operation)	20 % ... 90 %
Permissible humidity (storage/transport)	30 % ... 70 %

RBO 5-F/4 - Bolt connection terminal block



3058237

<https://www.phoenixcontact.com/pc/products/3058237>

Standards and regulations

Connection in acc. with standard	IEC 60947-7-1
----------------------------------	---------------

Mounting

Mounting type	direct screw connection
---------------	-------------------------

RBO 5-F/4 - Bolt connection terminal block




3058237

<https://www.phoenixcontact.com/pc/products/3058237>

Drawings

Circuit diagram



RBO 5-F/4 - Bolt connection terminal block



3058237

<https://www.phoenixcontact.com/pc/products/3058237>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/3058237>

 cUL Recognized Approval ID: FILE E 60425				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
Use group B				
	600 V	45 A	-	-
Use group C				
	600 V	45 A	-	-

 UL Recognized Approval ID: FILE E 60425				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
Use group B				
	600 V	45 A	-	-
Use group C				
	600 V	45 A	-	-

 EAC Approval ID: RU C-DE.BL08.B.00540				
---	--	--	--	--

cULus Recognized				
-------------------------	--	--	--	--

RBO 5-F/4 - Bolt connection terminal block



3058237

<https://www.phoenixcontact.com/pc/products/3058237>

Classifications

ECLASS

ECLASS-11.0	27141120
ECLASS-13.0	27250101

ETIM

ETIM 9.0	EC000897
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

RBO 5-F/4 - Bolt connection terminal block



3058237

<https://www.phoenixcontact.com/pc/products/3058237>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

RBO 5-F/4 - Bolt connection terminal block



3058237

<https://www.phoenixcontact.com/pc/products/3058237>

Accessories

i Note: Applying some accessories below might limit this product.

FB 10-13 - Fixed bridge

3059126

<https://www.phoenixcontact.com/pc/products/3059126>



Fixed bridge, pitch: 13 mm, number of positions: 10, color: silver

i Max. current carrying capacity: 57 A

with 41 A bridging between non-adjacent term. blocks

FB 10-13 ISO - Fixed bridge

3059663

<https://www.phoenixcontact.com/pc/products/3059663>



Fixed bridge, pitch: 13 mm, number of positions: 10, color: silver

i Max. current carrying capacity: 24 A

RBO 5-F/4 - Bolt connection terminal block



3058237

<https://www.phoenixcontact.com/pc/products/3058237>

TS-KK 3 - Separating plate

2770215

<https://www.phoenixcontact.com/pc/products/2770215>



Separating plate, depth: 16 mm, width: 0.5 mm, height: 14 mm, color: gray

AP RSC - Cover profile

3058017

<https://www.phoenixcontact.com/pc/products/3058017>



Cover profile, for covering terminal strips, directly snapped onto RBO... and RSC... terminal blocks. Length supplied: 1 m

RBO 5-F/4 - Bolt connection terminal block



3058237

<https://www.phoenixcontact.com/pc/products/3058237>

ZB 13:UNBEDRUCKT - Zack marker strip

0829131

<https://www.phoenixcontact.com/pc/products/0829131>



Zack marker strip, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 13 mm, lettering field size: 13 x 10.5 mm, Number of individual labels: 5

ZB 13 CUS - Zack marker strip

0829132

<https://www.phoenixcontact.com/pc/products/0829132>



Zack marker strip, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 13 mm, lettering field size: 13 x 10.5 mm, Number of individual labels: 5

RBO 5-F/4 - Bolt connection terminal block

3058237

<https://www.phoenixcontact.com/pc/products/3058237>



ZBF 13:UNBEDRUCKT - Zack Marker strip, flat

0829133

<https://www.phoenixcontact.com/pc/products/0829133>



Zack Marker strip, flat, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 13 mm, lettering field size: 13 x 5.2 mm, Number of individual labels: 5

ZBF 13 CUS - Zack Marker strip, flat

0829134

<https://www.phoenixcontact.com/pc/products/0829134>



Zack Marker strip, flat, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 13 mm, lettering field size: 13 x 5.2 mm, Number of individual labels: 5

RBO 5-F/4 - Bolt connection terminal block

3058237

<https://www.phoenixcontact.com/pc/products/3058237>



SHN 8 - Tool

1209868

<https://www.phoenixcontact.com/pc/products/1209868>

Socket wrench, wrench size 8 mm




CARRIER F-13 KIT - Short circuit kit for current transformers

3215070

<https://www.phoenixcontact.com/pc/products/3215070>

Short-circuit kit for current transformer. Use with panel mounted RBO/RSC 5 feed-through terminals



Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com