

# UP 4/ 3 - Plug

3060131

<https://www.phoenixcontact.com/pc/products/3060131>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Plug, nom. voltage: 800 V, nominal current: 32 A, number of positions: 3, connection method: Screw connection, Rated cross section: 4 mm<sup>2</sup>, cross section: 0.2 mm<sup>2</sup>- 6 mm<sup>2</sup>, color: gray

## Your advantages

- Screw actuation from the side
- Conductor connection from above
- The plug design enables space-saving potential distribution by using four-conductor terminal blocks with two slots

## Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 3060131             |
| Packing unit                         | 50 pc               |
| Minimum order quantity               | 1 pc                |
| Product key                          | BE1144              |
| Catalog page                         | Page 336 (C-1-2019) |
| GTIN                                 | 4046356090308       |
| Weight per piece (including packing) | 14.489 g            |
| Weight per piece (excluding packing) | 13.78 g             |
| Customs tariff number                | 85366990            |
| Country of origin                    | TR                  |

# UP 4/ 3 - Plug

3060131

<https://www.phoenixcontact.com/pc/products/3060131>



## Technical data

### Product properties

|                     |               |
|---------------------|---------------|
| Product type        | Terminal plug |
| Number of positions | 3             |
| Pitch               | 6.2 mm        |
| Potentials          | 1             |

### Insulation characteristics

|                      |     |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution  | 3   |

### Electrical properties

|                     |      |
|---------------------|------|
| Rated surge voltage | 8 kV |
|---------------------|------|

### Connection data

|                                                                                           |                                                       |
|-------------------------------------------------------------------------------------------|-------------------------------------------------------|
| Nominal cross section                                                                     | 4 mm <sup>2</sup>                                     |
| Screw thread                                                                              | M3                                                    |
| Tightening torque                                                                         | 0.6 ... 0.8 Nm                                        |
| Stripping length                                                                          | 9 mm                                                  |
| Internal cylindrical gage                                                                 | A4                                                    |
| Connection in acc. with standard                                                          | IEC 61984                                             |
| Conductor cross section rigid                                                             | 0.2 mm <sup>2</sup> ... 6 mm <sup>2</sup>             |
| Cross section AWG                                                                         | 24 ... 10 (converted acc. to IEC)                     |
| Conductor cross section flexible                                                          | 0.2 mm <sup>2</sup> ... 6 mm <sup>2</sup>             |
| Conductor cross section, flexible [AWG]                                                   | 24 ... 10 (converted acc. to IEC)                     |
| Conductor cross-section flexible (ferrule without plastic sleeve)                         | 0.25 mm <sup>2</sup> ... 4 mm <sup>2</sup>            |
| Flexible conductor cross section (ferrule with plastic sleeve)                            | 0.25 mm <sup>2</sup> ... 4 mm <sup>2</sup>            |
| 2 conductors with same cross section, solid                                               | 0.2 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>           |
| 2 conductors with same cross section, flexible                                            | 0.2 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>           |
| 2 conductors with same cross section, flexible, with ferrule without plastic sleeve       | 0.25 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>          |
| 2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve | 0.5 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>           |
| Nominal current                                                                           | 32 A                                                  |
| Maximum load current                                                                      | 32 A (with 6 mm <sup>2</sup> conductor cross section) |
| Nominal voltage                                                                           | 800 V                                                 |
| Nominal cross section                                                                     | 4 mm <sup>2</sup>                                     |

### Dimensions

|        |         |
|--------|---------|
| Width  | 18.6 mm |
| Height | 21 mm   |
| Depth  | 41.2 mm |
| Length | 21 mm   |
| Pitch  | 6.2 mm  |

# UP 4/ 3 - Plug



3060131

<https://www.phoenixcontact.com/pc/products/3060131>

## Material specifications

|                                                                         |             |
|-------------------------------------------------------------------------|-------------|
| Color                                                                   | gray        |
| Flammability rating according to UL 94                                  | V0          |
| Insulating material group                                               | I           |
| Insulating material                                                     | PA          |
| Static insulating material application in cold                          | -60 °C      |
| Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) | 125 °C      |
| Relative insulation material temperature index (Elec., UL 746 B)        | 130 °C      |
| Fire protection for rail vehicles (DIN EN 45545-2) R22                  | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R23                  | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R24                  | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R26                  | HL 1 - HL 3 |
| Calorimetric heat release NFPA 130 (ASTM E 1354)                        | 27,5 MJ/kg  |
| Surface flammability NFPA 130 (ASTM E 162)                              | passed      |
| Specific optical density of smoke NFPA 130 (ASTM E 662)                 | passed      |
| Smoke gas toxicity NFPA 130 (SMP 800C)                                  | passed      |

## Environmental and real-life conditions

### Ambient conditions

|                                          |                                                                          |
|------------------------------------------|--------------------------------------------------------------------------|
| Ambient temperature (operation)          | -60 °C (max. operating temperature see derating curve)                   |
| Ambient temperature (storage/transport)  | -25 °C ... 60 °C (for a short time, no longer than 24 h, -60°C to +70°C) |
| Ambient temperature (assembly)           | -5 °C ... 70 °C                                                          |
| Ambient temperature (actuation)          | -5 °C ... 70 °C                                                          |
| Permissible humidity (operation)         | 20 % ... 90 %                                                            |
| Permissible humidity (storage/transport) | 30 % ... 70 %                                                            |

## Standards and regulations


|                                  |           |
|----------------------------------|-----------|
| Connection in acc. with standard | IEC 61984 |
|----------------------------------|-----------|

## Drawings

Circuit diagram



Diagram



# UP 4/ 3 - Plug

3060131

<https://www.phoenixcontact.com/pc/products/3060131>



## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/3060131>

| CSA<br>Approval ID: 13631 |                       |                       |                   |                             |
|---------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|                           | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
| Use group B               | 600 V                 | 30 A                  | 26 - 10           | -                           |
| Use group C               | 600 V                 | 30 A                  | 26 - 10           | -                           |

| CB<br>IECEE CB Scheme<br>Approval ID: NL-34722_A1 |                       |                       |                   |                             |
|---------------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|                                                   | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|                                                   | 800 V                 | 32 A                  | -                 | -                           |

| EAC<br>Approval ID: RU C-DE.BL08.B.00511 |  |  |  |  |
|------------------------------------------|--|--|--|--|
|------------------------------------------|--|--|--|--|

| cULus<br>cULus Recognized<br>Approval ID: E60425 |                       |                       |                   |                             |
|--------------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|                                                  | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
| Use group B                                      | 600 V                 | 30 A                  | 26 - 10           | -                           |
| Multi-conductor connection                       | 600 V                 | 30 A                  | 26 - 14           | -                           |
| Use group C                                      | 600 V                 | 30 A                  | 26 - 10           | -                           |
| Multi-conductor connection                       | 600 V                 | 30 A                  | 26 - 14           | -                           |

| KEMA-KEUR<br>Approval ID: 71-114072 REV.1 |                       |                       |                   |                             |
|-------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|                                           | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|                                           | 800 V                 | 32 A                  | -                 | -                           |

# UP 4/ 3 - Plug

3060131

<https://www.phoenixcontact.com/pc/products/3060131>



## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27141151 |
| ECLASS-12.0 | 27141151 |
| ECLASS-13.0 | 27250306 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC002021 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# UP 4/ 3 - Plug

3060131

<https://www.phoenixcontact.com/pc/products/3060131>



## Environmental product compliance

|            |                                                         |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstraße 8  
D-32825 Blomberg  
+49 (0) 5235-3 00  
[info@phoenixcontact.com](mailto:info@phoenixcontact.com)