

STTB 2,5/2P-FS - Latching flange

3061428

<https://www.phoenixcontact.com/tw/products/3061428>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Latching flange, mounting type: NS 35/7,5, NS 35/15, color: gray



Product description

Flange for snapping onto COMBI connectors

Your advantages

- Same shape and pitch as the basic terminal blocks
- Automatic latching in self-locking flange

Commercial data

Item number	3061428
Packing unit	50 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Product key	BE214Z
Catalog page	Page 371 (C-1-2019)
GTIN	4046356555067
Weight per piece (including packing)	6.032 g
Weight per piece (excluding packing)	5.83 g
Customs tariff number	39269097
Country of origin	PL

STTB 2,5/2P-FS - Latching flange



3061428

<https://www.phoenixcontact.com/tw/products/3061428>

Technical data

Product properties

Product type	Flange
Number of rows	2

Dimensions

Width	5.2 mm
End cover width	2.2 mm
Height	71.5 mm
Depth	40 mm
Depth on NS 35/7,5	47.5 mm
Depth on NS 35/15	55 mm

Material specifications

Color	gray
Flammability rating according to UL 94	V0
Insulating material	PA
Static insulating material application in cold	-60 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	130 °C
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3
Calorimetric heat release NFPA 130 (ASTM E 1354)	28 MJ/kg
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed

Environmental and real-life conditions

Ambient conditions

Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (storage/transport)	30 % ... 70 %

Mounting

Mounting type	NS 35/7,5
	NS 35/15

STTB 2,5/2P-FS - Latching flange

3061428

<https://www.phoenixcontact.com/tw/products/3061428>



Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/tw/products/3061428>



EAC

Approval ID: RU C-DE.A*30.B.01742

STTB 2,5/2P-FS - Latching flange



3061428

<https://www.phoenixcontact.com/tw/products/3061428>

Classifications

ECLASS

ECLASS-11.0	27141190
ECLASS-12.0	27141190
ECLASS-13.0	27250302

ETIM

ETIM 9.0	EC002848
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

STTB 2,5/2P-FS - Latching flange



3061428

<https://www.phoenixcontact.com/tw/products/3061428>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

菲尼克斯有限公司
11560 台北市南港區三重路 66 號 3 樓 B 室 (南港軟體園區)

02 2785 2155
taiwan@phoenixcontact.com.tw