


3070310

<https://www.phoenixcontact.com/pc/products/3070310>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Test disconnect terminal block, nom. voltage: 500 V, nominal current: 41 A, connection method: Screw connection with spring support, 1 level, Rated cross section: 6 mm², cross section: 0.2 mm² - 10 mm², mounting type: NS 35/7,5, NS 35/15, NS 32, color: gray

Commercial data

Item number	3070310
Packing unit	50 pc
Minimum order quantity	1 pc
Product key	BE1233
Catalog page	Page 550 (C-1-2019)
GTIN	4046356661959
Weight per piece (including packing)	26.609 g
Weight per piece (excluding packing)	26.609 g
Customs tariff number	85369010
Country of origin	PL

USST 6-T/SB - Test disconnect terminal block



3070310

<https://www.phoenixcontact.com/pc/products/3070310>

Technical data

Product properties

Product type	Test disconnect terminal block
Number of connections	2
Number of rows	1
Potentials	1

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Electrical properties

Rated surge voltage	6 kV
Maximum power dissipation for nominal condition	1.31 W

Connection data

Number of connections per level	2
Nominal cross section	6 mm ²
Test socket torque	0.6

1 level

Screw thread	M4
Tightening torque	1.5 ... 1.8 Nm
Stripping length	12 mm
Internal cylindrical gage	A5
Connection in acc. with standard	IEC 60947-7-1
Conductor cross section rigid	0.2 mm ² ... 10 mm ²
Cross section AWG	24 ... 8 (converted acc. to IEC)
Conductor cross section flexible	0.2 mm ² ... 6 mm ²
Conductor cross section, flexible [AWG]	24 ... 10 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve)	0.25 mm ² ... 6 mm ²
Flexible conductor cross section (ferrule with plastic sleeve)	0.25 mm ² ... 6 mm ²
2 conductors with same cross section, solid	0.2 mm ² ... 2.5 mm ²
2 conductors with same cross section, flexible	0.2 mm ² ... 2.5 mm ²
2 conductors with same cross section, flexible, with ferrule without plastic sleeve	0.25 mm ² ... 1.5 mm ²
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve	0.5 mm ² ... 4 mm ²
Nominal current	41 A
Maximum load current	57 A (with 10 mm ² conductor cross section)
Nominal voltage	500 V (up to 690 V for pollution degree II)
Nominal cross section	6 mm ²

Dimensions

USST 6-T/SB - Test disconnect terminal block



3070310

<https://www.phoenixcontact.com/pc/products/3070310>

Width	8.2 mm
End cover width	2.2 mm
Height	82 mm
Depth on NS 32	57 mm
Depth on NS 35/7,5	52 mm
Depth on NS 35/15	59.5 mm

Material specifications

Color	gray
Flammability rating according to UL 94	V0
Insulating material group	I
Insulating material	PA
Static insulating material application in cold	-60 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	130 °C
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3
Calorimetric heat release NFPA 130 (ASTM E 1354)	28 MJ/kg
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed

Electrical tests

Surge voltage test

Test voltage setpoint	7.3 kV
Result	Test passed

Temperature-rise test

Requirement temperature-rise test	Increase in temperature ≤ 45 K
Result	Test passed
Short-time withstand current 6 mm ²	0.72 kA
Short-time withstand current 10 mm ²	1.2 kA
Result	Test passed

Power-frequency withstand voltage

Test voltage setpoint	1.89 kV
Result	Test passed

Mechanical properties

Mechanical data

Open side panel	Yes
-----------------	-----

USST 6-T/SB - Test disconnect terminal block



3070310

<https://www.phoenixcontact.com/pc/products/3070310>

Mechanical tests

Mechanical strength

Result	Test passed
--------	-------------

Attachment on the carrier

DIN rail/fixing support	NS 32/NS 35
Test force setpoint	5 N
Result	Test passed

Test for conductor damage and slackening

Rotation speed	10 rpm
Revolutions	135
Conductor cross section/weight	0.2 mm ² / 0.2 kg
	6 mm ² / 1.4 kg
	10 mm ² / 2 kg
Result	Test passed

Test for conductor damage and slackening

Rotation speed	10 rpm
Revolutions	135
Conductor cross section/weight	2.5 mm ² / 0.7 kg
Result	Test passed

Environmental and real-life conditions

Needle-flame test

Time of exposure	30 s
Result	Test passed

Oscillation/broadband noise

Specification	DIN EN 50155 (VDE 0115-200):2008-03
Spectrum	Service life test category 1, class B, body mounted
Frequency	$f_1 = 5 \text{ Hz}$ to $f_2 = 150 \text{ Hz}$
ASD level	1.857 (m/s ²) ² /Hz
Acceleration	0.8g
Test duration per axis	5 h
Test directions	X-, Y- and Z-axis
Result	Test passed

Shocks

Specification	DIN EN 50155 (VDE 0115-200):2008-03
Pulse shape	Half-sine
Acceleration	5g
Shock duration	30 ms
Number of shocks per direction	3

USST 6-T/SB - Test disconnect terminal block



3070310

<https://www.phoenixcontact.com/pc/products/3070310>

Test directions	X-, Y- and Z-axis (pos. and neg.)
Result	Test passed

Ambient conditions

Ambient temperature (operation)	-60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (operation)	20 % ... 90 %
Permissible humidity (storage/transport)	30 % ... 70 %

Standards and regulations

Connection in acc. with standard	IEC 60947-7-1
----------------------------------	---------------

Mounting

Mounting type	NS 35/7,5
	NS 35/15
	NS 32
Screw thread	M3

USST 6-T/SB - Test disconnect terminal block



3070310

<https://www.phoenixcontact.com/pc/products/3070310>

Drawings

Circuit diagram



Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/3070310>



EAC

Approval ID: RU C-DE.BL08.B.00534

	cULus Recognized Approval ID: E60425			
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
Use group B				
	300 V	30 A	24 - 10	-
Use group C				
	300 V	30 A	24 - 10	-
Use group D				
	600 V	5 A	24 - 10	-

USST 6-T/SB - Test disconnect terminal block



3070310

<https://www.phoenixcontact.com/pc/products/3070310>

Classifications

ECLASS

ECLASS-11.0	27141126
ECLASS-12.0	27141126
ECLASS-13.0	27250109

ETIM

ETIM 9.0	EC000902
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

USST 6-T/SB - Test disconnect terminal block



3070310

<https://www.phoenixcontact.com/pc/products/3070310>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

USST 6-T/SB - Test disconnect terminal block



3070310

<https://www.phoenixcontact.com/pc/products/3070310>

Accessories

i Note: Applying some accessories below might limit this product.

SCBI 10-8,15 - Screw bridge

3245134

<https://www.phoenixcontact.com/pc/products/3245134>



Screw bridge, with insulating collar, pitch: 8.2 mm, number of positions: 10, color: silver

i Max. current carrying capacity: 30 A

SCBI 10-8,15 ISO - Isolator bridge bar

3000417

<https://www.phoenixcontact.com/pc/products/3000417>



Isolator bridge bar, for switchable cross bridges, with insulating collar, pitch: 8.2 mm, number of positions: 10, color: silver

i Max. current carrying capacity: 24 A

USST 6-T/SB - Test disconnect terminal block



3070310

<https://www.phoenixcontact.com/pc/products/3070310>

SB 6-T 2-8 - Switching jumper

3075842

<https://www.phoenixcontact.com/pc/products/3075842>



Switching jumper, pitch: 8 mm, number of positions: 2, color: orange

 Max. current carrying capacity: 32 A

SB 6-T 3-8 - Switching jumper

3075843

<https://www.phoenixcontact.com/pc/products/3075843>



Switching jumper, pitch: 8 mm, number of positions: 3, color: orange

 Max. current carrying capacity: 32 A

USST 6-T/SB - Test disconnect terminal block



3070310

<https://www.phoenixcontact.com/pc/products/3070310>

SB 6-T 4-8 - Switching jumper

3075844

<https://www.phoenixcontact.com/pc/products/3075844>



Switching jumper, pitch: 8 mm, number of positions: 4, color: orange

 Max. current carrying capacity: 32 A

SB 6-T 10-8 - Switching jumper

3075846

<https://www.phoenixcontact.com/pc/products/3075846>



Switching jumper, pitch: 8 mm, number of positions: 10, color: orange

 Max. current carrying capacity: 32 A

USST 6-T/SB - Test disconnect terminal block



3070310

<https://www.phoenixcontact.com/pc/products/3070310>

SB 1/3/5/7-8-T - Switching jumper

3075845

<https://www.phoenixcontact.com/pc/products/3075845>



Switching jumper, number of positions: 7, pin assignment: 1, 3, 5, 7, color: orange

 Max. current carrying capacity: 32 A

SBP 6-T 2-8 - Switching jumper

3070321

<https://www.phoenixcontact.com/pc/products/3070321>



Switching jumper, with test socket, pitch: 8.2 mm, number of positions: 2, color: orange

 Max. current carrying capacity: 20 A

USST 6-T/SB - Test disconnect terminal block



3070310

<https://www.phoenixcontact.com/pc/products/3070310>

SBP 6-T 3-8 - Switching jumper

3070322

<https://www.phoenixcontact.com/pc/products/3070322>



Switching jumper, with test socket, pitch: 8.2 mm, number of positions: 3, color: orange

 Max. current carrying capacity: 20 A

SBP 6-T 4-8 - Switching jumper

3070323

<https://www.phoenixcontact.com/pc/products/3070323>



Switching jumper, with test socket, pitch: 8.2 mm, number of positions: 4, color: orange

 Max. current carrying capacity: 20 A

USST 6-T/SB - Test disconnect terminal block



3070310

<https://www.phoenixcontact.com/pc/products/3070310>

D-USST 6-T - End cover

3070367

<https://www.phoenixcontact.com/pc/products/3070367>

End cover, depth: 41.7 mm, width: 2.2 mm, height: 82 mm, color: gray



D-USST 6-T CS - End cover

3070369

<https://www.phoenixcontact.com/pc/products/3070369>

End cover, with lateral openings for cable lugs, can also be used as partition plate, depth: 41.7 mm, width: 2.2 mm, height: 82 mm, color: gray



USST 6-T/SB - Test disconnect terminal block

3070310

<https://www.phoenixcontact.com/pc/products/3070310>



ATP-URTK/SP - Partition plate

0311139

<https://www.phoenixcontact.com/pc/products/0311139>

Partition plate, depth: 64 mm, width: 2 mm, height: 99 mm, color: gray



TPS 3/20/5 - Test plug strip

3246586

<https://www.phoenixcontact.com/pc/products/3246586>

Test plug strip, for 4 mm test plugs, for screwing into the bridge shaft, number of positions: 1, color: silver



USST 6-T/SB - Test disconnect terminal block



3070310

<https://www.phoenixcontact.com/pc/products/3070310>

SL-SB - Switching lock

3035761

<https://www.phoenixcontact.com/pc/products/3035761>



Switching lock, for additional locking of short-circuit switching elements in current transformer measuring circuits, depth: 13.6 mm, width: 12.5 mm, height: 16.3 mm, color: white

SCP 2-8 - Short-circuit connector

3070402

<https://www.phoenixcontact.com/pc/products/3070402>



Short-circuit connector, pitch: 8.15 mm, number of positions: 2, color: orange

USST 6-T/SB - Test disconnect terminal block



3070310

<https://www.phoenixcontact.com/pc/products/3070310>

SCP 3-8 - Short-circuit connector

3070403

<https://www.phoenixcontact.com/pc/products/3070403>

Short-circuit connector, pitch: 8.15 mm, number of positions: 3, color: orange



SCP 4-8 - Short-circuit connector

3070404

<https://www.phoenixcontact.com/pc/products/3070404>

Short-circuit connector, pitch: 8.15 mm, number of positions: 4, color: orange



USST 6-T/SB - Test disconnect terminal block



3070310

<https://www.phoenixcontact.com/pc/products/3070310>

SCPI 2-8 - Short-circuit connector

3070423

<https://www.phoenixcontact.com/pc/products/3070423>

Short-circuit connector, pitch: 8.15 mm, number of positions: 2, color: orange



SCPI 4-8 - Short-circuit connector

3070424

<https://www.phoenixcontact.com/pc/products/3070424>

Short-circuit connector, pitch: 8.15 mm, number of positions: 4, color: orange



USST 6-T/SB - Test disconnect terminal block



3070310

<https://www.phoenixcontact.com/pc/products/3070310>

NS 32 PERF 2000MM-VPE 10 - DIN rail perforated

1201002

<https://www.phoenixcontact.com/pc/products/1201002>



DIN rail perforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, G profile, color: silver

NS 32 UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201015

<https://www.phoenixcontact.com/pc/products/1201015>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, G profile, color: silver

USST 6-T/SB - Test disconnect terminal block



3070310

<https://www.phoenixcontact.com/pc/products/3070310>

NS 35/ 7,5 PERF 2000MM - DIN rail perforated

0801733

<https://www.phoenixcontact.com/pc/products/0801733>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

NS 35/ 7,5 UNPERF 2000MM - DIN rail, unperforated

0801681

<https://www.phoenixcontact.com/pc/products/0801681>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

USST 6-T/SB - Test disconnect terminal block

3070310

<https://www.phoenixcontact.com/pc/products/3070310>



NS 35/ 7,5 WH PERF 2000MM - DIN rail perforated

1204119

<https://www.phoenixcontact.com/pc/products/1204119>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

NS 35/ 7,5 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204122

<https://www.phoenixcontact.com/pc/products/1204122>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

USST 6-T/SB - Test disconnect terminal block

3070310

<https://www.phoenixcontact.com/pc/products/3070310>



NS 35/ 7,5 AL UNPERF 2000MM - DIN rail, unperforated

0801704

<https://www.phoenixcontact.com/pc/products/0801704>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

NS 35/ 7,5 ZN PERF 2000MM - DIN rail perforated

1206421

<https://www.phoenixcontact.com/pc/products/1206421>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

USST 6-T/SB - Test disconnect terminal block

3070310

<https://www.phoenixcontact.com/pc/products/3070310>



NS 35/ 7,5 ZN UNPERF 2000MM - DIN rail, unperforated

1206434

<https://www.phoenixcontact.com/pc/products/1206434>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

NS 35/ 7,5 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

0801762

<https://www.phoenixcontact.com/pc/products/0801762>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

USST 6-T/SB - Test disconnect terminal block

3070310

<https://www.phoenixcontact.com/pc/products/3070310>



NS 35/ 7,5 CAP - End cap

1206560

<https://www.phoenixcontact.com/pc/products/1206560>

DIN rail end piece, for DIN rail NS 35/7.5



NS 35/15 PERF 2000MM - DIN rail perforated

1201730

<https://www.phoenixcontact.com/pc/products/1201730>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

USST 6-T/SB - Test disconnect terminal block

3070310

<https://www.phoenixcontact.com/pc/products/3070310>



NS 35/15 UNPERF 2000MM - DIN rail, unperforated

1201714

<https://www.phoenixcontact.com/pc/products/1201714>



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

NS 35/15 WH PERF 2000MM - DIN rail perforated

0806602

<https://www.phoenixcontact.com/pc/products/0806602>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: white

USST 6-T/SB - Test disconnect terminal block

3070310

<https://www.phoenixcontact.com/pc/products/3070310>



NS 35/15 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204135

<https://www.phoenixcontact.com/pc/products/1204135>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

NS 35/15 AL UNPERF 2000MM - DIN rail, unperforated

1201756

<https://www.phoenixcontact.com/pc/products/1201756>



DIN rail, unperforated, similar to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

USST 6-T/SB - Test disconnect terminal block

3070310

<https://www.phoenixcontact.com/pc/products/3070310>



NS 35/15 ZN PERF 2000MM - DIN rail perforated

1206599

<https://www.phoenixcontact.com/pc/products/1206599>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver

NS 35/15 ZN UNPERF 2000MM - DIN rail, unperforated

1206586

<https://www.phoenixcontact.com/pc/products/1206586>



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver

USST 6-T/SB - Test disconnect terminal block



3070310

<https://www.phoenixcontact.com/pc/products/3070310>

NS 35/15 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201895

<https://www.phoenixcontact.com/pc/products/1201895>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

NS 35/15 CAP - End cap

1206573

<https://www.phoenixcontact.com/pc/products/1206573>

DIN rail end piece, for DIN rail NS 35/15



USST 6-T/SB - Test disconnect terminal block



3070310

<https://www.phoenixcontact.com/pc/products/3070310>

NS 35/15-2,3 UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201798

<https://www.phoenixcontact.com/pc/products/1201798>




DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile 2.3 mm, color: silver

ZB 8:UNBEDRUCKT - Zack marker strip

1052002

<https://www.phoenixcontact.com/pc/products/1052002>



Zack marker strip, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 10.5 x 8.15 mm, Number of individual labels: 10

USST 6-T/SB - Test disconnect terminal block

3070310


<https://www.phoenixcontact.com/pc/products/3070310>



ZB 8 CUS - Zack marker strip

0825011

<https://www.phoenixcontact.com/pc/products/0825011>



Zack marker strip, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 8.2 mm, lettering field size: 10.5 x 8.15 mm, Number of individual labels: 10

UC-TM 8 - Marker for terminal blocks

0818072

<https://www.phoenixcontact.com/pc/products/0818072>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 7.6 x 10.5 mm, Number of individual labels: 56

USST 6-T/SB - Test disconnect terminal block

3070310

<https://www.phoenixcontact.com/pc/products/3070310>



UC-TM 8 CUS - Marker for terminal blocks

0824597

<https://www.phoenixcontact.com/pc/products/0824597>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 8.2 mm, lettering field size: 7.6 x 10.5 mm, Number of individual labels: 56

UCT-TM 8 - Marker for terminal blocks

0828740

<https://www.phoenixcontact.com/pc/products/0828740>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 7.6 x 10.5 mm, Number of individual labels: 42

USST 6-T/SB - Test disconnect terminal block



3070310

<https://www.phoenixcontact.com/pc/products/3070310>

UCT-TM 8 CUS - Marker for terminal blocks

0829616

<https://www.phoenixcontact.com/pc/products/0829616>




Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 8.2 mm, lettering field size: 7.6 x 10.5 mm, Number of individual labels: 42

ZB 8,LGS:FORTL.ZAHLEN - Zack marker strip

1052015

<https://www.phoenixcontact.com/pc/products/1052015>



Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, printed horizontally: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 91 ... 100, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 10.5 x 8.15 mm, Number of individual labels: 10

USST 6-T/SB - Test disconnect terminal block




3070310

<https://www.phoenixcontact.com/pc/products/3070310>

ZB 8,QR:FORTL.ZAHLEN - Zack marker strip

1052028

<https://www.phoenixcontact.com/pc/products/1052028>




Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, Printed vertically: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 91 ... 100, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 10.5 x 8.15 mm, Number of individual labels: 10

ZB 8,LGS:L1-N,PE - Marker for terminal blocks

1052413

<https://www.phoenixcontact.com/pc/products/1052413>



Marker for terminal blocks, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, horizontal: L1, L2, L3, N, PE, L1, L2, L3, N, PE, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 10.5 x 8.15 mm, Number of individual labels: 10

USST 6-T/SB - Test disconnect terminal block



3070310

<https://www.phoenixcontact.com/pc/products/3070310>

CLIPFIX 35 - End bracket

3022218

<https://www.phoenixcontact.com/pc/products/3022218>

Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, width: 9.5 mm, color: gray



CLIPFIX 35-5 - End bracket

3022276

<https://www.phoenixcontact.com/pc/products/3022276>

Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, with parking option for FBS...5, FBS...6, KSS 5, KSS 6, width: 5.15 mm, color: gray



USST 6-T/SB - Test disconnect terminal block



3070310


<https://www.phoenixcontact.com/pc/products/3070310>

E/NS 35 N - End bracket

0800886

<https://www.phoenixcontact.com/pc/products/0800886>

End clamp, width: 9.5 mm, color: gray



E/UK - End bracket

1201442

<https://www.phoenixcontact.com/pc/products/1201442>

End bracket, Mounting on a DIN rail NS 32 or NS 35, material: PA, color: gray



USST 6-T/SB - Test disconnect terminal block



3070310

<https://www.phoenixcontact.com/pc/products/3070310>

E/UK 1 - End bracket

1201413

<https://www.phoenixcontact.com/pc/products/1201413>



End clamps, for supporting the ends of double-level and three-level terminal blocks, width: 10 mm, color: gray

PSBJ 6-T GY - Test plug strip

3070316

<https://www.phoenixcontact.com/pc/products/3070316>



Test plug strip, number of positions: 1, color: gray

USST 6-T/SB - Test disconnect terminal block

3070310

<https://www.phoenixcontact.com/pc/products/3070310>



PSBJ 6-T BN - Test plug strip

3070317

<https://www.phoenixcontact.com/pc/products/3070317>

Test plug strip, number of positions: 1, color: brown



PSBJ 6-T BK - Test plug strip

3070318

<https://www.phoenixcontact.com/pc/products/3070318>

Test plug strip, number of positions: 1, color: black



USST 6-T/SB - Test disconnect terminal block

3070310

<https://www.phoenixcontact.com/pc/products/3070310>



PSBJ 6-T RD - Test plug strip

3070319

<https://www.phoenixcontact.com/pc/products/3070319>

Test plug strip, number of positions: 1, color: red



PSBJ 6-T OG - Test plug strip

3070320

<https://www.phoenixcontact.com/pc/products/3070320>

Test plug strip, number of positions: 1, color: orange



USST 6-T/SB - Test disconnect terminal block

3070310

<https://www.phoenixcontact.com/pc/products/3070310>



PSBJ 6-T WH - Test plug strip

3070324

<https://www.phoenixcontact.com/pc/products/3070324>



Test plug strip, number of positions: 1, color: white

PSBJ 6-T YE - Test plug strip

3070326

<https://www.phoenixcontact.com/pc/products/3070326>



Test plug strip, number of positions: 1, color: yellow

USST 6-T/SB - Test disconnect terminal block

3070310

<https://www.phoenixcontact.com/pc/products/3070310>



PSBJ 6-T GN - Test plug strip

3070327

<https://www.phoenixcontact.com/pc/products/3070327>

Test plug strip, number of positions: 1, color: green



PSBJ 6-T VT - Test plug strip

3070328

<https://www.phoenixcontact.com/pc/products/3070328>

Test plug strip, number of positions: 1, color: violet



USST 6-T/SB - Test disconnect terminal block

3070310

<https://www.phoenixcontact.com/pc/products/3070310>



PSBJ 6-T BU - Test plug strip

3070329

<https://www.phoenixcontact.com/pc/products/3070329>



Test plug strip, number of positions: 1, color: blue

SZS 1,0X4,0 VDE - Screwdriver

1205066

<https://www.phoenixcontact.com/pc/products/1205066>



Screwdriver, slot-headed, VDE insulated, size: 1.0 x 4.0 x 100 mm, 2-component grip, with non-slip grip

USST 6-T/SB - Test disconnect terminal block



3070310

<https://www.phoenixcontact.com/pc/products/3070310>

SZS 0,6X3,5 - Screwdriver

1205053

<https://www.phoenixcontact.com/pc/products/1205053>



Actuation tool, for ST terminal blocks, insulated, also suitable for use as a bladed screwdriver, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip

CRIMPFOX-RCI 6 - Crimping pliers

1212057

<https://www.phoenixcontact.com/pc/products/1212057>



Crimping pliers, for insulated cable lugs, 0.5 mm² ... 6.0 mm² (red, blue, yellow), oval crimp, symmetrical

USST 6-T/SB - Test disconnect terminal block



3070310

<https://www.phoenixcontact.com/pc/products/3070310>

C-BCI 1,5/2,8 - Cable lug

3240015

<https://www.phoenixcontact.com/pc/products/3240015>



Flat pin cable lug, with tab, soldered neck, red, 0.5 ... 1.5 mm², pin width: 2.8 mm, easy conductor entry with Easy-Entry, for horizontal and vertical crimping with CRIMPFOX-RCI 6

C-BCI 1,5/4,6 - Cable lug

3240568

<https://www.phoenixcontact.com/pc/products/3240568>



Flat pin cable lug, with tab, soldered neck, red, 0.5 ... 1.5 mm², pin width: 4.6 mm, easy conductor entry with Easy-Entry, for horizontal and vertical crimping with CRIMPFOX-RCI 6

USST 6-T/SB - Test disconnect terminal block



3070310

<https://www.phoenixcontact.com/pc/products/3070310>

C-BCI 2,5/2,8 - Cable lug

3240046

<https://www.phoenixcontact.com/pc/products/3240046>



Flat pin cable lug, with tab, soldered neck, blue, 1.5 ... 2.5 mm², pin width: 2.8 mm, easy conductor entry with Easy-Entry, for horizontal and vertical crimping with CRIMPFOX-RCI 6

C-BCI 2,5/4,6 - Cable lug

3240569

<https://www.phoenixcontact.com/pc/products/3240569>



Flat pin cable lug, with tab, soldered neck, blue, 1.5 ... 2.5 mm², pin width: 4.6 mm, easy conductor entry with Easy-Entry, for horizontal and vertical crimping with CRIMPFOX-RCI 6

USST 6-T/SB - Test disconnect terminal block



3070310

<https://www.phoenixcontact.com/pc/products/3070310>

C-BCI 6/4,6 SO - Cable lug

3240067

<https://www.phoenixcontact.com/pc/products/3240067>



Flat pin cable lug, with tab, soldered neck, yellow, 4 ... 6 mm², pin width: 4.6 mm, easy conductor entry with Easy-Entry, for horizontal and vertical crimping with CRIMPFOX-RCI 6

SF-SL 0,6X3,5-100 S-VDE - Screwdriver

1212587

<https://www.phoenixcontact.com/pc/products/1212587>



Actuation tool, for ST terminal blocks, VDE insulated, with slimmer insulation integrated in the blade, also suitable for use as a bladed screwdriver, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip

USST 6-T/SB - Test disconnect terminal block



3070310

<https://www.phoenixcontact.com/pc/products/3070310>

TS-UT 6-T/SP - Separating plate

3072821

<https://www.phoenixcontact.com/pc/products/3072821>

Separating plate, depth: 67.5 mm, width: 1 mm, height: 105.2 mm, color: gray



Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG

Flachsmarktstraße 8

D-32825 Blomberg

+49 (0) 5235-3 00

info@phoenixcontact.com