

# Product data sheet

Specifications



## Square D - PowerLogic 3090 SCCT - split core CT - 600/5 A - size 3 - 5 VA

3090SCCT063

Product availability: Non-Stock - Not normally stocked in  
distribution facility

Price\*: 285.76 USD

### Main

Range	PowerLogic
Product Or Component Type	Current transformer
Accessory / Separate Part Categor	Measurement accessory

### Complementary

Range Compatibility	PowerLogic PowerLogic PM3000 power meter PowerLogic PowerLogic PM5000 power meter PowerLogic PowerLogic PM8000 power meter PowerLogic PowerLogic ION7400 power meter PowerLogic CM4000T circuit monitor Acti 9 Acti9 iEM3000 energy meter
Current Transformer Type	Split core
Primary Operational Current	600 A
Secondary Current	5 A
Network Type	AC
Network Frequency	50/60 Hz
Current Transformer Ratio	600/5
Burden	5 VA
Electrical Connection	5.91 ft (1.8 m) AWG 18 flying leads
Insulation	Basic insulation 600 V AC Reinforced insulation 300 V AC
Measurement Accuracy	1 % full scale
Mounting Location	Indoor use only
Width	Internal: 2.44 in (62 mm) External: 5.91 in (150 mm)
Depth	1.14 in (29 mm)
Height	Internal: 2.87 in (73 mm) External: 5.55 in (141 mm)

### Environment

Relative Humidity	0...95 % non-condensing
Installation Category	III
Pollution Degree	2
Ambient Air Temperature For Operation	5...140 °F (-15...60 °C)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ambient Air Temperature For Storage	-40...158 °F (-40...70 °C)
Operating Altitude	<= 9842.52 ft (3000 m)
Standards	UL 1015 IEC 61010-1 UL 61010-1

## Ordering and shipping details

Category	US10PL109661
Discount Schedule	0PL1
Gtin	785901000471
Returnability	No
Country Of Origin	US

## Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	0.98 in (2.5 cm)
Package 1 Width	5.24 in (13.3 cm)
Package 1 Length	5.87 in (14.9 cm)
Package 1 Weight	19.24 oz (545.45 g)

## Contractual warranty

Warranty	18 months
----------	-----------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

## Well-being performance

✓	Reach Free Of Svhc	
✓	Toxic Heavy Metal Free	
✓	Mercury Free	
✓	Rohs Exemption Information	Yes
Reach Regulation	<a href="#">REACH Declaration</a>	
Eu Rohs Directive	Compliant	<a href="#">EU RoHS Declaration</a>
China Rohs Regulation	<a href="#">China RoHS declaration</a>	
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="#">www.P65Warnings.ca.gov</a>	