

A 0,75- 6 - Ferrule

3200221

<https://www.phoenixcontact.com/pc/products/3200221>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Ferrule, sleeve length: 6 mm, color: silver



Commercial data

Item number	3200221
Packing unit	1,000 pc
Minimum order quantity	1,000 pc
Sales key	05
Product key	BH3412
Catalog page	Page 480 (C-3-2019)
GTIN	4017918093877
Weight per piece (including packing)	0.037 g
Weight per piece (excluding packing)	0.037 g
Customs tariff number	85369010
Country of origin	DE

A 0,75- 6 - Ferrule

3200221

<https://www.phoenixcontact.com/pc/products/3200221>



Technical data

Product properties


Product type	Cable end sleeve
Conductor category	stranded conductors, class 2, 5, 6 / B, C, K, M

Connection data

Conductor connection

Conductor cross section flexible max.	0.75 mm²
Conductor cross section AWG max.	18
Stripping length	7 mm

Dimensions

Dimensional drawing	
Sleeve length	6 mm
Ferrule diameter	1.2 mm
Sleeve wall thickness	0.15 mm
Inner dimensions of the insulating collar	2.3 mm

Material specifications

Color	silver
Material	CU-DHP
Coating	tin-plated (galvanic)

Mechanical properties

Technical data

Sleeve length	6 mm
---------------	------

Environmental and real-life conditions

Ambient conditions

Permanent temperature	105 °C
Short-term temperature	120 °C

Standards and regulations

Design according to standard	DIN 46228-1, UL 486F-A
------------------------------	------------------------

A 0,75- 6 - Ferrule

3200221

<https://www.phoenixcontact.com/pc/products/3200221>



Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com