

# AI 0,75-12 GY - Ferrule



3200849

<https://www.phoenixcontact.com/gb/products/3200849>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Ferrule, sleeve length: 12 mm, color: gray

## Your advantages

- The insulation reliability of close connections is increased and the splicing of wires is prevented
- The ferrules with plastic sleeve are made from soft tin-plated electrolytic copper

## Commercial data

Item number	3200849
Packing unit	100 pc
Minimum order quantity	100 pc
Sales key	BH3411
Product key	BH3411
Catalog page	Page 481 (C-3-2019)
GTIN	4017918094393
Weight per piece (including packing)	0.116 g
Weight per piece (excluding packing)	0.109 g
Customs tariff number	85369010
Country of origin	DE

# AI 0,75-12 GY - Ferrule



3200849

<https://www.phoenixcontact.com/gb/products/3200849>

## Technical data

### Product properties


Product type	Cable end sleeve
Conductor category	stranded conductors, class 2, 5, 6 / B, C, K, M

### Connection data

#### Conductor connection

Conductor cross section flexible max.	0.75 mm²
Conductor cross section AWG max.	18
Stripping length	15 mm

### Dimensions

Dimensional drawing	
Sleeve length	12 mm
Maximum stripping length	15 mm
Ferrule diameter	1.3 mm
Sleeve wall thickness	0.15 mm
Insulating collar thickness	0.25 mm
Inner dimensions of the insulating collar	2.8 mm

### Material specifications

Color	gray
Material	CU-DHP
Flammability rating according to UL 94	HB
Coating	tin-plated (galvanic)
Components	free from silicone and halogen

### Mechanical properties

#### Technical data

Sleeve length	12 mm
---------------	-------

### Environmental and real-life conditions

#### Ambient conditions

Permanent temperature	105 °C (-40 °C no load / 0 °C dynamic load)
Short-term temperature	120 °C

### Standards and regulations

# AI 0,75-12 GY - Ferrule



3200849

<https://www.phoenixcontact.com/gb/products/3200849>

Design according to standard	DIN 46228-4, UL 486F-E
------------------------------	------------------------

# AI 0,75-12 GY - Ferrule


3200849

<https://www.phoenixcontact.com/gb/products/3200849>



## Drawings

Dimensional drawing



# AI 0,75-12 GY - Ferrule




3200849


<https://www.phoenixcontact.com/gb/products/3200849>

## Approvals


To download certificates, visit the product detail page: <https://www.phoenixcontact.com/gb/products/3200849>



**UL Listed**  
Approval ID: E488001



**cUL Listed**  
Approval ID: E488001



**cULus Listed**  
Approval ID: E488001

**cULus Listed**

# AI 0,75-12 GY - Ferrule

3200849

<https://www.phoenixcontact.com/gb/products/3200849>



## Classifications

### ECLASS

ECLASS-11.0	27400201
ECLASS-13.0	27400201
ECLASS-12.0	27400201

### ETIM

ETIM 9.0	EC000005
----------	----------

### UNSPSC

UNSPSC 21.0	27121700
-------------	----------

# AI 0,75-12 GY - Ferrule



3200849  
<https://www.phoenixcontact.com/gb/products/3200849>

## Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd  
Halesfield 13, Telford  
Shropshire, TF7 4PG  
01952 681700  
[info@phoenixcontact.co.uk](mailto:info@phoenixcontact.co.uk)