# PH 2,5/6 - Cable housing

3209730

https://www.phoenixcontact.com/us/products/3209730



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable housing, pitch: 31.2 mm, depth: 36.8 mm, width: 31.2 mm, height: 19.9 mm, number of positions: 6, color: gray

## Your advantages

- · Robust cable housing for strain relief on connecting cables
- · Can be aligned without any loss of pitch
- · Additional scope for marking plugs

## Commercial data

Item number	3209730
Packing unit	25 рс
Minimum order quantity	25 рс
Sales key	BE22
Product key	BE224Z
Catalog page	Page 366 (C-1-2019)
GTIN	4046356366939
Weight per piece (including packing)	9.672 g
Weight per piece (excluding packing)	7.17 g
Customs tariff number	39269097
Country of origin	PL

# PH 2,5/ 6 - Cable housing

3209730

https://www.phoenixcontact.com/us/products/3209730



## Technical data

### Product properties

Product type	Cable housing
Number of positions	6
Pitch	31.2 mm

### Material specifications

Color	gray (RAL 7042)
Material	PA
Flammability rating according to UL 94	V0
Static insulating material application in cold	-60 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	130 °C
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3
Calorimetric heat release NFPA 130 (ASTM E 1354)	28 MJ/kg
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed

#### Dimensions

Width	31.2 mm
Height	19.9 mm
Depth	36.8 mm
Pitch	31.2 mm

#### Notes

Assembly note a cable tie or cable clamp is required for strain relief	
--	--

# PH 2,5/ 6 - Cable housing

3209730

https://www.phoenixcontact.com/us/products/3209730



# Classifications

### ECLASS

ECLASS-12.0 27440202   ECLASS-13.0 27440202	ECLASS-11.0	27440202
ECLASS-13.0 27440202	ECLASS-12.0	27440202
	ECLASS-13.0	27440202

### ETIM

	ETIM 9.0	EC000437
UNSPSC		
	UNSPSC 21.0	31261500

# PH 2,5/6 - Cable housing

3209730

https://www.phoenixcontact.com/us/products/3209730



## Environmental product compliance

#### EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com