

PTMED 4-PE - Ground terminal



3212154

<https://www.phoenixcontact.com/no/products/3212154>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Ground terminal, number of connections: 2, connection method: Push-in connection, 1 level, cross section: 0.2 mm² - 6 mm², mounting type: NS 35/7,5, NS 35/15, color: green-yellow

Commercial data

Item number	3212154
Packing unit	50 pc
Minimum order quantity	1 pc
Sales key	31BB22
Product key	BE2233
Catalog page	Page 105 (C-1-2019)
GTIN	4046356661911
Weight per piece (including packing)	16.782 g
Weight per piece (excluding packing)	12.6 g
Customs tariff number	85369010
Country of origin	PL

PTMED 4-PE - Ground terminal



3212154

<https://www.phoenixcontact.com/no/products/3212154>

Technical data

Product properties

Product type	Ground terminal block
Number of connections	2
Number of rows	1

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Electrical properties

Rated surge voltage	6 kV
Maximum power dissipation for nominal condition	1.02 W

Connection data

Grounding foot	Yes
Number of connections per level	2
Nominal cross section	4 mm ²

1 level

Note	Please observe the current carrying capacity of the DIN rails.
Stripping length	10 mm ... 12 mm
Internal cylindrical gage	A4
Connection in acc. with standard	IEC 60947-7-2
Conductor cross section rigid	0.2 mm ² ... 6 mm ²
Cross section AWG	24 ... 10 (converted acc. to IEC)
Conductor cross section flexible	0.2 mm ² ... 4 mm ²
Conductor cross section, flexible [AWG]	24 ... 12 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve)	0.25 mm ² ... 4 mm ²
Flexible conductor cross section (ferrule with plastic sleeve)	0.25 mm ² ... 4 mm ²

1 level Connection cross sections directly pluggable

Conductor cross section rigid	0.5 mm ² ... 6 mm ²
Conductor cross-section flexible (ferrule without plastic sleeve)	0.5 mm ² ... 4 mm ²
Flexible conductor cross section (ferrule with plastic sleeve)	0.5 mm ² ... 4 mm ²

Dimensions

Width	6.2 mm
End cover width	2.2 mm
Height	70.5 mm
Depth	48.8 mm
Depth on NS 35/7,5	49.5 mm
Depth on NS 35/15	57 mm

PTMED 4-PE - Ground terminal



3212154

<https://www.phoenixcontact.com/no/products/3212154>

Material specifications

Color	green-yellow
Flammability rating according to UL 94	V0
Insulating material group	I
Insulating material	PA
Static insulating material application in cold	-60 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	130 °C
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3
Calorimetric heat release NFPA 130 (ASTM E 1354)	28 MJ/kg
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed

Mechanical properties

Mechanical data

Open side panel	Yes
-----------------	-----

Environmental and real-life conditions

Oscillation/broadband noise

Specification	DIN EN 50155 (VDE 0115-200):2008-03
Spectrum	Service life test category 2, bogie-mounted
Frequency	$f_1 = 5 \text{ Hz}$ to $f_2 = 250 \text{ Hz}$
ASD level	$6.12 \text{ (m/s}^2\text{)}^2/\text{Hz}$
Acceleration	3.12g
Test duration per axis	5 h
Test directions	X-, Y- and Z-axis
Result	Test passed

Shocks

Specification	DIN EN 50155 (VDE 0115-200):2008-03
Pulse shape	Half-sine
Acceleration	30g
Shock duration	18 ms
Number of shocks per direction	3
Test directions	X-, Y- and Z-axis (pos. and neg.)
Result	Test passed

Ambient conditions

Ambient temperature (operation)	-60 °C ... 110 °C (Operating temperature range incl. self-heating;
---------------------------------	--

PTMED 4-PE - Ground terminal



3212154

<https://www.phoenixcontact.com/no/products/3212154>

	for max. short-term operating temperature, see RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (operation)	20 % ... 90 %
Permissible humidity (storage/transport)	30 % ... 70 %

Standards and regulations

Connection in acc. with standard	IEC 60947-7-2
----------------------------------	---------------

Mounting

Mounting type	NS 35/7,5
	NS 35/15

PTMED 4-PE - Ground terminal


3212154

<https://www.phoenixcontact.com/no/products/3212154>




Drawings

Circuit diagram



Circuit diagram




PTMED 4-PE - Ground terminal

3212154


<https://www.phoenixcontact.com/no/products/3212154>



Circuit diagram



Circuit diagram



PTMED 4-PE - Ground terminal



3212154

<https://www.phoenixcontact.com/no/products/3212154>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/no/products/3212154>

 CSA Approval ID: 2030668				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	-	-	24 - 10	-

 EAC Approval ID: RU C-DE.BL08.B.00644				
---	--	--	--	--

 cULus Recognized Approval ID: E60425				
--	--	--	--	--

 cULus Recognized Approval ID: E60425				
--	--	--	--	--

 cULus Recognized Approval ID: E60425				
--	--	--	--	--

PTMED 4-PE - Ground terminal



3212154

<https://www.phoenixcontact.com/no/products/3212154>

Classifications

ECLASS

ECLASS-11.0	27141141
ECLASS-13.0	27250109

ETIM

ETIM 9.0	EC000901
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

PTMED 4-PE - Ground terminal



3212154

<https://www.phoenixcontact.com/no/products/3212154>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



Accessories

FBS 20-6 - Plug-in bridge

3030365

<https://www.phoenixcontact.com/no/products/3030365>



Plug-in bridge, pitch: 6.2 mm, number of positions: 20, color: red

FBS 10-6 - Plug-in bridge

3030271

<https://www.phoenixcontact.com/no/products/3030271>



Plug-in bridge, pitch: 6.2 mm, number of positions: 10, color: red

PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



FBS 6-6 - Plug-in bridge

1008238

<https://www.phoenixcontact.com/no/products/1008238>



Plug-in bridge, One side not fully isolated, pitch: 6.2 mm, number of positions: 6, color: red

FBS 5-6 - Plug-in bridge

3030349

<https://www.phoenixcontact.com/no/products/3030349>



Plug-in bridge, pitch: 6.2 mm, number of positions: 5, color: red

PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



FBS 4-6 - Plug-in bridge

3030255

<https://www.phoenixcontact.com/no/products/3030255>

Plug-in bridge, pitch: 6.2 mm, number of positions: 4, color: red



FBS 3-6 - Plug-in bridge

3030242

<https://www.phoenixcontact.com/no/products/3030242>

Plug-in bridge, pitch: 6.2 mm, number of positions: 3, color: red



PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



FBS 2-6 - Plug-in bridge

3030336

<https://www.phoenixcontact.com/no/products/3030336>



Plug-in bridge, pitch: 6.2 mm, number of positions: 2, color: red

FBS 50-6 - Plug-in bridge

3032224

<https://www.phoenixcontact.com/no/products/3032224>



Plug-in bridge, pitch: 6.2 mm, number of positions: 50, color: red

PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



SB-ME 2-6 - Switching jumper

3035755

<https://www.phoenixcontact.com/no/products/3035755>



Switching jumper, pitch: 6.2 mm, number of positions: 2, length: 21 mm, color: gray/orange

SB-ME 3-6 - Switching jumper

3035756

<https://www.phoenixcontact.com/no/products/3035756>



Switching jumper, pitch: 6.2 mm, number of positions: 3, length: 21 mm, color: gray/orange

PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



SB-ME 4-6 - Switching jumper

3035757

<https://www.phoenixcontact.com/no/products/3035757>



Switching jumper, pitch: 6.2 mm, number of positions: 4, length: 21 mm, color: gray/orange

FBSR 2-6 - Plug-in bridge

3033715

<https://www.phoenixcontact.com/no/products/3033715>



Plug-in bridge, pitch: 6.2 mm, number of positions: 2, color: red

PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



FBSR 3-6 - Plug-in bridge

3001594

<https://www.phoenixcontact.com/no/products/3001594>



Plug-in bridge, pitch: 6.2 mm, number of positions: 3, color: red

FBSR 4-6 - Plug-in bridge

3001595

<https://www.phoenixcontact.com/no/products/3001595>



Plug-in bridge, pitch: 6.2 mm, number of positions: 4, color: red

PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



FBSR 5-6 - Plug-in bridge

3001596

<https://www.phoenixcontact.com/no/products/3001596>



Plug-in bridge, pitch: 6.2 mm, number of positions: 5, color: red

FBSR 10-6 - Plug-in bridge

3033716

<https://www.phoenixcontact.com/no/products/3033716>



Plug-in bridge, pitch: 6.2 mm, number of positions: 10, color: red

PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



FBSRH 2-6 - Short-circuit connector

3033812

<https://www.phoenixcontact.com/no/products/3033812>



Short-circuit connector, pitch: 6.2 mm, number of positions: 2, color: red

FBS 2-6 BU - Plug-in bridge

3036932

<https://www.phoenixcontact.com/no/products/3036932>



Plug-in bridge, pitch: 6.2 mm, number of positions: 2, color: blue

PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



FBS 3-6 BU - Plug-in bridge

3036945

<https://www.phoenixcontact.com/no/products/3036945>



Plug-in bridge, pitch: 6.2 mm, number of positions: 3, color: blue

FBS 4-6 BU - Plug-in bridge

3036958

<https://www.phoenixcontact.com/no/products/3036958>



Plug-in bridge, pitch: 6.2 mm, number of positions: 4, color: blue

PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



FBS 5-6 BU - Plug-in bridge

3036961

<https://www.phoenixcontact.com/no/products/3036961>



Plug-in bridge, pitch: 6.2 mm, number of positions: 5, color: blue

FBS 10-6 BU - Plug-in bridge

3032198

<https://www.phoenixcontact.com/no/products/3032198>



Plug-in bridge, pitch: 6.2 mm, number of positions: 10, color: blue

PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>




FBS 20-6 BU - Plug-in bridge

3032208

<https://www.phoenixcontact.com/no/products/3032208>

Plug-in bridge, pitch: 6.2 mm, number of positions: 20, color: blue



FBS 50-6 BU - Plug-in bridge

3032211

<https://www.phoenixcontact.com/no/products/3032211>

Plug-in bridge, pitch: 6.2 mm, number of positions: 50, color: blue



PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



GBS 5-25X12 - Group marker label for terminal marking

0810588

<https://www.phoenixcontact.com/no/products/0810588>



Group marker label, snaps onto terminal center for screw, spring-cage and quick connection terminal blocks, labeled with a 25 x 12 mm label or manually with the B-STIFT, in the foot part with ZB 5

GBS-ZB/26X6 - Group marker label for terminal marking

0809298

<https://www.phoenixcontact.com/no/products/0809298>



Group marking label, snaps onto terminal center for screw, spring-cage and quick connection terminal blocks, labeled with ESL 26x6 mm or EST 25x6 mm, in the foot part with Zack marker strip, length: 29 mm

PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



CARRIER-TM 300 - Marker carriers

0828282

<https://www.phoenixcontact.com/no/products/0828282>



Marker adapter, 300 mm in length, for manual cutting, can be engaged in a flat marker groove, for ZB ..., UC-TM ... or UCT-TM ...

AP-ME

METER - Cover profile

3034361

<https://www.phoenixcontact.com/no/products/3034361>



Cover profile, for covering terminal strips, snapped onto APT-ME cover profile carrier or APH-ME end bracket. A cover profile carrier should be positioned at the ends and at intervals of around 40 cm. Length supplied: 1 m

PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>




APH-ME - Cover profile carrier

3034374

<https://www.phoenixcontact.com/no/products/3034374>

Cover profile carrier, for mounting on NS 35/7,5 DIN rail, for fixing the AP-ME cover profile, can be sealed as an option



APT-ME - Cover profile carrier

3034358

<https://www.phoenixcontact.com/no/products/3034358>

Cover profile carrier for mounting on NS 35/7.5 DIN rail for attaching the cover profile AP-ME



PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



D-PTME 4 - End cover

3212167

<https://www.phoenixcontact.com/no/products/3212167>

End cover, depth: 39.7 mm, width: 2.2 mm, height: 70.6 mm, color: gray




TS-UK 6-T - Separating plate

3072820

<https://www.phoenixcontact.com/no/products/3072820>

Separating plate, depth: 62.5 mm, width: 1 mm, height: 66.5 mm, color: gray



PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



NS 35/ 7,5 PERF 2000MM - DIN rail perforated

0801733

<https://www.phoenixcontact.com/no/products/0801733>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

NS 35/ 7,5 UNPERF 2000MM - DIN rail, unperforated

0801681

<https://www.phoenixcontact.com/no/products/0801681>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



NS 35/ 7,5 WH PERF 2000MM - DIN rail perforated

1204119

<https://www.phoenixcontact.com/no/products/1204119>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

NS 35/ 7,5 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204122

<https://www.phoenixcontact.com/no/products/1204122>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



NS 35/ 7,5 AL UNPERF 2000MM - DIN rail, unperforated

0801704

<https://www.phoenixcontact.com/no/products/0801704>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

NS 35/ 7,5 ZN PERF 2000MM - DIN rail perforated

1206421

<https://www.phoenixcontact.com/no/products/1206421>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



NS 35/ 7,5 ZN UNPERF 2000MM - DIN rail, unperforated

1206434

<https://www.phoenixcontact.com/no/products/1206434>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

NS 35/ 7,5 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

0801762

<https://www.phoenixcontact.com/no/products/0801762>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



NS 35/ 7,5 CAP - End cap

1206560

<https://www.phoenixcontact.com/no/products/1206560>

DIN rail end piece, for DIN rail NS 35/7.5



NS 35/15 PERF 2000MM - DIN rail perforated

1201730

<https://www.phoenixcontact.com/no/products/1201730>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



NS 35/15 UNPERF 2000MM - DIN rail, unperforated

1201714

<https://www.phoenixcontact.com/no/products/1201714>



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

NS 35/15 WH PERF 2000MM - DIN rail perforated

0806602

<https://www.phoenixcontact.com/no/products/0806602>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: white

PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



NS 35/15 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204135

<https://www.phoenixcontact.com/no/products/1204135>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

NS 35/15 AL UNPERF 2000MM - DIN rail, unperforated

1201756

<https://www.phoenixcontact.com/no/products/1201756>



DIN rail, unperforated, similar to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



NS 35/15 ZN PERF 2000MM - DIN rail perforated

1206599

<https://www.phoenixcontact.com/no/products/1206599>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver

NS 35/15 ZN UNPERF 2000MM - DIN rail, unperforated

1206586

<https://www.phoenixcontact.com/no/products/1206586>



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver

PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



NS 35/15 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201895

<https://www.phoenixcontact.com/no/products/1201895>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

NS 35/15 CAP - End cap

1206573

<https://www.phoenixcontact.com/no/products/1206573>

DIN rail end piece, for DIN rail NS 35/15



PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



NS 35/15-2,3 UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201798

<https://www.phoenixcontact.com/no/products/1201798>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile 2.3 mm, color: silver

ZB 6:UNBEDRUCKT - Zack marker strip

1051003

<https://www.phoenixcontact.com/no/products/1051003>



Zack marker strip, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 6.15 x 10.5 mm, Number of individual labels: 10

PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



ZB 6 CUS - Zack marker strip

0824992

<https://www.phoenixcontact.com/no/products/0824992>




Zack marker strip, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 6.2 mm, lettering field size: 6.15 x 10.5 mm, Number of individual labels: 10

ZB 6,LGS:FORTL.ZAHLEN - Zack marker strip

1051016

<https://www.phoenixcontact.com/no/products/1051016>



Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, printed horizontally: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 491 ... 500, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 6.15 x 10.5 mm, Number of individual labels: 10

PTMED 4-PE - Ground terminal

3212154


<https://www.phoenixcontact.com/no/products/3212154>



ZB 6,QR:FORTL.ZAHLEN - Zack marker strip

1051029

<https://www.phoenixcontact.com/no/products/1051029>



Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, Printed vertically: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 491 ... 500, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 6.15 x 10.5 mm, Number of individual labels: 10

ZB 6,LGS:GLEICHE ZAHLEN - Zack marker strip

1051032

<https://www.phoenixcontact.com/no/products/1051032>



Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, printed horizontally: Identical numbers 1 or 2, etc. up to 100, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 6.15 x 10.5 mm, Number of individual labels: 10

PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



ZB 6,LGS:L1-N,PE - Marker for terminal blocks

1051414

<https://www.phoenixcontact.com/no/products/1051414>



Marker for terminal blocks, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, horizontal: L1, L2, L3, N, PE, L1, L2, L3, N, PE, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 6.15 x 10.5 mm, Number of individual labels: 10

ZB 6,LGS:U-N - Marker for terminal blocks

1051430

<https://www.phoenixcontact.com/no/products/1051430>



Marker for terminal blocks, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, printed horizontally: U, V, W, N, GND, U, V, W, N, GND, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 6.15 x 10.5 mm, Number of individual labels: 10

PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



UC-TM 6 - Marker for terminal blocks

0818085

<https://www.phoenixcontact.com/no/products/0818085>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 5.6 x 10.5 mm, Number of individual labels: 80

UC-TM 6 CUS - Marker for terminal blocks

0824589

<https://www.phoenixcontact.com/no/products/0824589>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 6.2 mm, lettering field size: 5.6 x 10.5 mm, Number of individual labels: 80

PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



UCT-TM 6 - Marker for terminal blocks

0828736

<https://www.phoenixcontact.com/no/products/0828736>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 5.6 x 10.5 mm, Number of individual labels: 60

UCT-TM 6 CUS - Marker for terminal blocks

0829602

<https://www.phoenixcontact.com/no/products/0829602>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 6.2 mm, lettering field size: 5.6 x 10.5 mm, Number of individual labels: 60

PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



ZBF 6:UNBEDRUCKT - Zack Marker strip, flat

0808710

<https://www.phoenixcontact.com/no/products/0808710>



Zack Marker strip, flat, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 5.15 x 6.15 mm, Number of individual labels: 10

ZBF 6 CUS - Zack Marker strip, flat

0825027

<https://www.phoenixcontact.com/no/products/0825027>



Zack Marker strip, flat, Strip, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 6.2 mm, lettering field size: 5.15 x 6.15 mm, Number of individual labels: 10

PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



UC-TMF 6 - Marker for terminal blocks

0818140

<https://www.phoenixcontact.com/no/products/0818140>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 5.6 x 5.1 mm, Number of individual labels: 80

UC-TMF 6 CUS - Marker for terminal blocks

0824646

<https://www.phoenixcontact.com/no/products/0824646>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 6.2 mm, lettering field size: 5.6 x 5.1 mm, Number of individual labels: 80

PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



UCT-TMF 6 - Marker for terminal blocks

0828746

<https://www.phoenixcontact.com/no/products/0828746>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 5.4 x 4.7 mm, Number of individual labels: 60

UCT-TMF 6 CUS - Marker for terminal blocks

0829665

<https://www.phoenixcontact.com/no/products/0829665>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 6.2 mm, lettering field size: 5.4 x 4.7 mm, Number of individual labels: 60

PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



ZBF 6,LGS:FORTL.ZAHLEN - Zack Marker strip, flat

0808749

<https://www.phoenixcontact.com/no/products/0808749>



Zack Marker strip, flat, Strip, white, labeled, printed horizontally: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 91 ... 100, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 5.15 x 6.15 mm, Number of individual labels: 10

ZBF 6,QR:FORTL.ZAHLEN - Zack Marker strip, flat

0808765

<https://www.phoenixcontact.com/no/products/0808765>



Zack Marker strip, flat, Strip, white, labeled, Printed vertically: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 91 ... 100, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 5.15 x 6.15 mm, Number of individual labels: 10

PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



ZBF 6,LGS:GERADE ZAHLEN - Zack Marker strip, flat

0810834

<https://www.phoenixcontact.com/no/products/0810834>




Zack Marker strip, flat, Strip, white, labeled, printed horizontally: consecutive even numbers 2 ... 20, 22 ... 40, etc. up to 82 ... 100, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 5.15 x 6.15 mm, Number of individual labels: 10

ZBF 6,LGS:UNGERADE ZAHLEN - Zack Marker strip, flat

0810876

<https://www.phoenixcontact.com/no/products/0810876>



Zack Marker strip, flat, Strip, white, labeled, printed horizontally: Odd numbers 1 - 19, 21 - 39, etc. up to 81 - 99, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 5.15 x 6.15 mm, Number of individual labels: 10

PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



MPS-MT - Test plug

0201744

<https://www.phoenixcontact.com/no/products/0201744>



Test plug, with solder connection up to 1 mm² conductor cross section, number of positions: 1, color: gray

MPS-IH WH - Insulating sleeve

0201663

<https://www.phoenixcontact.com/no/products/0201663>

Insulating sleeve, color: white



PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



MPS-IH RD - Insulating sleeve

0201676

<https://www.phoenixcontact.com/no/products/0201676>

Insulating sleeve, color: red




MPS-IH BU - Insulating sleeve

0201689

<https://www.phoenixcontact.com/no/products/0201689>

Insulating sleeve, color: blue



PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



MPS-IH YE - Insulating sleeve

0201692

<https://www.phoenixcontact.com/no/products/0201692>

Insulating sleeve, color: yellow



MPS-IH GN - Insulating sleeve

0201702

<https://www.phoenixcontact.com/no/products/0201702>

Insulating sleeve, color: green



PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



MPS-IH GY - Insulating sleeve

0201728

<https://www.phoenixcontact.com/no/products/0201728>

Insulating sleeve, color: gray



MPS-IH BK - Insulating sleeve

0201731

<https://www.phoenixcontact.com/no/products/0201731>

Insulating sleeve, color: black



PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



ISH 4/0,5 - Insulating sleeve

3002885

<https://www.phoenixcontact.com/no/products/3002885>



Insulating sleeve, color: gray

ISH 4/1,0 - Insulating sleeve

3002898

<https://www.phoenixcontact.com/no/products/3002898>



Insulating sleeve, color: black

PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



PAI-4-FIX-5/6 BU - Test adapter

3035975

<https://www.phoenixcontact.com/no/products/3035975>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

PAI-4-FIX-5/6 OG - Test adapter

3035974

<https://www.phoenixcontact.com/no/products/3035974>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



PAI-4-FIX-5/6 YE - Test adapter

3035977

<https://www.phoenixcontact.com/no/products/3035977>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

PAI-4-FIX-5/6 RD - Test adapter

3035976

<https://www.phoenixcontact.com/no/products/3035976>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



PAI-4-FIX-5/6 GN - Test adapter

3035978

<https://www.phoenixcontact.com/no/products/3035978>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

PAI-4-FIX-5/6 BK - Test adapter

3035980

<https://www.phoenixcontact.com/no/products/3035980>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



PAI-4-FIX-5/6 GY - Test adapter

3035982

<https://www.phoenixcontact.com/no/products/3035982>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

PAI-4-FIX-5/6 VT - Test adapter

3035979

<https://www.phoenixcontact.com/no/products/3035979>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



PAI-4-FIX-5/6 BN - Test adapter

3035981

<https://www.phoenixcontact.com/no/products/3035981>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

PAI-4-FIX-5/6 WH - Test adapter

3035983

<https://www.phoenixcontact.com/no/products/3035983>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



PS-6 - Test plug

3030996

<https://www.phoenixcontact.com/no/products/3030996>



Test plug, Modular test plug, number of positions: 1, color: red

PS-6/2,3MM RD - Test plug

3038736

<https://www.phoenixcontact.com/no/products/3038736>



Test plug, number of positions: 1, color: red

PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



TMT 6 R - Marker for terminal blocks

0816498

<https://www.phoenixcontact.com/no/products/0816498>



Marker for terminal blocks, Roll, white, unlabeled, can be labeled with: THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, THERMOMARK S1.1, perforated, mounting type: snapped, snap into flat marker groove, for terminal block width: 6.2 mm, lettering field size: 6.35 x 6.15 mm, Number of individual labels: 16000

TMT 6 R CUS - Marker for terminal blocks

0824488

<https://www.phoenixcontact.com/no/products/0824488>



Marker for terminal blocks, can be ordered: by line, white, labeled according to customer specifications, mounting type: snap into universal marker groove, snap into flat marker groove, for terminal block width: 6.2 mm, lettering field size: 6.35 x 6.15 mm

PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



TMT (EX9,5)R - Marker for terminal blocks

0828295

<https://www.phoenixcontact.com/no/products/0828295>



Marker for terminal blocks, Roll, white, unlabeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting type: snapped, snap into tall marker groove, for terminal block width: 30000 mm, lettering field size: 9.5 x 50000 mm, Number of individual labels: 1

US-TM 100 - Marker for terminal blocks

0829255

<https://www.phoenixcontact.com/no/products/0829255>



Marker for terminal blocks, Card, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, lettering field size: 104 x 9.8 mm, Number of individual labels: 13

PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



SZF 1-0,6X3,5 - Screwdriver

1204517

<https://www.phoenixcontact.com/no/products/1204517>



Actuation tool, for ST terminal blocks, also suitable for use as a bladed screwdriver, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip

ST-BW - Actuation tool

1207608

<https://www.phoenixcontact.com/no/products/1207608>



Actuation tool, for all 2.5 mm² - 4.0 mm² spring-cages

PTMED 4-PE - Ground terminal

3212154

<https://www.phoenixcontact.com/no/products/3212154>



PROJECT COMPLETE - Software

1050453

<https://www.phoenixcontact.com/no/products/1050453>



Intuitive planning and marking software for configuring terminal strips and for professional marking of marking materials for terminal blocks, conductors, cables, devices, and systems. The software is available for download

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT AS

Strømsveien 344

N-1081 Oslo

+47 22 07 68 00

norge@phoenixcontact.com