

https://www.phoenixcontact.com/us/products/3240024



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Ring cable lug, blue, 1.5 ... 2.5 mm<sup>2</sup>, M5

## Your advantages

- The sleeves are conically tapered to facilitate easy and correct insertion of the conductor
- The insulated ring cable lugs with plastic sleeve are hard-soldered and feature the 'EASY ENTRY' system

### Commercial data

Item number	3240024
Packing unit	100 pc
Minimum order quantity	100 pc
Sales key	BH34
Product key	BH3421
Catalog page	Page 492 (C-3-2019)
GTIN	4046356452014
Weight per piece (including packing)	0.964 g
Weight per piece (excluding packing)	0.945 g
Customs tariff number	85369010
Country of origin	CN



https://www.phoenixcontact.com/us/products/3240024



## Technical data

### Product properties

Product type	Connector	
Data management status		
Article revision	00	

## Electrical properties

Fuse	VAS
i use	yes

### **Dimensions**

Dimensional drawing	
Width	9.5 mm
Length of the insulating material sleeve	11 mm
Maximum stripping length	8 mm
Distance from the center to the insulating material sleeve	7.3 mm
Min. material thickness	0.8 mm
Inner dimensions of the insulating collar	4.5 mm
Internal dimensions	
Internal diameter	5.3 mm

### Material specifications

Color	blue
Material	Copper
Flammability rating according to UL 94	V2
Coating	tin-plated
Insulating material	PA
Components	halogen-free

### Environmental and real-life conditions

### Ambient conditions

Optimum ambient temperature (storage/transport)	20.00 °C 50.00 % Humidity (RH), store inside sealed original packaging. Avoid direct sunlight and heat.
Ambient temperature (operation)	-20 °C 105 °C
Ambient temperature (assembly)	-20 °C 100 °C
Short-term temperature	100 °C

### Standards and regulations



https://www.phoenixcontact.com/us/products/3240024



Design according to standard JIS, UL, CSA


3240024


https://www.phoenixcontact.com/us/products/3240024



## Drawings

## Dimensional drawing







https://www.phoenixcontact.com/us/products/3240024



## Classifications

UNSPSC 21.0

### **ECLASS**

I	ECLASS-11.0	27400204
ı	ECLASS-13.0	27400204
I	ECLASS-12.0	27400204
ETIM		
I	ETIM 9.0	EC001052
UNS	PSC	

27121700



https://www.phoenixcontact.com/us/products/3240024



## Environmental product compliance

#### EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com