


CD 120X80 - Cable duct

3240202

<https://www.phoenixcontact.com/za/products/3240202>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable duct for installation and mounting in control cabinets, gray, comprising upper part and mounting base, width: 120 mm, height: 80 mm, length: 2000 mm

Your advantages

- Predetermined breaking point enables tool-free, burr-free removal of bars
- Thanks to its leverage and special cutting geometry, the PPS CD cable duct cutter enables easy, burr-free cutting with minimum effort
- Easy, burr-free cutting with minimum effort using the CUTFOX-CD cable duct cutter
- The wide, diagonal heads of the cable duct bars make it easy to fit the cover and hold it securely in place
- Installed conductors are securely held in place by means of wire retaining clips that can be snapped onto bars on the side
- Plastic body-bound rivets enable easy fixing of cable ducts using the rivet setting tool

Commercial data

Item number	3240202
Packing unit	8 pc
Minimum order quantity	1 pc
Sales key	032
Product key	BE7431
Catalog page	Page 581 (C-3-2019)
GTIN	4046356459266
Weight per piece (including packing)	2 687,5 g
Weight per piece (excluding packing)	2 687,5 g
Customs tariff number	39259020
Country of origin	DE

CD 120X80 - Cable duct

3240202

<https://www.phoenixcontact.com/za/products/3240202>



Technical data


Product properties

Product type	Wiring duct
--------------	-------------

Connection data

Nominal cross section	6737 mm²
-----------------------	----------

Dimensions

Dimensional drawing	
Width	120 mm
Height	2000 mm
Depth	80 mm
Length	2000 mm

Material specifications

Color	gray
Material	PVC
Flammability rating according to UL 94	V0
Components	Lead-free

Cable/line

Halogen-free	no
--------------	----

Environmental and real-life conditions

Ambient conditions	
Ambient temperature (operation)	-5 °C ... 60 °C


CD 120X80 - Cable duct

3240202

<https://www.phoenixcontact.com/za/products/3240202>



Drawings



Base perforation according to DIN EN 50085

CD 120X80 - Cable duct



3240202

<https://www.phoenixcontact.com/za/products/3240202>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/za/products/3240202>



VDE Zeichengenehmigung

Approval ID: 40058456



cULus Recognized

Approval ID: E328576



cCSAus

Approval ID: 80202282

CD 120X80 - Cable duct

3240202

<https://www.phoenixcontact.com/za/products/3240202>



Classifications

ECLASS

ECLASS-11.0	27400703
ECLASS-12.0	27400703
ECLASS-13.0	27400703

ETIM

ETIM 9.0	EC000012
----------	----------

UNSPSC

UNSPSC 21.0	39131700
-------------	----------

CD 120X80 - Cable duct



3240202
<https://www.phoenixcontact.com/za/products/3240202>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT (Pty) Ltd.
36 Lyn Road P.O. Box 916 ZA-Ferndale 2160

+27/11/801-8200
info@phoenixcontact.co.za