

3240680

https://www.phoenixcontact.com/us/products/3240680

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Protective hose, material: PA 6, UV-resistant: yes, flexible, degree of protection: IP68, color: black, flammability rating in acc. with UL 94: V0, inner diameter: 7 mm, Total length: 50 m

Commercial data

Item number	3240680
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF68
Product key	BF7DSA
Catalog page	Page 585 (C-3-2019)
GTIN	4046356736473
Weight per piece (including packing)	3,160 g
Weight per piece (excluding packing)	3,160 g
Customs tariff number	39173200
Country of origin	DE



3240680

https://www.phoenixcontact.com/us/products/3240680

Technical data

Notes

General	Protective hose length is measured stretched out; length tolerance ±5%
General	UV-resistant

Product properties

Product type	Corrugated pipe
Tensile strength GRP	100 N

Dimensions

External dimensions

Outside diameter	10 mm	
Internal dimensions		
Internal diameter	6.5 mm	

Material specifications

Material	PA 6
Flammability rating according to UL 94	V0
Components	free from silicone, halogen, and cadmium

Cable/line

Bending radius, dynamic	35 mm
Bending radius, static	13 mm
Tensile strength	100 N
Halogen-free	yes

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP68
	IP69K
Ambient temperature (operation)	-40 °C 120 °C
Resistance to UV radiation	yes
Short-term temperature	150 °C

Standards and regulations

Resistance to UV radiation	yes



3240680

https://www.phoenixcontact.com/us/products/3240680

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/3240680



UL Recognized



LR



VDE Zeichengenehmigung

DNV

Approval ID: TAE0000188_Rev-1



3240680

https://www.phoenixcontact.com/us/products/3240680

Classifications

UNSPSC 21.0

ECLASS

	ECLASS-11.0	27430304
	ECLASS-13.0	27430304
	ECLASS-12.0	27430304
ETIM		
	ETIM 9.0	EC001177
UNSPSC		

40141700



3240680

https://www.phoenixcontact.com/us/products/3240680

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values



3240680

https://www.phoenixcontact.com/us/products/3240680

Accessories

WP-EC TPE HF 10,0 BK - Transition sleeve from hose to cable

3240974

https://www.phoenixcontact.com/us/products/3240974



Transition sleeve from hose to cable, material: TPE, color: black, flammability rating in acc. with UL 94: HB

WP-SC PA HF 10,0 BK - Cable protection end sleeve

3240981

https://www.phoenixcontact.com/us/products/3240981



Cable protection end sleeve, material: PA 6, color: black, flammability rating in acc. with UL 94: V2, inner diameter: 4 mm



3240680

https://www.phoenixcontact.com/us/products/3240680

WP-G HF IP66 PG7 BK - Screw connection

3240888

https://www.phoenixcontact.com/us/products/3240888



Cable gland, Pg thread, IP66 protection, straight

WP-G HF IP66 M10 BK - Screw connection

3240895

https://www.phoenixcontact.com/us/products/3240895



Cable gland, metric thread, IP66 protection, straight



3240680

https://www.phoenixcontact.com/us/products/3240680

WP-G HF IP69K PG7 BK - Screw connection

3240874

https://www.phoenixcontact.com/us/products/3240874



Cable gland, Pg thread, IP68/69k protection, straight

WP-G HF IP69K M10 BK - Screw connection

3240881

https://www.phoenixcontact.com/us/products/3240881



Cable gland, metric thread, IP68/69k protection, straight



3240680

https://www.phoenixcontact.com/us/products/3240680

WP-GA HF IP66 PG7 BK - Screw connection

3240916

https://www.phoenixcontact.com/us/products/3240916

Cable gland, Pg thread, IP66 protection, angled



WP-GA HF IP66 M10 BK - Screw connection

3240923

https://www.phoenixcontact.com/us/products/3240923

Cable gland, metric thread, IP66 protection, angled





3240680

https://www.phoenixcontact.com/us/products/3240680

WP-GA HF IP69K PG7 BK - Screw connection

3240902

https://www.phoenixcontact.com/us/products/3240902

Cable gland, Pg thread, IP68/69k protection, angled



WP-GA HF IP69K M10 BK - Screw connection

3240909

https://www.phoenixcontact.com/us/products/3240909

Cable gland, metric thread, IP68/69k protection, angled





3240680

https://www.phoenixcontact.com/us/products/3240680

WP-GR HF IP66 PG7 BK - Screw connection

3240944

https://www.phoenixcontact.com/us/products/3240944



Cable gland, Pg thread, IP66 protection, with strain relief

WP-GR HF IP69K PG7 BK - Screw connection

3240930

https://www.phoenixcontact.com/us/products/3240930



Cable gland, Pg thread, IP68/69k protection, with strain relief



3240680

https://www.phoenixcontact.com/us/products/3240680

WP-BASE C PA HF 10,0 BK - Hose holder with cover

3240958

https://www.phoenixcontact.com/us/products/3240958



Hose holder with cover, material: PA, color: black, flammability rating in acc. with UL 94: V2

WP-BASE HF 9-10 - Hose clamp

3240965

https://www.phoenixcontact.com/us/products/3240965



Hose clamp, material: Steel, galvanized, color: black/silver

Mar 28, 2024, 9:25 AM Page 12 (13)



3240680

https://www.phoenixcontact.com/us/products/3240680

WP-GR HF IP66 M12 BK - Screw connection

3240952

https://www.phoenixcontact.com/us/products/3240952



Cable gland, metric thread, IP66 protection, with strain relief

WP-GR HF IP69K M12 BK - Screw connection

3240938

https://www.phoenixcontact.com/us/products/3240938



Cable gland, metric thread, IP68/69k protection, with strain relief

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com