3240796

https://www.phoenixcontact.com/gb/products/3240796

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable binders for quick and secure fastening, can be detected using metallic pigments

Commercial data

Item number	3240796
Packing unit	100 pc
Minimum order quantity	100 pc
Sales key	BE7131
Product key	BE7131
Catalog page	Page 619 (C-3-2019)
GTIN	4046356705240
Weight per piece (including packing)	1.073 g
Weight per piece (excluding packing)	0.99 g
Customs tariff number	39269097
Country of origin	IT

PHŒNIX

3240796

https://www.phoenixcontact.com/gb/products/3240796



Technical data

Product properties

Type Internal teeth	
Tensile strength GRP 130 N	

Dimensions

Width	3.5 mm
Length	200 mm

Material specifications

Material PA 6.6 Flammability rating according to UL 94 V2 Components free from silicone and halogen	Color	blue
	Material	PA 6.6
Components free from silicone and halogen	Flammability rating according to UL 94	V2
	Components	free from silicone and halogen

Cable/line

External cable diameter	2 mm 50 mm
Tensile strength	130 N

Environmental and real-life conditions

Optimum ambient temperature (storage/transport)	23.00 °C 50.00 % Polyamide 6.6 has pronounced hygroscopic properties. It absorbs or releases water in accordance with the level of humidity within its environment. Its properties are ideal when the percentage of water is 2 - 3%. The packaging, which is tailored specifically to the product concerned, contains the optimum level of moisture. To ensure that the ideal properties are maintained, the following points should be observed during storage: Keep product stored inside sealed original packaging, carry out any product processing soon after breaking open the packaging, avoid direct sunlight, avoid direct heat.
Ambient temperature (operation)	-40 °C 85 °C
Ambient temperature (assembly)	-10 °C 60 °C
Resistance to UV radiation	no
Short-term temperature	110 °C

Mounting

Mounting type	Cannot be removed
mounting type	

3240796

https://www.phoenixcontact.com/gb/products/3240796



Classifications

ECLASS

ECLASS-11.0	27140702
ECLASS-12.0	27140702
ECLASS-13.0	27140702

ETIM

	ETIM 9.0	EC000046
UN	ISPSC	
	UNSPSC 21.0	39121700

3240796

https://www.phoenixcontact.com/gb/products/3240796



Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions	
China RoHS		
Environment friendly use period (EFUP)	EFUP-E	
	No hazardous substances above the limits	
EU REACH SVHC		
REACH candidate substance (CAS No.)	No substance above 0.1 wt%	

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT Ltd Halesfield 13, Telford Shropshire, TF7 4PG 01952 681700 info@phoenixcontact.co.uk