

3260148

<https://www.phoenixcontact.com/za/products/3260148>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Pick-off terminal block, nom. voltage: 1500 V, nominal current: 57 A, number of connections: 2, connection method: Push-in connection, 1 level, Rated cross section: 10 mm², cross section: 0.5 mm² - 16 mm², mounting type: on base element, color: blue

Your advantages

- Large-surface marking
- The fully insulated, optionally used pick-off terminal block enables voltage pick-off
- Pick-off terminal block, for snapping into the side insertion funnel

Commercial data

Item number	3260148
Packing unit	10 pc
Minimum order quantity	1 pc
Sales key	BE2
Product key	BE2ZWX
Catalog page	Page 136 (C-1-2019)
GTIN	4046356779081
Weight per piece (including packing)	23,118 g
Weight per piece (excluding packing)	22,6 g
Customs tariff number	85369010
Country of origin	PL

AGK 10-PTPOWER BU - Pick-off terminal block



3260148

<https://www.phoenixcontact.com/za/products/3260148>

Technical data

Notes

General	For use with PTPOWER 50, 95, 150, and 185 PowerTurn high-current terminal blocks
---------	--

Product properties

Product type	Pick-off terminal
Number of connections	2
Number of rows	1
Potentials	1

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Electrical properties

Rated surge voltage	8 kV
Maximum power dissipation for nominal condition	1.82 W

Connection data

Number of connections per level	2
Nominal cross section	10 mm ²

1 level

Stripping length	18 mm
Internal cylindrical gage	A6
Conductor cross section rigid	0.5 mm ² ... 16 mm ²
Cross section AWG	20 ... 6 (converted acc. to IEC)
Conductor cross section flexible	0.5 mm ² ... 10 mm ²
Conductor cross section, flexible [AWG]	20 ... 8 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve)	0.5 mm ² ... 10 mm ²
Flexible conductor cross section (ferrule with plastic sleeve)	0.5 mm ² ... 10 mm ²
Conductor cross-section flexible (2 conductors with the same cross-section, with TWIN ferrule and plastic sleeve)	0.5 mm ² ... 4 mm ²
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve	1.5 mm ² ... 4 mm ²
Nominal current	57 A
Maximum load current	57 A (The maximum load current must not be exceeded by the total current of all connected conductors.)
Nominal voltage	1500 V
Nominal cross section	10 mm ²

1 level Connection cross sections directly pluggable

Conductor cross section rigid	1 mm ² ... 16 mm ²
Conductor cross-section flexible (ferrule without plastic sleeve)	4 mm ² ... 10 mm ²

AGK 10-PTPOWER BU - Pick-off terminal block



3260148

<https://www.phoenixcontact.com/za/products/3260148>

Flexible conductor cross section (ferrule with plastic sleeve)	2.5 mm ² ... 10 mm ²
--	--

Ex data

Rated data (ATEX/IECEX)

Identification	Ex II 2 GD Ex eb IIC Gb
Operating temperature range	-60 °C ... 110 °C
Ex-certified accessories	1204517 SZF 1-0,6X3,5
Ex temperature increase	40 K (51 A / 10 mm ²)
Rated voltage	1100 V
Rated insulation voltage	1000 V
output	(Permanent)

Ex level General

Rated current	50 A
Maximum load current	50 A
Contact resistance	1.05 mΩ

Ex connection data General

Ferrule length	18 mm
Stripping length	18 mm
Nominal cross section	10 mm ²
Rated cross section AWG	6
Connection capacity rigid	0.5 mm ² ... 16 mm ²
Connection capacity AWG	20 ... 6
Conductor cross section flexible, with ferrule without plastic sleeve min.	1.5 mm ²
Conductor cross section flexible, with ferrule without plastic sleeve max.	10 mm ²
Single conductor/terminal point, flexible, with ferrule, without plastic sleeve, AWG	20 ... 8

Dimensions

Width	18.5 mm
Height	35 mm
Depth	34.7 mm

Material specifications

Color	blue
Flammability rating according to UL 94	V0
Insulating material group	I
Insulating material	PA
Static insulating material application in cold	-60 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	125 °C
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3

AGK 10-PTPOWER BU - Pick-off terminal block



3260148

<https://www.phoenixcontact.com/za/products/3260148>

Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3
Calorimetric heat release NFPA 130 (ASTM E 1354)	27,5 MJ/kg
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed

Mechanical properties

Mechanical data

Open side panel	No
-----------------	----

Environmental and real-life conditions

Ambient conditions

Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (storage/transport)	30 % ... 70 %

Mounting

Mounting type	on base element
---------------	-----------------

AGK 10-PTPOWER BU - Pick-off terminal block



3260148

<https://www.phoenixcontact.com/za/products/3260148>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/za/products/3260148>



CSA

Approval ID: 13631



cUL Recognized

Approval ID: E60425

	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
Use group C				
	1000 V	57 A	20 - 6	-



UL Recognized

Approval ID: E60425

	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
Use group E				
	1000 V	57 A	20 - 6	-



EAC

Approval ID: RU C-DE.BL08.B.00644



CSA

Approval ID: 13631



EAC Ex

Approval ID: RU C-DE.Ax07.B.03227



IEC Ex

Approval ID: IECExSEV14.0013U



ATEX

Approval ID: SEV14ATEX0156U

	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
Only rigid conductors	1100 V	50 A	-	0.5 - 16
multi-stranded with ferrule	1100 V	50 A	-	0.5 - 10



CCC

AGK 10-PTPOWER BU - Pick-off terminal block



3260148

<https://www.phoenixcontact.com/za/products/3260148>

Approval ID: 2020322313000630



UKCA-EX

Approval ID: CML 22UKEX1227U



IECEx

Approval ID: IECExSEV14.0013U

cULus Recognized

AGK 10-PTPOWER BU - Pick-off terminal block



3260148

<https://www.phoenixcontact.com/za/products/3260148>

Classifications

ECLASS

ECLASS-11.0	27141151
ECLASS-12.0	27141151
ECLASS-13.0	27250308

ETIM

ETIM 9.0	EC000897
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

AGK 10-PTPOWER BU - Pick-off terminal block



3260148

<https://www.phoenixcontact.com/za/products/3260148>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT (Pty) Ltd.
36 Lyn Road P.O. Box 916 ZA-Ferndale 2160

+27/11/801-8200
info@phoenixcontact.co.za