

# PTMC 1,5-2 /BK - Marshalling patchboard



3270434

<https://www.phoenixcontact.com/pc/products/3270434>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Marshalling patchboard, nom. voltage: 500 V, nominal current: 17.5 A, connection method: Push-in connection, cross section: 0.14 mm<sup>2</sup> - 2.5 mm<sup>2</sup>, mounting: for snapping onto a DIN rail adapter, for snapping onto a cover flange, color: gray, color of connection elements: black

## Your advantages

- Tool-free wiring in a confined space thanks to compact size
- Color configuration possible according to VDE 0812, VDE 0815, DIN 47100 or unlimited.
- Individual setup thanks to modular principle
- High contact quality thanks to push-in technology as a replacement for Wire-Wrap®, TERMI-POINT®, etc.
- Individual color assignment of cable and terminal point to ensure error-free, safe operation
- Suitable for DIN rail mounting and panel cutouts with corresponding accessories

## Commercial data

|                                      |                    |
|--------------------------------------|--------------------|
| Item number                          | 3270434            |
| Packing unit                         | 10 pc              |
| Minimum order quantity               | 10 pc              |
| Product key                          | BE6212             |
| Catalog page                         | Page 57 (C-1-2019) |
| GTIN                                 | 4055626114187      |
| Weight per piece (including packing) | 3.14 g             |
| Weight per piece (excluding packing) | 3.05 g             |
| Customs tariff number                | 85369010           |
| Country of origin                    | PL                 |

# PTMC 1,5-2 /BK - Marshalling patchboard



3270434

<https://www.phoenixcontact.com/pc/products/3270434>

## Technical data

### Product properties

|                       |                      |
|-----------------------|----------------------|
| Product type          | Marshalling terminal |
| Number of positions   | 1                    |
| Number of connections | 4                    |
| Number of rows        | 1                    |

### Data management status

|                  |    |
|------------------|----|
| Article revision | 02 |
|------------------|----|

### Insulation characteristics

|                      |     |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution  | 3   |

### Electrical properties

|                                                 |        |
|-------------------------------------------------|--------|
| Rated surge voltage                             | 6 kV   |
| Maximum power dissipation for nominal condition | 0.56 W |

### Connection data

|                                                                   |                                                                                                                                                                  |
|-------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Number of connections per level                                   | 4                                                                                                                                                                |
| Nominal cross section                                             | 1.5 mm <sup>2</sup>                                                                                                                                              |
| Rated cross section AWG                                           | 14                                                                                                                                                               |
| Stripping length                                                  | 8 mm ... 10 mm                                                                                                                                                   |
| Internal cylindrical gage                                         | A1                                                                                                                                                               |
| Connection in acc. with standard                                  | IEC 60947-7-1                                                                                                                                                    |
| Conductor cross section rigid                                     | 0.14 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>                                                                                                                     |
| Cross section AWG                                                 | 26 ... 14 (converted acc. to IEC)                                                                                                                                |
| Conductor cross section flexible                                  | 0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>                                                                                                                     |
| Conductor cross section, flexible [AWG]                           | 26 ... 16 (converted acc. to IEC)                                                                                                                                |
| Conductor cross-section flexible (ferrule without plastic sleeve) | 0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>                                                                                                                     |
| Flexible conductor cross section (ferrule with plastic sleeve)    | 0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>                                                                                                                     |
| Nominal current                                                   | 17.5 A                                                                                                                                                           |
| Maximum load current                                              | 24 A (in case of a 2.5 mm <sup>2</sup> conductor cross section, the maximum load current must not be exceeded by the total current of all connected conductors.) |
| Nominal voltage                                                   | 500 V                                                                                                                                                            |

### Connection cross sections directly pluggable

|                                                                   |                                              |
|-------------------------------------------------------------------|----------------------------------------------|
| Conductor cross section rigid                                     | 0.34 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> |
| Conductor cross section, rigid [AWG]                              | 20 ... 14 (converted acc. to IEC)            |
| Conductor cross-section flexible (ferrule without plastic sleeve) | 0.34 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> |
| Flexible conductor cross section (ferrule with plastic sleeve)    | 0.34 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> |

## Dimensions

# PTMC 1,5-2 /BK - Marshalling patchboard



3270434

<https://www.phoenixcontact.com/pc/products/3270434>

|        |        |
|--------|--------|
| Width  | 11 mm  |
| Height | 8.6 mm |
| Depth  | 30 mm  |

## Material specifications

|                                                                         |                 |
|-------------------------------------------------------------------------|-----------------|
| Color                                                                   | gray (RAL 7042) |
| Color of connection elements                                            | black           |
| Flammability rating according to UL 94                                  | V0              |
| Insulating material group                                               | I               |
| Insulating material                                                     | PA              |
| Static insulating material application in cold                          | -60 °C          |
| Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) | 125 °C          |
| Relative insulation material temperature index (Elec., UL 746 B)        | 130 °C          |
| Fire protection for rail vehicles (DIN EN 45545-2) R22                  | HL 1 - HL 3     |
| Fire protection for rail vehicles (DIN EN 45545-2) R23                  | HL 1 - HL 3     |
| Fire protection for rail vehicles (DIN EN 45545-2) R24                  | HL 1 - HL 3     |
| Fire protection for rail vehicles (DIN EN 45545-2) R26                  | HL 1 - HL 3     |
| Calorimetric heat release NFPA 130 (ASTM E 1354)                        | 27,5 MJ/kg      |
| Surface flammability NFPA 130 (ASTM E 162)                              | passed          |
| Specific optical density of smoke NFPA 130 (ASTM E 662)                 | passed          |
| Smoke gas toxicity NFPA 130 (SMP 800C)                                  | passed          |

## Electrical tests

### Surge voltage test

|                       |             |
|-----------------------|-------------|
| Test voltage setpoint | 7.3 kV      |
| Result                | Test passed |

### Temperature-rise test

|                                                  |                                     |
|--------------------------------------------------|-------------------------------------|
| Requirement temperature-rise test                | Increase in temperature $\leq 45$ K |
| Result                                           | Test passed                         |
| Short-time withstand current 1.5 mm <sup>2</sup> | 0.18 kA                             |
| Short-time withstand current 2.5 mm <sup>2</sup> | 0.3 kA                              |
| Result                                           | Test passed                         |

### Power-frequency withstand voltage

|                       |             |
|-----------------------|-------------|
| Test voltage setpoint | 1.89 kV     |
| Result                | Test passed |

## Mechanical properties

### Mechanical data

|                 |    |
|-----------------|----|
| Open side panel | No |
|-----------------|----|

## Mechanical tests

# PTMC 1,5-2 /BK - Marshalling patchboard



3270434

<https://www.phoenixcontact.com/pc/products/3270434>

## Mechanical strength

|        |             |
|--------|-------------|
| Result | Test passed |
|--------|-------------|

## Attachment on the carrier

|                         |             |
|-------------------------|-------------|
| DIN rail/fixing support | NS 35       |
| Test force setpoint     | 1 N         |
| Result                  | Test passed |

## Test for conductor damage and slackening

|                                |                               |
|--------------------------------|-------------------------------|
| Rotation speed                 | 10 rpm                        |
| Revolutions                    | 135                           |
| Conductor cross section/weight | 0.14 mm <sup>2</sup> / 0.2 kg |
|                                | 1.5 mm <sup>2</sup> / 0.4 kg  |
|                                | 2.5 mm <sup>2</sup> / 0.7 kg  |
| Result                         | Test passed                   |

## Environmental and real-life conditions

### Aging

|                    |             |
|--------------------|-------------|
| Temperature cycles | 192         |
| Result             | Test passed |

### Needle-flame test

|                  |             |
|------------------|-------------|
| Time of exposure | 30 s        |
| Result           | Test passed |

### Oscillation/broadband noise

|                        |                                                     |
|------------------------|-----------------------------------------------------|
| Specification          | DIN EN 50155 (VDE 0115-200):2008-03                 |
| Spectrum               | Service life test category 1, class B, body mounted |
| Frequency              | $f_1 = 5 \text{ Hz}$ to $f_2 = 150 \text{ Hz}$      |
| ASD level              | 0.964 (m/s <sup>2</sup> )/Hz                        |
| Acceleration           | 0.58g                                               |
| Test duration per axis | 5 h                                                 |
| Test directions        | X-, Y- and Z-axis                                   |
| Result                 | Test passed                                         |

### Shocks

|                                |                                     |
|--------------------------------|-------------------------------------|
| Specification                  | DIN EN 50155 (VDE 0115-200):2008-03 |
| Pulse shape                    | Half-sine                           |
| Acceleration                   | 5g                                  |
| Shock duration                 | 30 ms                               |
| Number of shocks per direction | 3                                   |
| Test directions                | X-, Y- and Z-axis (pos. and neg.)   |
| Result                         | Test passed                         |

### Ambient conditions

|                                 |                                                               |
|---------------------------------|---------------------------------------------------------------|
| Ambient temperature (operation) | -60 °C ... 105 °C (max. short-term operating temperature RTI) |
|---------------------------------|---------------------------------------------------------------|

# PTMC 1,5-2 /BK - Marshalling patchboard



3270434

<https://www.phoenixcontact.com/pc/products/3270434>

|                                          |                                                                           |
|------------------------------------------|---------------------------------------------------------------------------|
|                                          | Elec.)                                                                    |
| Ambient temperature (storage/transport)  | -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C) |
| Ambient temperature (assembly)           | -5 °C ... 70 °C                                                           |
| Ambient temperature (actuation)          | -5 °C ... 70 °C                                                           |
| Permissible humidity (storage/transport) | 30 % ... 70 %                                                             |

## Standards and regulations

|                                  |               |
|----------------------------------|---------------|
| Connection in acc. with standard | IEC 60947-7-1 |
|----------------------------------|---------------|

## Mounting

|               |                                      |
|---------------|--------------------------------------|
| Mounting type | for snapping onto a DIN rail adapter |
|               | for snapping onto a cover flange     |

# PTMC 1,5-2 /BK - Marshalling patchboard

3270434

<https://www.phoenixcontact.com/pc/products/3270434>



## Drawings

### Circuit diagram



# PTMC 1,5-2 /BK - Marshalling patchboard



3270434

<https://www.phoenixcontact.com/pc/products/3270434>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/3270434>

|  <b>CSA</b><br>Approval ID: 13631 |                       |                       |                   |                             |
|--------------------------------------------------------------------------------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|                                                                                                                    | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
| Use group B                                                                                                        | 300 V                 | 10 A                  | 24 - 16           | -                           |
| Use group C                                                                                                        | 300 V                 | 10 A                  | 24 - 16           | -                           |
| Use group D                                                                                                        | 300 V                 | 10 A                  | 24 - 16           | -                           |

|  <b>EAC</b><br>Approval ID: RU C-DE.BL08.B.00682 |  |  |  |  |
|-----------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|
|-----------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|

|  <b>cULus Recognized</b><br>Approval ID: E60425 |                       |                       |                   |                             |
|------------------------------------------------------------------------------------------------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|                                                                                                                                    | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
| Use group B                                                                                                                        | 300 V                 | 10 A                  | 24 - 16           | -                           |
| Use group C                                                                                                                        | 300 V                 | 10 A                  | 24 - 16           | -                           |

# PTMC 1,5-2 /BK - Marshalling patchboard



3270434

<https://www.phoenixcontact.com/pc/products/3270434>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27141120 |
| ECLASS-13.0 | 27250106 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC000897 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|



# PTMC 1,5-2 /BK - Marshalling patchboard



3270434

<https://www.phoenixcontact.com/pc/products/3270434>

## Environmental product compliance

|                                         |                                          |
|-----------------------------------------|------------------------------------------|
| EU RoHS                                 |                                          |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |
| China RoHS                              |                                          |
| Environment friendly use period (EFUP)  | EFUP-E                                   |
|                                         | No hazardous substances above the limits |
| EU REACH SVHC                           |                                          |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachmarktstraße 8  
D-32825 Blomberg  
+49 (0) 5235-3 00  
[info@phoenixcontact.com](mailto:info@phoenixcontact.com)