



PRODUCT-DETAILS

3750DP
30A,PLG,2P3W,FD,600VAC,SPEC



General Information

Extended Product Type	3750DP
Product ID	7TAA057630R0000
EAN	5414363141686
Catalog Description	30A,PLG,2P3W,FD,600VAC,SPEC
Long Description	FD 30 Amp. Plug, 2 Pole 3 Wire, 600VAC, Special

Ordering

EAN	5414363141686
UPC	708917176381
Country of Origin	Mexico
Selling Unit of Measure	each

Container Information

Package Level 1 Units	1 EA
Package Level 1 Width	95.25 mm 3.75 in
Package Level 1 Height	101.6 mm

	4 in
Package Level 1 Depth / Length	171.45 mm 6.75 in
Package Level 2 Units	32 EA
Package Level 2 Width	342.9 mm 13.5 in
Package Level 2 Height	419.1 mm 16.5 in
Package Level 2 Depth / Length	342.9 mm 13.5 in

Additional Information

Application	Designed for lower-ameprage marine and rough service applications with rugged die cast aluminum housings and epoxy powder coated finishes.
Brand / Label	Russellstoll
Current Rating	30 A
Effective Date	19960411
Material	Non-metallic
Number of Conductors	3
Number of Poles	2P
Product Name	ELECTRICAL APPARATUS FOR SWITCHING OR PROTECTING ELECTRICAL CIRCUITS, OR FOR MAKING CONNECTION TO/ IN ELECTRICAL CIRCUIT
Product Type	FS/FD Metallic Connections Systems
Special Functions	Precision-made, self-aligning and self-wiping contacts, receptacles provided with spring-actuated, self-closing flaps, available in watertight and weathertight versions, solderless screw terminals for convenient wiring
Standards	UL e2630
Voltage Rating	600 V

Certificates and Declarations

Data Sheet, Technical Information	3750DP
-----------------------------------	--------

External Classifications and Standards

ETIM 7	EC001322 - Round socket/plug for high currents
ETIM 8	EC001322 - Round socket/plug for high currents
UNSPSC	39121404
IDEA Granular Category Code (IGCC)	4528 >> Electrical sleeves

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Pin & Sleeve Connectors

