

39978503

General Information

Extended Product Type:	D4/8.SF.I.ADO
Product ID:	1SNA399785R0300
EAN:	3472593997857
Catalog Description:	D4/8.SF.I.ADO IDC Terminal Blocks - For 5 x 20 and 5 x 25 fuses - with test socket ADO - screw clamp - Grey
Long Description:	D4/8.SF.I.ADO IDC Terminal Blocks - Fuse - Grey, 1.5mm ² RatedCrossSection, 8mm Spacing TH 35-7.5, TH 35-15 Rail



Categories

Products » Low Voltage Products and Systems » Connection Devices »
Terminal Blocks » IDC Terminal Blocks

Ordering

EAN:	3472593997857
Minimum Order Quantity:	50 piece
Customs Tariff Number:	85361010

Dimensions

Product Net Width:	8.0 mm
Product Net Height:	68.2 mm
Product Net Depth:	40.9 mm
Product Net Weight:	13.00 g

Container Information

Package Level 1 Units:	50 piece
Package Level 1 Width:	75 mm
Package Level 1 Height:	107 mm
Package Level 1 Length:	225 mm
Package Level 1 Gross Weight:	0.65000 kg
Package Level 1 EAN:	3472593997857
Package Level 2 Units:	700 piece
Package Level 2 Width:	300 mm
Package Level 2 Height:	300 mm
Package Level 2 Length:	500 mm
Package Level 2 Gross Weight:	9.6 kg
Package Level 3 Units:	16800 piece
Product Packing Type:	Box

Environmental

RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
---------------------	-----------------------------------------------------------------

Technical UL/CSA

Connecting Capacity-Main Circuit UL/CSA:	Screw Clamp / Flexible 1x 22-10 AWG
-------------------------------------------------	-------------------------------------

Flammability According to UL94: V0

Additional Information

Color:	Grey
Connecting Capacity-Main Circuit:	Screw Clamp / Flexible 1x 0.22-4 mm ² Screw Clamp / Rigid 1x 0.2-4 mm ²
Connection Type:	Screw clamp - ADO System
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Function:	Fuse
Gauge Type:	A4
IIT Publishing Status:	Level 0 - Information enabled
Mounting on DIN Rail:	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Number of Levels:	1
Pollution Degree:	3
Product Main Type:	D4/8.SF.I.ADO
Product Name:	Terminal block
Rated Cross-Section:	1.5 mm ²
Rated Current (I_n):	Main Circuit 6.3 A
Rated Impulse Withstand Voltage (U_{imp}):	8000 V
Rated Short-time Withstand Current (I_{cw}):	for 1.0s 180 A
Rated Voltage (U_r):	630 V
Recommended Screw Driver:	4 mm
Spacing:	8 mm
Sub-Function:	for 5x20 and 5x25 Fuses
Wire Stripping Length:	9.5 mm

Certificates and Declarations (Document Number)

Declaration of Conformity - CE:	1SND225014C1005
GOST Certificate:	1SND161005A1104
RoHS Information:	1SND230472F0201

Classifications

ETIM 4.0:	EC000899 - Fuse terminal block
ETIM 5.0:	EC000899 - Fuse terminal block
Object Classification Code:	X